

ARTIFICIAL INTELLIGENCE IN ORAL MEDICINE AND RADIOLOGY



Dr. Bhanu Teja Pallagani
Dr. M. Srinivasa Raju
Dr. Mrudula Raju B
Dr. Myla Swathi



SAN INTERNATIONAL
SCIENTIFIC PUBLICATIONS

Artificial Intelligence in Oral Medicine and Radiology

Authors

Dr. Bhanu Teja Pallagani

Department of Oral Medicine & Radiology
St. Joseph Dental College
Duggirala, Eluru district, Andhra Pradesh, India

Dr. M. Srinivasa Raju

Professor and Head
Department of Oral Medicine & Radiology
St. Joseph Dental College
Duggirala, Eluru district, Andhra Pradesh, India

Dr. Mrudula Raju B

Professor
Department of Oral Medicine & Radiology
St. Joseph Dental College
Duggirala, Eluru district, Andhra Pradesh, India

Dr. Myla Swathi

Reader
Department of Oral Medicine & Radiology
St. Joseph Dental College
Duggirala, Eluru district, Andhra Pradesh, India



SAN INTERNATIONAL
SCIENTIFIC PUBLICATIONS

Copyright © 2026 by the Authors

All rights reserved.

This book and its contents are protected under the Indian Copyright Act, 1957, as amended. No part of this publication may be reproduced, stored, transmitted, or distributed in any form or by any means—electronic, mechanical, photocopying, recording, scanning, or otherwise—without the prior written permission of the author and publisher, except as permitted under Sections 52 and other applicable provisions of the Act.

Copyright Statement

The copyright of the book content remains with the author(s). The copyright of the compilation, editorial matter, and overall layout is held by the publisher.

Publisher Information

Published by:

San International Scientific Publications

Chennai – 600127, Tamil Nadu, India

Email: editor@nobelonline.in

Website: sanpublications.nobelonline.in

Book Details

Title: Artificial Intelligence in Oral Medicine and Radiology

Authors: Dr. Bhanu Teja Pallagani, Dr. M. Srinivasa Raju, Dr. Mrudula Raju B, and Dr. Myla Swathi

ISBN: 978-81-69857-22-2

DOI: <https://doi.org/10.59646/780>

Edition 1: July 27, 2026

Price: ₹500 /- (India)

Printed and bound in India

Fair Use Notice

This publication has been prepared solely for educational, academic, research, knowledge-transfer, and personal study purposes and is not intended for commercial use. Brief excerpts may be used for education, research, review, criticism, or other scholarly purposes with proper acknowledgment, in accordance with the provisions of the Indian Copyright Act, 1957.

Acknowledgement

The completion of this book stands as a testament to the guidance, encouragement, and goodwill of many individuals, to whom I owe a profound debt of gratitude.

I am deeply indebted to my guide, Dr. M. Srinivasa Raju, Professor and Head of the Department, Department of Oral Medicine and Radiology, St. Joseph Dental College & Hospital, Eluru, for his exemplary guidance, unfailing support, and sharp professional insight. His invaluable assistance, coupled with his constructive criticism, shaped this work at every stage of its preparation.

I wish to express my heartfelt appreciation to my esteemed teachers, Dr. Mrudula Raj, Professor, and Dr. M. Swathi, Reader, Department of Oral Medicine and Radiology, St. Joseph Dental College & Hospital, Eluru, whose wisdom, patience, and generous mentorship have left an indelible mark on my academic journey. Their astute insights and unwavering encouragement have been instrumental in bringing this dissertation book to fruition.

I am equally grateful to my batchmate and seniors, whose camaraderie, wisdom, and moral support enriched this endeavour and made the journey a truly memorable one.

My sincere thanks go to our Principal, Dr. N. Sleeva Raju, and management for graciously granting permission to utilize the outstanding facilities of St. Joseph Dental College & Hospital, Eluru, without which this work would not have been possible.

Above all, I owe an immeasurable debt of gratitude to my parents, grandparents, and friends, whose boundless love, patience, and unwavering faith in me have been the true foundation of this achievement. It is to them that I dedicate this work, with heartfelt reverence and love.

This book is based on the dissertation submitted to Dr. NTR University of Health Sciences (Dr. NTRUHS) in partial fulfilment of the requirements for the degree of Master of Dental Surgery (MDS) in Oral Medicine and Radiology.

With regards,

Dr. Pallagani Bhanu Teja

Preface

Artificial Intelligence (AI) is transforming healthcare by enabling faster, more accurate, and data-driven clinical decision-making. In dentistry, particularly in Oral Medicine and Oral Radiology, AI has become an invaluable tool for enhancing diagnostic accuracy, interpreting radiographic images, detecting oral diseases at an early stage, supporting treatment planning, and improving patient care. The integration of machine learning, deep learning, and computer vision technologies is reshaping traditional dental practices and paving the way for precision dentistry.

Artificial Intelligence in Oral Medicine and Radiology has been designed to provide students, academicians, researchers, and dental practitioners with a comprehensive introduction to the concepts, applications, and future potential of AI in dental healthcare. The book begins with the fundamentals and evolution of artificial intelligence, followed by its relevance to dentistry, core AI concepts, and the development of AI-based radiograph annotation platforms. It further explores predictive analytics, AI applications across dental specialties, annotation tools, commercial AI solutions, and the latest advances in intelligent diagnostic systems.

In addition to technological developments, this book highlights the challenges, limitations, ethical considerations, and regulatory aspects associated with the implementation of AI in dentistry. It emphasizes the importance of responsible and evidence-based adoption of AI technologies while recognizing that these systems are intended to support – not replace – the clinical expertise of dental professionals.

It is hoped that this book will serve as a valuable reference for undergraduate and postgraduate students, educators, researchers, and clinicians seeking to understand the evolving role of artificial intelligence in Oral Medicine and Radiology. By combining theoretical foundations with practical applications, this text aims to contribute to the advancement of digital dentistry and inspire future innovations in oral healthcare.

Contents

Section	Title	Page Number
1	Introduction	1
2	Definition and Evolution of Artificial Intelligence	2
3	Why Dentistry and Oral Medicine are Ideal Fields for AI Adoption	6
4	Core Concepts of Artificial Intelligence	9
5	Step-By-Step Development of an AI Radiograph Annotation Platform	20
6	AI in Oral Medicine and Radiology	32
7	Predictive Analytics in Oral Healthcare	40
8	Artificial Intelligence Across All Dental Departments	42
9	Annotation Tools and Platforms for Dental AI	63
10	Challenges and Limitations of AI in Oral Medicine and Radiology	69
11	Future Directions in AI for Oral Medicine and Radiology	74
12	Regulatory and Ethical Considerations in Dental AI	78
13	Summary	82
14	Conclusion	83
15	Bibliography	84

1 Introduction

The advent of digital technology and the exponential growth in computational power over the past two decades have catalyzed a paradigm shift in biomedical sciences. At the forefront of this revolution is Artificial Intelligence (AI), a field of computer science dedicated to the creation of systems capable of performing tasks that ordinarily require human intelligence. These tasks encompass perception, pattern recognition, reasoning, learning, language understanding, decision-making, and problem-solving – the cognitive capabilities that form the foundation of clinical practice in medicine and dentistry. The rapid maturation of AI from a theoretical concept to a practical clinical tool represents one of the most significant developments in the history of healthcare. In dentistry and oral medicine, AI is rapidly emerging as a powerful tool that promises to augment clinical decision-making, enhance diagnostic accuracy, streamline administrative workflows, and ultimately improve patient outcomes. The specialty of oral medicine and radiology, with its emphasis on diagnostic imaging interpretation, pattern recognition in clinical and radiographic presentations, and the integration of systemic and local disease manifestations, is particularly well-positioned to benefit from AI augmentation. ^[1]

Oral medicine and radiology represent a domain particularly well-suited for AI integration due to the inherently visual and pattern-recognition-intensive nature of radiographic diagnosis. The discipline involves the interpretation of complex two-dimensional and three-dimensional dental images, identification of subtle pathological changes, correlation of radiographic findings with clinical presentations, and the generation of differential diagnoses from multimodal data. These tasks, while highly skilled, are associated with substantial inter-observer and intra-observer variability, creating an opportunity for AI-assisted systems to standardize diagnostic consistency. Studies have consistently demonstrated that even experienced radiologists and clinicians show significant disagreement in the interpretation of dental radiographs, particularly for subtle early-stage lesions. ^[2]

The global burden of oral disease is staggering. According to the World Health Organization (WHO), oral diseases affect nearly 3.5 billion people worldwide, with dental being the most prevalent non-communicable disease affecting 2.3 billion people with permanent teeth caries.

Periodontal disease, in its severe form, affects approximately 19% of the global adult population, representing more than one billion cases. Oral cancers, predominantly oral squamous cell carcinoma, account for over 377,000 new cases and 177,000 deaths annually worldwide. The scale of this burden, combined with chronic shortages of dental specialists in most parts of the world, creates an urgent imperative for scalable, accessible, and accurate diagnostic tools. Artificial intelligence has the potential to address this gap by providing automated, reliable, and cost-effective diagnostic support at scale ^[3]. The intersection of AI and oral medicine is further facilitated by the near-universal digitization of dental imaging. Digital radiography systems, intraoral scanners, cone beam computed tomography (CBCT) units, and digital clinical photography generate vast quantities of standardized, high-quality imaging data in formats amenable to machine learning analysis.

The establishment of electronic health records (EHR) in dental practice settings further creates rich longitudinal patient data that can be leveraged for AI-powered predictive analytics and clinical decision support. ^[4]

This introductory chapter traces the definition and evolution of artificial intelligence from its philosophical origins through successive technological revolutions to its current state of clinical deployment. It reviews historical milestones in medical imaging AI, elucidates the specific characteristics of dentistry and oral medicine that make these fields particularly amenable to AI adoption, and outlines the comprehensive objectives of AI integration in dental radiology as synthesized from the global research literature.

2 Definition and Evolution of Artificial Intelligence

The intellectual roots of artificial intelligence can be traced to ancient philosophical inquiries about the nature of mind, reasoning, and the possibility of mechanical thought. However, the formal birth of AI as a scientific discipline is conventionally dated to the summer of 1956, when John McCarthy, Marvin Minsky, Nathaniel Rochester, and Claude Shannon organized the seminal Dartmouth Conference, at which McCarthy coined the term 'Artificial Intelligence' and defined it as 'the science and engineering of making intelligent machines.' This foundational definition has been elaborated and refined over subsequent decades, but its essential insight — that intelligence need not be confined to biological substrates — has guided the field's development for nearly seven decades. ^[5]

The historical arc of AI development is conventionally described as alternating 'AI summers' and 'AI winters' — periods of intense optimism, rapid progress, and generous funding alternating with disillusionment, disappointment, and funding contraction. Understanding this oscillatory pattern is essential for contextualizing the current AI revolution, assessing its sustainability, and avoiding the hype cycles that have historically preceded AI winters. ^[6]

2.1 First AI Summer (1956–1974): Rule-Based Systems and Early Optimism

The first AI summer was characterized by remarkable early achievements that generated widespread optimism about the imminence of artificial general intelligence. The Logic Theorist (1956), developed by Newell and Simon, proved 38 of the first 52 theorems in Whitehead and Russell's *Principia Mathematica*, demonstrating that computational systems could perform mathematical reasoning. The General Problem Solver (1957) implemented a means-ends analysis framework intended to model human problem-solving. Early programs that played checkers, learned from experience (Samuel, 1959), proved geometric theorems, and engaged in limited natural language dialogue seemed to validate the Dartmouth Conference's ambitious goals. ^[7]

However, the rule-based approach that dominated this period — in which human expertise was painstakingly encoded as explicit logical rules — suffered from fundamental limitations that became apparent as problems of greater complexity were tackled.

The combinatorial explosion of possible states in complex domains, the brittleness of rule-based systems in the face of unanticipated inputs, and the difficulty of capturing tacit human expertise in explicit rules all contributed to the first AI winter of the mid-1970s.^[8]

2.2 Expert Systems Era (1970s–1980s): Knowledge Engineering

The development of expert systems in the 1970s and 1980s represented the field's most commercially successful early chapter. Expert systems encoded the knowledge of domain specialists in structured rule bases and used inference engines to reason about specific domains with some success. MYCIN (1972), developed at Stanford by Shortliffe and colleagues, diagnosed bacterial blood infections and recommended antibiotic therapies with accuracy comparable to infectious disease specialists. DENDRAL (1965–1980) identified chemical structures from mass spectrometry data. CADUCEUS diagnosed complex internal medicine conditions. INTERNIST-I accumulated clinical knowledge covering over 500 diseases. In dentistry, early expert systems were developed for oral diagnosis and treatment planning, though their scope was limited.^[9]

Despite their commercial success — expert systems represented a \$1 billion industry by the mid-1980s — their fundamental limitations became apparent: they were expensive to build and maintain, unable to learn from new data, confined to narrowly defined domains, incapable of handling uncertainty in a principled way, and unable to adapt to changing environments. The second AI winter of the late 1980s followed the collapse of the expert systems market.^[10]

2.3 Statistical Machine Learning Era (1990s–2000s)

The resurgence of AI in the 1990s was driven by a fundamental methodological shift from knowledge engineering (hand-coding expert rules) to data-driven machine learning (learning patterns from data). Statistical machine learning algorithms — support vector machines (SVMs), decision trees, random forests, Bayesian classifiers, k-nearest neighbors, and artificial neural networks (ANNs) — provided more robust, adaptable, and theoretically principled approaches to pattern recognition from data. These methods could be trained from labeled examples without requiring explicit rule specification, and many had well-understood theoretical properties including generalization bounds.^[11]

In medical imaging, statistical machine learning drove significant advances in computer-aided detection (CAD) for mammography, lung nodule detection on CT, and diabetic retinopathy screening. In dental applications, neural network-based studies on caries detection in intraoral radiographs appeared in the 1990s, establishing proof-of-concept for automated dental image analysis.

However, the performance of shallow machine learning methods was fundamentally limited by the need for hand-crafted feature engineering — the requirement for human experts to manually identify and extract relevant image features for the algorithms to process.^[12]

2.4 The Deep Learning Revolution (2012–Present)

The current AI revolution, now over a decade in duration with no signs of the waning enthusiasm that preceded previous AI winters, was ignited in 2012 when the AlexNet convolutional neural network achieved a 15.3% error rate on the ImageNet Large Scale Visual Recognition Challenge (ILSVRC) – compared to 26.2% for the next-best approach. The magnitude of this performance gap was unprecedented in the history of competitive computer vision benchmarks, and its significance was immediately grasped by the research community. Within two years, virtually every competitive entry in the ILSVRC used deep convolutional architectures.^[13]

The breakthrough of deep learning was enabled by the convergence of three enabling factors: the availability of large labeled datasets (particularly ImageNet's 1.2 million labeled images across 1,000 categories), the development of powerful parallel computing hardware (NVIDIA GPUs providing orders-of-magnitude speedups over CPU-based training), and algorithmic advances including the ReLU activation function (Nair and Hinton, 2010), dropout regularization (Srivastava et al., 2014), batch normalization (Ioffe and Szegedy, 2015), and residual connections (He et al., 2016). These factors collectively made it practical to train neural networks with dozens or hundreds of layers – deep networks that could learn hierarchical representations of increasing abstraction directly from raw pixel data, without human-designed feature extraction.^[14]

The deep learning revolution rapidly spread from general computer vision to medical imaging. In 2016, Gulshan et al. published a landmark study in JAMA demonstrating that a deep learning algorithm detected diabetic retinopathy from fundus photographs with sensitivity and specificity exceeding that of board-certified ophthalmologists. In 2017, Esteva et al. demonstrated dermatologist-level accuracy in classifying skin lesions from clinical photographs. Rajpurkar et al. (2017) showed that a CNN exceeded average radiologist performance in detecting pneumonia from chest radiographs. These demonstrations across multiple medical imaging specialties established deep learning as a clinically viable diagnostic AI paradigm.^[15]

In dentistry, the adoption of deep learning followed rapidly. Tuzoff et al. (2019) demonstrated automated tooth detection and numbering across all 32 teeth on panoramic radiographs. Lee et al. (2018) applied CNNs to caries detection. Ekert et al. (2019) achieved specialist-level performance in periapical lesion detection. The subsequent five years saw an exponential increase in dental AI publications, commercial AI product launches, and regulatory submissions, confirming the field's transition from research curiosity to clinical reality.^[16]

2.5 Historical Milestones in Medical Imaging AI

The history of AI in medical imaging is characterized by a progressive expansion of both technical capability and clinical application scope, from the narrow expert systems of the 1960s to the comprehensive, multi-task deep learning platforms of the 2020s. Understanding this historical trajectory contextualizes current developments and informs realistic expectations about the pace and nature of future progress. The earliest computerized approaches to radiographic image analysis date to the 1960s.

Lodwick and colleagues (1963) developed computerized methods for diagnosing primary bone tumors from radiographs, establishing the foundational concept that computational analysis of medical images could provide diagnostic insights. These pioneering studies were necessarily rule-based and limited in scope, but they established the intellectual precedent for computer-aided diagnosis (CAD) as a clinically meaningful concept. [17]

The development of mammographic CAD systems in the 1980s and 1990s represented the first sustained and commercially successful application of medical imaging AI. Driven by the urgent clinical need for improved breast cancer detection sensitivity in mass screening programs, researchers at the University of Chicago (notably Giger, Jiang, Schmidt, and colleagues) developed a succession of increasingly sophisticated CAD algorithms for detecting microcalcification clusters and masses on mammograms. This work culminated in the FDA clearance in 1998 of the first commercial CAD system for mammography (R2 Technology ImageChecker), marking a historic milestone in the clinical deployment of medical imaging AI. [18]

In dental radiology, automated analysis systems were developed in parallel with general medical imaging AI, though the field attracted considerably less research attention and commercial investment until the deep learning era. Notable early contributions included neural network approaches to caries detection on bitewing radiographs (Wenzel and Hintze, 1999), computerized analysis of periodontal bone loss on bitewing radiographs, and early CAD systems for detecting periapical changes on periapical radiographs. These studies established the technical feasibility of automated dental image analysis but were limited by the performance ceiling of shallow machine learning approaches. [19]

The deep learning era has produced a dramatic acceleration in the scope and performance of dental imaging AI. Landmark studies include: Lee et al. (2018) demonstrating CNN-based proximal caries detection on bitewing radiographs with diagnostic accuracy comparable to experienced dental practitioners; Tuzoff et al. (2019) achieving automated detection and labeling of 14 dental pathologies on panoramic radiographs using a modified ResNet architecture; Ekert et al. (2019) demonstrating that a deep learning system for periapical lesion detection achieved 92% sensitivity on periapical radiographs; Arik et al. (2017) developing a CNN for automated cephalometric landmark detection with clinically acceptable accuracy; and Hwang et al. (2020) demonstrating automated cephalometric analysis exceeding human performance on several landmark detection tasks. [20]

The commercial translation of dental imaging AI research has also accelerated dramatically since 2018, with multiple companies launching FDA-cleared AI products for intraoral radiograph analysis (VideaHealth, Pearl, Overjet/Carestream), cephalometric analysis (Ceph X, WebCeph), CBCT segmentation (Diagnocat, Anatomage InVivo, 3Disc Halo), and comprehensive oral health assessment. This rapid commercial deployment validates the clinical readiness of current dental AI technologies and signals the beginning of a fundamental transformation in how oral radiography is practiced.

3 Why Dentistry and Oral Medicine are Ideal Fields for AI Adoption

Several structural characteristics of dentistry and oral medicine make these disciplines particularly amenable to AI integration, creating a convergence of clinical need, data availability, and task suitability that positions dental AI as one of the most promising applications of medical AI.

3.1 Image-Centric Nature of Dental Diagnosis

Dental practice is fundamentally image-centric. The diagnosis and monitoring of the vast majority of dental diseases relies heavily on radiographic imaging. Dental caries, periodontal disease, periapical pathology, dentoalveolar infections, jaw tumors and cysts, temporomandibular disorders, developmental anomalies, and craniofacial trauma all require radiographic assessment for definitive diagnosis, treatment planning, and outcome monitoring.

The availability of large volumes of dental radiographs in digital format — estimated at hundreds of millions of images generated annually worldwide — provides the massive data substrate necessary for training high-performance AI models. [21]

3.1.1 Digital Standardization of Dental Imaging

The digitization of dental imaging is now near-universal in developed nations and rapidly advancing in developing countries. Digital radiographic systems produce standardized DICOM (Digital Imaging and Communications in Medicine) format images with consistent resolution, dynamic range, bit depth, and metadata — properties that facilitate the construction of large, homogeneous datasets for AI training. The DICOM standard's embedded metadata (imaging parameters, patient demographics, examination dates) further enriches AI training data with contextual information. [22]

3.1.2 Well-Defined Visual Pattern Recognition Tasks

The radiographic interpretation tasks fundamental to dental diagnosis — recognition of carious lesions, bone loss patterns, root morphology, pulp chamber anatomy, periapical lucencies, and calcified structures — involve identification of well-characterized visual patterns from defined anatomical regions.

These pattern recognition tasks are precisely the domain where deep learning excels, and the radiographic appearances of dental diseases follow relatively consistent and learnable visual signatures. In contrast to some medical imaging tasks that require complex integration of clinical and imaging data, many dental AI tasks can be well-defined as image analysis problems amenable to supervised learning. [23]

3.1.3 High Prevalence of Oral Disease Creates Large Datasets

The extraordinary prevalence of dental caries, periodontal disease, and other dental conditions means that dental practices accumulate vast numbers of cases with positive findings — a crucial advantage for AI training. Unlike rare cancers or unusual systemic diseases where positive training examples are scarce, dental caries is present in the majority of adults and can be identified on radiographs in enormous

numbers. This abundance of positive training examples facilitates the development of high-sensitivity detection algorithms without the severe class imbalance challenges that constrain AI development in rare disease detection tasks. ^[24]

3.1.4 Inter-Observer Variability Motivates AI Standardization

The substantial inter-observer and intra-observer variability documented in dental radiographic interpretation creates a compelling clinical motivation for AI-assisted standardization. Studies have consistently demonstrated significant disagreement among experienced dental practitioners in the interpretation of dental radiographs, particularly for early-stage lesions, borderline findings, and complex three-dimensional anatomical assessments. AI systems that achieve consistent, reproducible diagnostic outputs have the potential to reduce this variability and improve the reliability of dental diagnosis at the population level. ^[25]

3.2 Objectives of AI Integration in Dental Radiology

The integration of artificial intelligence into dental radiology is driven by a convergence of clinical, operational, and public health objectives that collectively define the transformative potential of AI in the specialty. These objectives can be organized across five principal domains, each representing a distinct dimension of AI's potential contribution to oral healthcare.

3.2.1 Diagnostic Enhancement

The primary and most extensively studied objective of dental AI is improving the accuracy, sensitivity, and reproducibility of radiographic diagnosis. AI systems can detect lesions that may be missed by fatigued or distracted clinicians, standardize diagnostic thresholds across practitioners and institutions, provide second-opinion support particularly for cases at the periphery of clinical certainty, and quantify lesion characteristics with precision that exceeds manual measurement. The goal is not to replace clinical judgment but to augment it — providing a reliable, consistent diagnostic baseline that supports clinician decision-making. ^[26]

3.2.2 Workflow Efficiency Optimization

AI-driven automation of time-consuming radiographic assessment tasks has the potential to dramatically improve clinical workflow efficiency. Manual tasks such as cephalometric landmark identification, alveolar bone level measurement, tooth numbering, caries charting from bitewing radiographs, and structured radiological report generation consume significant clinician time and are amenable to AI automation. By automating these routine tasks, AI can redirect clinician cognitive resources toward higher-complexity clinical reasoning and patient communication, improving both efficiency and the quality of clinician-patient interaction. ^[27]

3.2.3 Early Disease Detection

Many oral diseases, including dental caries, periodontal disease, and oral cancer, can be more effectively treated when detected at early stages. AI systems capable of detecting incipient changes — pre-cavitated carious lesions, early periodontal bone

resorption, subtle mucosal changes preceding dysplasia — before they become clinically apparent have the potential to shift treatment from reactive to preventive paradigms. The high sensitivity achievable by deep learning systems for subtle lesion detection, when appropriately validated, may enable the identification of pathology at stages where minimally invasive or preventive interventions are still effective. [28]

3.2.4 Personalized Treatment Planning and Precision Oral Medicine

The convergence of AI with large-scale patient data creates opportunities for personalized treatment planning approaches that go far beyond what is achievable through conventional clinical assessment. AI systems that integrate radiographic imaging data, clinical examination findings, genetic profiles, microbiome composition, salivary biomarkers, and longitudinal treatment history can generate individualized risk predictions, treatment outcome forecasts, and optimized treatment plans tailored to the unique biological and clinical profile of each patient. This precision oral medicine approach represents the long-term vision for AI-transformed dental care. [29]

3.2.5 Equitable Access to Diagnostic Expertise

Perhaps the most socially impactful objective of dental AI is its potential to democratize access to specialist-level diagnostic capabilities. In low- and middle-income countries, specialist dental radiologists and oral medicine specialists are extremely scarce relative to the population requiring dental diagnosis. AI-powered tele-radiology platforms, mobile diagnostic tools, and automated screening systems can extend specialist-level diagnostic accuracy to primary dental care settings, community health programs, and remote populations, potentially reducing health disparities in oral disease detection and management. [30]

3.3 Global Burden of Oral Disease and the Strategic Imperative for AI

The World Health Organization's Global Oral Health Status Report (2022) documents the profound global burden of oral disease and its systemic health implications. Oral conditions, collectively representing the most prevalent group of non-communicable diseases, affect an estimated 3.5 billion people — nearly 45% of the world's population — and were responsible for 13.5 billion Disability-Adjusted Life Years (DALYs) globally in 2019. This burden falls disproportionately on low- and middle-income countries and on socioeconomically disadvantaged populations within high-income nations, reflecting the profound influence of social determinants of health on oral health outcomes. [31]

Dental caries in permanent teeth, the most prevalent of all diseases assessed in the Global Burden of Disease study, affects 2.3 billion people and represents a major source of pain, functional impairment, and school and work absenteeism globally. Severe periodontitis, the sixth most prevalent condition globally, affects 19% of the world's adult population. Edentulism (complete tooth loss), resulting from untreated caries and periodontal disease, affects over 200 million people. These statistics underscore the urgent need for scalable diagnostic innovations that can address the gap between the scale of oral disease burden and the available dental workforce. [32]

In India, the context of particular relevance for this dissertation, the oral health burden is substantial. Caries prevalence in mixed dentition children reaches 49-51%, while periodontal disease affects up to 90% of adults in various surveys. Oral cancer incidence is among the highest in the world, with India accounting for approximately one-third of global oral cancer cases, largely attributable to the widespread use of tobacco, betel nut, and areca nut. The severe shortage of dental specialists relative to India's 1.4 billion population creates a compelling strategic imperative for AI-assisted oral diagnosis that can extend specialist capabilities across the country's vast geographic expanse and diverse population. [33]

The WHO's global action plan on oral health 2023–2030 explicitly identifies digital health technologies, including AI, as strategic enablers for achieving universal oral health coverage. The plan calls for investment in AI-powered oral health screening and diagnostic tools, particularly for low-resource settings, and for the development of evidence-based guidelines for the deployment of digital health technologies in oral healthcare. This international policy context lends further urgency and relevance to the academic investigation of AI applications in oral medicine and radiology. [34]

4. Core Concepts of Artificial Intelligence

A thorough understanding of the conceptual and technical foundations of artificial intelligence is prerequisite for appreciating its applications in oral medicine and radiology, critically evaluating the research literature, and making informed decisions about the deployment of AI tools in clinical practice. This chapter provides a comprehensive overview of the principal AI paradigms most relevant to dental imaging and clinical decision support. The exposition is designed to be accessible to clinicians with limited computational backgrounds while providing sufficient technical depth to enable meaningful engagement with the primary research literature. Each subsection covers both theoretical foundations and specific applications in dental radiology, contextualizing abstract computational concepts in clinically meaningful terms.

4.1 The Hierarchy of Artificial Intelligence Paradigms

Artificial intelligence, in its broadest conception, encompasses any computational approach to performing tasks that require human-like intelligence. Within this broad field, machine learning (ML) represents the subfield concerned with algorithms that enable computers to learn patterns from data, without being explicitly programmed for each specific task. Deep learning (DL) is a further subfield of ML, specifically concerning neural networks with many layers (deep architectures) that can learn hierarchical representations from raw data. Understanding the hierarchical relationship between these paradigms – AI encompasses ML, which encompasses DL – is fundamental to understanding the AI literature in dentistry. [35]

Traditional programming follows an explicit procedural paradigm: a human programmer specifies the exact rules the computer should follow to accomplish a task. Machine learning inverts this paradigm: instead of specifying rules, the programmer specifies a learning algorithm and provides examples of the desired input-output relationship, allowing the algorithm to discover the rules from data.

This inversion from explicit programming to data-driven learning is the conceptual foundation of modern AI and underlies its remarkable versatility across applications as diverse as dental caries detection, natural language report generation, and surgical robotics [36]




Figure 1; Artificial intelligence (AI) is a branch of data science that encompasses both traditional programming and machine learning (ML). Within ML, a variety of models and approaches exist, including artificial neural networks (ANN) and deep learning (DL).²⁰⁹

(Source- Choi RY, Coyner AS, Kalpathy-Cramer J, Chiang MF, Campbell JP. Introduction to Machine Learning, Neural Networks, and Deep Learning. Transl Vis Sci Technol. 2020 Feb 27;9(2):14.)

4.1.1 Types of Machine Learning

Supervised learning is the most widely applied ML paradigm in dental AI. The algorithm is trained on a labeled dataset — a collection of input-output pairs where inputs are dental radiographs and outputs are diagnostic labels assigned by expert clinicians — and learns to predict outputs for new, unseen inputs. Classification (predicting discrete category labels, e.g., caries present/absent) and regression (predicting continuous values, e.g., bone loss measurement in millimeters) are the primary supervised learning tasks. The quality of a supervised model is directly bounded by the quality and representativeness of its labeled training data^[23]. Unsupervised learning involves discovering hidden structure in unlabeled data. Clustering algorithms (k-means, hierarchical clustering, density-based clustering) group similar data points, enabling patient stratification and disease subtype discovery without predefined categories. Dimensionality reduction methods (Principal Component Analysis, t-SNE, UMAP) create lower-dimensional representations of high-dimensional data for visualization and analysis. Autoencoders learn compact latent representations of data and can be used for anomaly detection — identifying radiographic images that differ substantially from the training distribution, potentially flagging unusual pathological presentations^[37]. Semi-supervised learning combines a small amount of labeled data with a large amount of unlabeled data, exploiting the structure of the unlabeled data to improve model performance.

Given the high cost of expert dental radiograph annotation, semi-supervised methods are particularly attractive for dental AI. Self-supervised learning, a recent development in which models are trained on pretext tasks generated from unlabeled data (e.g., predicting masked image patches), has enabled the pre-training of powerful visual representations without manually labeled data. [38]

Reinforcement learning (RL) involves an agent learning through sequential interaction with an environment, receiving reward signals for actions that advance toward a goal. While less directly applied to dental image diagnosis, RL has been explored in autonomous surgical robotics, adaptive treatment planning, and drug discovery for oral diseases. RL-based approaches are particularly promising for sequential clinical decision-making tasks where treatment strategies must adapt to patient responses over time. [39]

4.1.2 Artificial Neural Networks: Architecture and Learning

Artificial Neural Networks (ANNs) are the computational backbone of modern deep learning AI systems. Loosely inspired by the biological neural architecture of the brain, ANNs consist of interconnected computational units (artificial neurons) organized in layers. Each neuron receives numerical inputs, computes a weighted sum, applies a nonlinear activation function, and passes the output to the next layer. The network learns by adjusting the synaptic weights connecting neurons based on the discrepancy between predicted and target outputs [40]. The mathematical foundation of ANN training is the backpropagation algorithm (Rumelhart, Hinton, Williams, 1986), which efficiently computes the gradient of the loss function with respect to all network weights using the chain rule of differential calculus. These gradients are used to update weights in the direction that reduces prediction error, through the gradient descent optimization algorithm. Modern variants including Adam (Adaptive Moment Estimation), RMSprop, and AdaGrad provide adaptive learning rate schedules that substantially accelerate convergence compared to vanilla gradient descent. [41]

Activation functions introduce non-linearity into neural networks, enabling them to learn complex, non-linear mappings between inputs and outputs. The Rectified Linear Unit (ReLU, $f(x) = \max(0, x)$), introduced to deep learning by Nair and Hinton (2010), has become the default activation function in deep networks due to its computational efficiency, biological plausibility, and mitigation of the vanishing gradient problem that plagued earlier sigmoid and tanh activations in deep networks. Variants including Leaky ReLU, ELU, GELU, and Swish have been developed to address ReLU's limitation of producing dead neurons [42]. Regularization techniques are essential in deep learning to prevent overfitting — the tendency of complex models to memorize training data rather than learning generalizable patterns. Key regularization methods include L1 and L2 weight decay (penalizing large weights), dropout (randomly deactivating neurons during training, introduced by Srivastava et al., 2014), batch normalization (normalizing layer activations across the batch to stabilize and accelerate training, Ioffe and Szegedy, 2015), and data augmentation (artificially expanding the training dataset through transformations). [43]

4.1.3 Deep Learning: Depth and Representational Power

The defining feature of deep learning is the use of neural networks with many hidden layers (typically 10–1000+ layers), enabling the learning of hierarchical representations of increasing abstraction. In the context of visual processing – highly relevant to dental radiograph analysis – the hierarchical representations learned by deep networks have been extensively analyzed and found to mirror the hierarchical organization of the visual cortex: early layers detect local features (edges, textures, intensity gradients), intermediate layers detect structural patterns (shapes, anatomical boundaries), and later layers detect high-level semantic concepts (pathological lesion patterns, anatomical structures). [44]

The practical utility of deep learning was unlocked by the convergence of three enabling factors. First, the availability of large labeled datasets enabled by digitization: ImageNet (1.2 million images), Google Open Images (9 million images), and medical imaging datasets including CheXpert (224,316 chest radiographs) and OpenI (7,470 chest radiographs with reports) provided the training data substrate for powerful visual models.

Second, GPU computing: the parallel architecture of graphics processing units (GPUs), originally developed for video game rendering, proved ideally suited for the massively parallel matrix operations underlying deep learning, providing 50–100× speedups over CPU-based training. Third, algorithmic innovations including ReLU, dropout, batch normalization, and residual connections enabled the training of networks far deeper than previously feasible[45].

In the context of dental AI, deep learning provides several critical advantages over shallow machine learning approaches: (1) automatic feature learning eliminates the need for hand-crafted dental-specific image features, which required considerable domain expertise and were often suboptimal; (2) end-to-end learning optimizes all feature extraction and classification stages jointly, rather than separately optimizing feature extractor and classifier; (3) scalability with data enables continuous performance improvements as more training data becomes available; and (4) transfer learning from large natural image datasets provides strong initialization for dental image models even when dental-specific training data is limited. [46]

4.2 Convolutional Neural Networks (CNNs) for Dental Image Analysis

4.2.1 Convolutional Layer Operation

Convolutional Neural Networks (CNNs) are a specialized class of deep neural networks architecturally optimized for processing data with grid-like topology – including digital images. The defining operation of a CNN is the convolution: a set of learnable filters (small matrices, typically 3×3 or 5×5) slide across the spatial dimensions of the input image, computing element-wise products at each position and summing to produce a scalar output. When a filter is applied to every position in the input, it produces a feature map representing the spatial distribution of a specific pattern that filter has learned to detect. By stacking multiple filters per layer, CNNs generate multi-channel feature maps encoding diverse visual patterns at each

spatial scale^[47]. The computational efficiency of CNNs arises from weight sharing: the same filter weights are applied across all spatial positions in the input (shared weights), dramatically reducing the number of learnable parameters compared to fully connected networks applied to images. A 224×224 image analyzed by fully connected layers would require over 150,000 parameters per neuron; a CNN with 3×3 filters requires only 9 parameters per filter per layer, shared across the entire image. This parameter efficiency enables CNNs to process high-resolution dental radiographs with manageable computational cost. ^[48]

4.2.2 Landmark CNN Architectures in Dental AI

The evolution of CNN architectures has been the primary driver of progress in medical and dental imaging AI. AlexNet (Krizhevsky et al., 2012), with 8 weighted layers and ReLU activations, initiated the deep learning revolution. VGGNet (Simonyan and Zisserman, 2014), using only 3×3 convolutional filters in networks up to 19 layers deep, demonstrated that depth was a critical architectural component of CNN performance. GoogLeNet/Inception (Szegedy et al., 2014) introduced the inception module – parallel convolutions with multiple filter sizes – enabling efficient deep networks^[49]. ResNet (He et al., 2016) introduced the residual connection – a shortcut path that adds the input of a residual block directly to its output – enabling the training of extremely deep networks (up to 1000 layers) by providing gradients a direct path during backpropagation, mitigating the vanishing gradient problem. ResNet architectures (ResNet-50, ResNet-101, ResNet-152, ResNeXt) have become the dominant backbone for dental imaging AI and are used in the majority of published dental AI studies.

DenseNet (Huang et al., 2017) extended the residual connection concept by connecting each layer to all subsequent layers, further improving gradient flow and feature reuse^[50]. EfficientNet (Tan and Le, 2019) introduced neural architecture search and compound scaling – simultaneously scaling network width, depth, and resolution – to achieve superior accuracy-efficiency tradeoffs across a family of models (EfficientNet-B0 through B7). EfficientNet-B4 and B5 have demonstrated particularly strong transfer learning performance on medical imaging tasks including dental radiograph analysis. Vision Transformer (ViT, Dosovitskiy et al., 2021) replaced convolutional operations with transformer self-attention mechanisms, achieving state-of-the-art performance on large-scale image recognition and demonstrating the potential of attention-based architectures for medical image analysis. ^[51]

4.2.3 Object Detection Architectures

Object detection – identifying the location and category of multiple objects within an image – is a critical capability for dental AI systems that must detect and localize specific pathological findings within complex dental radiographs containing multiple teeth, supporting structures, and potential pathologies. The major object detection paradigms used in dental AI include: ^[52] Region-based CNNs (R-CNN family): R-CNN (Girshick et al., 2014), Fast R-CNN (Girshick, 2015), and Faster R-CNN (Ren et al., 2015) use region proposal networks to generate candidate object

regions, which are then classified and refined. Faster R-CNN provides the best accuracy among the R-CNN family and has been applied to multi-pathology detection on panoramic radiographs. RetinaNet, which addresses class imbalance with focal loss, achieves high accuracy for detecting small or rare objects such as early-stage carious lesions.




Figure 2: object detection in R-CNN with algorithm flow.²¹⁰

(Source- An J, Zhang D, Xu K, Wang D. An OpenCL-Based FPGA Accelerator for Faster R-CNN. *Entropy (Basel)*. 2022 Sep 23;24(10):1346)

Single-stage detectors: YOLO (You Only Look Once, Redmon et al., 2016–2023) reformulates object detection as a single regression problem, directly predicting bounding boxes and class probabilities from the full image in a single forward pass, achieving real-time detection speeds. YOLOv5, YOLOv8, and their variants are widely used in dental AI for real-time applications such as chairside caries detection and interactive CBCT segmentation. SSD (Single Shot MultiBox Detector, Liu et al., 2016) provides a good balance between speed and accuracy for multi-scale detection tasks. [53]

4.3 Segmentation Architectures for Dental Imaging

Semantic segmentation — assigning a class label to every pixel in an image — is essential for dental AI applications requiring precise boundary delineation such as tooth segmentation, periapical lesion boundary definition, and alveolar bone level measurement. U-Net (Ronneberger et al., 2015) introduced the encoder-decoder architecture with skip connections that has become the dominant paradigm for biomedical image segmentation. The encoder progressively downsamples the image while extracting features, and the decoder upsamples back to the original resolution while incorporating skip-connected features from the encoder, enabling both precise localization and contextual understanding [54]. U-Net++ (Zhou et al., 2018) introduced a nested U-Net architecture with dense skip connections that improves segmentation accuracy on dental structures with varied scales and textures. Attention U-Net (Oktay et al., 2018) incorporates spatial attention gates that focus the network on relevant anatomical regions, reducing false positives from non-dental background structures. TransUNet (Chen et al., 2021) integrates transformer self-attention into the U-Net framework, combining global context modeling with local precision for dental structure segmentation. For 3D CBCT volume segmentation, 3D-UNet extends the U-Net paradigm to volumetric data, enabling voxel-level segmentation of jaw bones, individual teeth, and nerve canals. [55]

4.3.1 Recurrent Neural Networks and Long Short-Term Memory Networks

Recurrent Neural Networks (RNNs) are neural network architectures designed to process sequential data by maintaining a hidden state that accumulates information across time steps, effectively giving the network memory of previous inputs. In dental AI contexts, RNNs are relevant for processing temporal sequences such as longitudinal radiographic data series, sequential clinical examination records, time-series salivary biomarker data, and structured clinical reports. [56]




Figure 3: Network Image of Rnn-Cnn. ²¹¹

(Source- Kanjanasurat I, Tenghongsakul K, Purahong B, Lasakul A. CNN-RNN Network Integration for the Diagnosis of COVID-19 Using Chest X-ray and CT Images. *Sensors (Basel)*. 2023 Jan 25;23(3):1356.)

Standard RNNs suffer from the vanishing gradient problem – the difficulty of learning dependencies between temporally distant events during backpropagation through time – which limits their ability to capture long-range dependencies in sequences. Long Short-Term Memory networks (LSTMs, Hochreiter and Schmidhuber, 1997) address this limitation through a gating mechanism consisting of input, forget, and output gates that regulate information flow through a cell state, enabling the network to maintain and access information over long temporal spans. [57]. In dental AI, LSTM-based approaches have been applied to: predicting periodontal disease progression from longitudinal clinical attachment level and radiographic bone loss sequences; modeling patient treatment adherence trajectories for personalized recall interval prediction; processing longitudinal CBCT imaging sequences in orthodontic treatment monitoring; and extracting structured clinical information from sequential dental examination records in electronic health records. Bidirectional LSTM architectures, which process sequences in both forward and backward directions, achieve better performance for tasks requiring both prior and future context. [58]

4.3.2 Generative Adversarial Networks (GANs) in Dental Imaging

Generative Adversarial Networks (Goodfellow et al., 2014) consist of two competing neural networks: a generator that learns to produce synthetic data samples resembling real data, and a discriminator that learns to distinguish real from synthetic samples. These networks are trained adversarially: the generator attempts to fool the discriminator, while the discriminator attempts to detect generated samples. The iterative adversarial training drives both networks to improve, ultimately producing a generator capable of synthesizing highly realistic data. [59]




Figure 4: Generator and Discriminator networks images.²¹²

(Source- Waqas M, Hasan S, Ghorri AF, Alfaraj A, Faheemuddin M, Khurshid Z. *Synthetic Orthopantomography Image Generation Using Generative Adversarial Networks for Data Augmentation. Int Dent J. 2025 Dec;75(6):103878.*)

In dental imaging AI, GANs have been applied to several important problems. First, data augmentation: GANs trained on dental radiograph datasets can synthesize realistic artificial radiographs with specific pathological features, augmenting limited training datasets for rare pathologies such as ameloblastoma, odontogenic keratocyst, and early-stage oral cancer. Second, image-to-image translation: conditional GANs (pix2pix, CycleGAN) can translate between imaging modalities – for example, synthesizing CBCT volumes from panoramic radiographs, or generating dental radiograph images from segmentation masks – enabling data augmentation across modalities. Third, image enhancement: GAN-based super-resolution and denoising networks can improve the quality of low-dose dental radiographs, enabling dose reduction without proportional image quality degradation^[60]. The StyleGAN architecture has been applied to generate photorealistic synthetic oral mucosal lesion images, providing a mechanism for augmenting limited oral cancer training datasets. Diffusion models, the most recent generation of generative models (DALL-E 2, Stable Diffusion, Imagen), are beginning to be applied to medical image synthesis and show promise for generating diverse, high-quality synthetic dental imaging data with controlled pathological features, potentially transforming the data augmentation landscape for dental AI. [61]




Figure 5: Workflow of the GAN-based image generation.²¹²

Source- Waqas M, Hasan S, Ghori AF, Alfaraj A, Faheemuddin M, Khurshid Z. Synthetic Orthopantomography Image Generation Using Generative Adversarial Networks for Data Augmentation. *Int Dent J.* 2025 Dec;75(6):103878.

4.3.3 Vision Transformers and Attention Mechanisms

The transformer architecture (Vaswani et al., 2017), originally developed for natural language processing, has emerged as a powerful alternative to CNNs for visual recognition tasks through the development of Vision Transformers (ViT, Dosovitskiy et al., 2021). Unlike CNNs which process local image regions through fixed-size convolutional filters, ViT divides images into fixed-size patches, linearly embeds each patch, and processes the patch sequence through transformer self-attention layers that compute relationships between all pairs of patches regardless of spatial distance. ^[62]

The self-attention mechanism enables transformers to model global long-range dependencies between distant image regions from the first layer, in contrast to CNNs which build up receptive field size through successive convolutional and pooling layers. For dental radiograph analysis, this global context modeling capability is advantageous for tasks requiring integration of information from spatially distributed anatomical landmarks — particularly cephalometric analysis, panoramic radiograph interpretation, and whole-jaw CBCT assessment. Dental Transformer models combining the local feature extraction of CNNs with the global attention of transformers (hybrid architectures) have demonstrated superior performance on several dental AI benchmarks. ^[63]

4.4 Natural Language Processing (NLP) in Dental Records and Reporting

4.4.1 Evolution of NLP for Clinical Text

Natural Language Processing (NLP) encompasses the computational methods for enabling machines to understand, analyze, and generate human language. The clinical significance of NLP in dentistry derives from the enormous volume of unstructured textual information generated in dental practice — clinical notes, patient histories, examination records, operative reports, radiological reports, prescription records, referral letters, and patient communication — much of which is never systematically analyzed due to its unstructured form. NLP provides the tools to transform this textual information into structured, analyzable data that can support clinical research, quality improvement, and decision support. ^[64]

The current state of the art in clinical NLP is represented by large pre-trained language models built on the transformer architecture. BERT (Bidirectional Encoder Representations from Transformers, Devlin et al., 2018) introduced bidirectional language model pre-training on massive text corpora, enabling remarkably versatile representations of clinical language. ClinicalBERT and BioBERT are BERT variants pre-trained specifically on clinical notes and biomedical literature respectively, achieving superior performance on clinical NLP tasks. GPT-4 and similar large language models (LLMs) demonstrate remarkable capability in clinical text generation, summarization, question answering, and diagnostic reasoning. ^[65]

4.4.2 NLP Applications in Oral Medicine and Radiology

Automated Radiological Report Generation represents a particularly impactful NLP application in oral medicine and radiology. AI systems that analyze dental radiographs and generate structured, clinically formatted reports combine computer vision (for image analysis) with natural language generation (for report text production). Such systems can automatically produce findings sections covering tooth inventory, detected pathologies, severity assessments, and diagnostic impressions — dramatically reducing report turnaround time and ensuring consistent terminology across practitioners. ^[66]

Clinical Information Extraction from dental records enables retrospective research at scale. NLP algorithms trained on clinical note text can automatically identify: diagnoses (ICD codes from free-text descriptions), procedures performed, medications prescribed, allergies and contraindications, patient-reported symptoms and chief complaints, and treatment outcomes. This structured extraction from unstructured notes enables epidemiological analyses, treatment outcome studies, and quality improvement audits that would be impractical through manual record review. ^[67]

Symptom-Based Triage and Clinical Decision Support represents an emerging application of NLP in dental practice management. Conversational AI systems (chatbots powered by large language models) can conduct pre-appointment symptom assessment, triage urgent presentations such as dental abscesses and trauma, screen for oral cancer risk factors, and collect structured medical histories before the clinical encounter — improving appointment efficiency and enabling better clinical preparation.

AI-powered clinical decision support tools that analyze the full semantic content of patient records can alert clinicians to potential drug interactions, contraindications, and clinical red flags that might be missed in busy practice environments. ^[68]

4.4.3 Explainable AI (XAI): From Black Box to Transparent Diagnostics

The clinical deployment of AI diagnostic systems is fundamentally constrained not only by their performance accuracy but also by the intelligibility of their reasoning to the clinicians who must act upon their outputs. Modern deep learning models, while often highly accurate, make predictions through complex non-linear transformations across hundreds of millions of parameters that are intrinsically opaque to human

interpretation — the 'black box' problem that represents one of the most significant barriers to clinical AI adoption and regulatory acceptance. Explainable AI (XAI) addresses this challenge through methods that provide human-interpretable insights into how AI systems reach their conclusions.^[69]

4.5 The Clinical Importance of XAI in Dentistry

In clinical dental practice, the ability to understand and verify AI diagnostic reasoning is essential for multiple reasons. First, clinicians need to assess whether AI predictions are based on clinically relevant radiographic features or spurious correlations in the training data. Second, patients have an ethical right to understand the basis for clinical decisions that affect their care, including decisions supported by AI. Third, regulatory bodies require evidence that AI diagnostic systems are making clinically appropriate inferences. Fourth, the detection of AI failure modes — situations where the AI has learned incorrect features or exhibits unexpected behavior — requires interpretability tools that can reveal what the model has actually learned.^[27]

4.5.1 Gradient-Weighted Class Activation Mapping (Grad-CAM)

Grad-CAM (Selvaraju et al., 2017) is the most widely used XAI visualization technique in medical imaging AI, including dental AI. Grad-CAM computes the gradients of the target class score with respect to the feature maps of the last convolutional layer, weights the feature maps by the globally-averaged gradients, and produces a heat map that highlights the image regions most influential for the model's prediction. When overlaid on the original dental radiograph, the Grad-CAM heat map provides a visual explanation of which radiographic regions drove the AI's diagnosis.^[70]




Figure 6: Grad-CAM design approach.²¹³

(Source- Liu Y, Tang L, Liao C, Zhang C, Guo Y, Xia Y, Zhang Y, Yao S. Optimized Dropkey-Based Grad-CAM: Toward Accurate Image Feature Localization. *Sensors (Basel)*. 2023 Oct 10;23(20):8351.)

In dental AI clinical studies, Grad-CAM visualizations have been used to verify that CNN models for caries detection attend to the correct tooth regions (enamel and dentin of the crown), that models for periapical lesion detection focus on the periapical region of tooth roots, and that models for bone loss detection attend to the alveolar bone crest and CEJ region. Studies have also used Grad-CAM to identify cases where models attend to irrelevant regions — for example, imaging artifacts or adjacent anatomical structures — providing insights into model failure modes that inform dataset curation and model improvement.^[71]

4.5.2 SHAP and Feature Attribution Methods

SHAP (SHapley Additive exPlanations, Lundberg and Lee, 2017) is a model-agnostic XAI framework that assigns each input feature a Shapley value — derived from cooperative game theory — representing that feature's contribution to a specific prediction, averaged across all possible orderings of feature inclusion. SHAP values provide consistent, theoretically grounded feature importance attributions for any machine learning model.

In dental AI applications using tabular clinical data (e.g., periodontal risk prediction models with clinical input features), SHAP provides interpretable explanation of which clinical parameters most strongly influence individual risk predictions, enabling clinician understanding and trust in AI recommendations.^[72]

4.5.3 Uncertainty Quantification

Beyond explaining the basis for predictions, XAI in clinical AI also encompasses uncertainty quantification — providing calibrated confidence estimates that communicate when an AI model is operating outside its reliable range. Bayesian deep learning approaches (Monte Carlo dropout, deep ensembles, Bayesian neural networks) provide principled uncertainty estimates that distinguish between aleatoric uncertainty (inherent ambiguity in the input data, such as genuinely ambiguous radiographic findings) and epistemic uncertainty (model uncertainty from limited training data or out-of-distribution inputs). AI systems that communicate high uncertainty can flag cases for mandatory clinician review, operating as intelligent screening tools that focus clinical attention on genuinely challenging cases while providing confident automated assessment for clear-cut presentations.^[73]

5 Step-By-Step Development of an AI Radiograph Annotation Platform

The development of an AI-powered radiographic annotation and diagnostic platform is a complex, multidisciplinary endeavor requiring coordinated expertise across oral medicine and radiology, data science, software engineering, biomedical informatics, clinical research methodology, regulatory compliance, and ethics.

Unlike the development of conventional clinical diagnostic algorithms — which typically follow established statistical frameworks — AI platform development requires iterative, data-driven cycles of model training, evaluation, and refinement that demand specialized expertise and infrastructure.

The framework presented in this chapter integrates methodological guidance from multiple authoritative sources: the CRISP-DM (Cross-Industry Standard Process for Data Mining) framework for data science project management; MLOps (Machine Learning Operations) principles for production AI system deployment and lifecycle management; the FDA's Predetermined Change Control Plan (PCCP) framework for continuously learning medical AI; WHO guidance on AI for health; EQUATOR reporting guidelines for clinical prediction model studies (TRIPOD+AI, CLAIM); and the growing body of best-practice literature from dental AI research groups worldwide. The ten-step framework provides a comprehensive, actionable guide for oral medicine and radiology departments seeking to develop and deploy institutional AI diagnostic tools.

Step 1: Problem Identification and Clinical Specification

The foundation of any successful AI development project is a precisely and comprehensively defined clinical problem. Problem identification is not merely a preliminary step but a critical determinant of the entire development trajectory — the choice of clinical problem defines the data requirements, annotation protocols, model architecture, performance metrics, deployment target, and clinical validation strategy. Vague, poorly constrained, or clinically irrelevant problem statements lead to technically sophisticated but practically useless AI systems.^[74]

A. Clinical Needs Assessment

A structured clinical needs assessment should be conducted through several complementary approaches.

- First, a systematic review of the dental AI literature identifies which clinical problems have already been addressed, what performance levels have been achieved, and where performance gaps or unmet clinical needs remain.
- Second, formal interviews with practicing oral medicine and radiology specialists and referring clinicians identify the diagnostic tasks where AI assistance would provide greatest clinical value.
- Third, analysis of institutional diagnostic error patterns — including cases flagged for second opinion, cases with delayed diagnosis, and cases with significant inter-clinician disagreement — identifies the specific failure modes in current clinical practice that AI could address. Fourth, workflow analysis quantifies the time spent on specific diagnostic tasks, identifying opportunities for AI-driven efficiency improvement.

B. Task Definition and Formalization

The identified clinical problem must be formalized as a specific, measurable machine learning task. This formalization requires: specification of the input data type (intraoral bitewing radiographs, OPG, CBCT, clinical photographs, or multimodal combinations); specification of the output type (binary or multi-class classification label, bounding box coordinates, pixel-level segmentation mask, continuous measurement, or survival probability); definition of the target patient population, imaging modality, and clinical setting for deployment; specification of the gold

standard against which model performance will be evaluated (expert radiologist consensus, histopathological diagnosis, clinical follow-up); and definition of clinically acceptable performance thresholds (minimum sensitivity and specificity, maximum false positive rate).^[75]

A critical decision in problem specification is the intended role of the AI system in the clinical workflow. The FDA recognizes a spectrum from computer-aided detection (CAD) tools that flag potential findings for mandatory clinician review, to clinical decision support systems (CDSS) that provide recommendations while preserving clinician autonomy, to autonomous AI diagnostic systems that make diagnostic decisions without clinician review. The intended use specification has major implications for regulatory strategy, liability, and clinical validation requirements. For initial dental AI deployments, a CAD or CDSS role — AI as a second opinion or quality check — is generally the most clinically appropriate and regulatorily straightforward approach.^[76]

Step 2: Data Acquisition — Building a Dental AI Dataset

The performance of any machine learning model is fundamentally bounded by the quality, quantity, and representativeness of its training data. The maxim 'garbage in, garbage out' applies with particular force to clinical AI, where training data quality directly determines diagnostic performance in deployment. Building a high-quality dental imaging dataset is typically the most resource-intensive step in AI platform development, requiring sustained collaboration between clinical and technical teams over months to years.^[22]

A. Imaging Modalities and Technical Requirements

The principal digital imaging modalities used in dental AI dataset construction are intraoral periapical (IOPA) radiographs, bitewing radiographs, panoramic (orthopantomographic, OPG) radiographs, and cone beam computed tomography (CBCT) volumes. Each modality has distinct technical properties, clinical applications, and AI task suitabilities that must be considered in dataset planning. Intraoral radiographs (IOPA and bitewings) offer the highest spatial resolution (typically 10–20-line pairs/mm for digital sensors), making them optimal for detecting small-scale pathologies such as early interproximal caries (as small as 1–2 mm), early periapical bone changes, root resorption, and fine endodontic anatomy. The standardized geometric projection geometry of intraoral radiographs (particularly with film/sensor holders and beam alignment devices) facilitates the development of AI models with strong generalization.^[77]

Panoramic radiographs provide a comprehensive overview of the entire dentition, alveolar bone, temporomandibular joints, maxillary sinuses, and surrounding structures in a single image, making them suitable for AI systems targeting simultaneous detection of multiple pathologies across the full dental arch. The inherent geometric distortion and superimposition of structures in panoramic radiography presents a challenging imaging environment for AI but one where the ability to process the full dental complement simultaneously provides unique capabilities not available from intraoral radiographs alone.^[78]

CBCT provides isotropic three-dimensional volumetric imaging with spatial resolution approaching intraoral radiography, enabling visualization of structures in any orientation without projection superimposition. AI analysis of CBCT data is more computationally demanding due to the three-dimensional nature of the data and the large volume size (typically 400–4000 slices per volume), but enables detection of pathologies invisible on two-dimensional projections, precise volumetric measurements, and three-dimensional anatomical model generation.^[79]

B. Dataset Size Requirements

Determining the minimum dataset size required to train a high-performance dental AI model is a complex statistical problem that depends on multiple interacting factors: the complexity of the clinical task, the number of output classes, the degree of within-class variability, the architecture employed, the use of transfer learning, and the required performance level. Practical guidelines from the dental AI literature suggest: for binary classification tasks with ImageNet transfer learning, 500–2,000 labeled examples per class may be sufficient to achieve performance competitive with specialist clinicians; for multi-class detection tasks (>5 classes) with moderate within-class variability, 3,000–10,000 labeled examples per class are typically required; for dense segmentation tasks or de novo training without transfer learning, 50,000+ labeled images may be needed for high performance^[80]. Dataset diversity is at least as important as size for model generalization. A dataset of 5,000 radiographs from a single institution using a single imaging system will typically produce a model with poor generalization to other settings. Diverse datasets spanning multiple institutions, imaging systems, patient demographics, disease severities, and acquisition parameters produce models with substantially better generalization – even when the total dataset size is smaller. Planning for dataset diversity from the outset, through multi-institutional collaboration or systematic equipment-diverse collection protocols, is a critical element of dataset strategy.^[81]

C. Data Sources and Collection Strategies

Retrospective mining of institutional PACS repositories is the most efficient initial data collection strategy. Institutional PACS systems containing digital dental radiographs accumulated over years of clinical practice can provide tens to hundreds of thousands of radiographs with demographic information and prior clinical diagnoses. Systematic queries using ICD-10 diagnosis codes, procedure codes, or clinical keywords can identify radiographs associated with specific diagnoses for inclusion in condition-specific training datasets. However, retrospective PACS mining typically yields unbalanced datasets with over-representation of common findings and under-representation of rare pathologies, necessitating targeted supplemental collection^[82]. Multi-institutional data sharing through collaborative research consortia represents the most impactful strategy for assembling large, diverse datasets. The federated dental AI model – in which multiple institutions agree to share annotated datasets under a common data governance framework – has been successfully implemented in several regions, including the European Dental AI Research Consortium and multi-institutional collaborations among Indian dental schools.

Data use agreements specifying permissible uses, access controls, attribution requirements, and data retention limits must govern all inter-institutional data sharing. Public dental imaging datasets, while more limited than in other medical imaging domains, are growing in availability. The Tufts Dental Database (1,000 panoramic radiographs with periapical annotations), the DENTEX dataset from the MICCAI 2023 challenge (panoramic radiographs with multi-pathology annotations), and various institution-specific datasets shared through academic repositories (Zenodo, Figshare, PhysioNet, Harvard Dataverse) provide accessible starting points for dental AI research. Competitive machine learning challenges (Kaggle, Grand Challenge) provide curated, well-annotated dental imaging benchmarks that facilitate fair comparison of AI methods.^[83]

Step 3: Ethical Clearance and Regulatory Compliance

Any AI development project involving patient-derived data requires comprehensive ethical oversight and regulatory clearance before data collection or use. This is not merely a regulatory formality but a fundamental ethical obligation arising from the use of sensitive personal health information for research purposes. The ethical clearance process provides a structured framework for ensuring that the research benefits justify the privacy and other risks to participants, that data are collected and used with appropriate consent and safeguards, and that the research adheres to the highest standards of scientific integrity.

A. Ethics Committee Submission

The research protocol must be submitted to the institutional ethics committee (Institutional Review Board, IRB, or equivalent) for prospective review and approval before any data collection or use begins. The protocol submission must include: the scientific rationale and objectives of the research; detailed description of data sources, types, and collection methods; patient eligibility criteria and recruitment procedures; informed consent procedures and consent form; data anonymization and de-identification methods; data storage, security, and access control measures; data retention and destruction plan; risk-benefit assessment; and procedures for handling participant queries and withdrawals.^[84]

In India, the ethics committee requirements for AI research using patient data are governed by the ICMR National Ethical Guidelines for Biomedical and Health Research Involving Human Participants (2017) and applicable institutional policies. Research classified as involving no more than minimal risk (e.g., retrospective analysis of de-identified radiographic data) may qualify for expedited review, while prospective studies involving identifiable patient data require full committee review. Approval from the ethics committee must be obtained and documented before data collection begins.

B. Informed Consent Principles

For prospective dental AI data collection studies involving patient radiographs and clinical data, written informed consent must be obtained from each participating patient before data collection.

The consent form must be written in the patient's language and at an appropriate literacy level, and must disclose: the purpose and nature of the research, including how AI will be developed from the data; the specific types of data to be collected, stored, and analyzed; the anonymization measures applied and residual re-identification risks; the identity of all parties who will have access to the data; the voluntary nature of participation and right to withdraw without consequence; the absence of direct clinical benefit to the participant from study participation; and contact information for the research team and ethics committee.^[85]

C. DICOM Anonymization and De-identification

Dental DICOM images contain embedded patient-identifiable metadata including patient name, patient ID, date of birth, sex, institution name, date of examination, and operator name – any of which could enable re-identification of de-identified records. Rigorous DICOM anonymization is essential before sharing or using patient imaging data for AI development. The HIPAA Safe Harbor method requires removal of 18 specific patient identifiers; the Expert Determination method uses statistical verification that re-identification risk is sufficiently low.^[86]




Figure 7: Anonymization for pixel data in DICOM images.²¹⁴

(Source- Silva JM, Pinho E, Monteiro E, Silva JF, Costa C. Controlled searching in reversibly de-identified medical imaging archives. *J Biomed Inform.* 2018 Jan;77:81-90.)

Specialized DICOM anonymization tools (CTP – RSNA Clinical Trials Processor, dcm4che DICOM Toolkit, Orthanc DICOM server with anonymization plugins, and PyDicom for Python-based batch processing) automate the anonymization of large DICOM datasets with documented audit trails. The anonymization process must be verified by testing a sample of anonymized images to confirm the absence of identifying metadata. Pixels containing burned-in patient information (some older imaging systems embed patient data directly in image pixels) require additional pixel-level anonymization.

Step 4: Annotation Process – Creating Ground Truth Labels

Annotation – the systematic labeling of dental radiographs with ground truth diagnostic information – is simultaneously the most scientifically consequential and most practically challenging step in dental AI development. The clinical validity and diagnostic performance of an AI system are directly determined by the quality and accuracy of the annotations it learns from. An AI system trained on inaccurate, inconsistent, or poorly specified annotations will learn inaccurate and inconsistent diagnostic patterns – regardless of the sophistication of its architecture or the scale of its training.^[87]

A. Annotation Taxonomy Design

The design of a comprehensive annotation taxonomy – the structured classification scheme defining what is labeled and how – requires careful collaboration between oral medicine and radiology experts and AI developers. The taxonomy must balance clinical comprehensiveness (covering all diagnostically relevant findings) with practical annotability (being clear enough that annotators can apply labels consistently without ambiguity). The International Caries Detection and Assessment System (ICDAS), WHO periodontal staging criteria (Stage I-IV, Grade A-C), and WHO oral mucosal disease classification provide internationally standardized clinical frameworks that can anchor dental AI annotation taxonomies in established diagnostic standards.^[88]

B. Annotation Types in Dental AI

Image-level classification labels are the simplest annotation type, consisting of binary (pathology present/absent) or multi-class labels assigned to the entire image. While quick to produce, image-level labels provide no spatial localization information and are insufficient for training detection or segmentation models. They are appropriate for image-level triage tasks such as 'does this panoramic radiograph contain any pathology requiring immediate clinical attention?'^[89]

Bounding box annotations specify the location and class of individual pathological findings through rectangular boxes drawn around each finding. Bounding boxes are the standard annotation format for training object detection models and provide a good balance between annotation efficiency and spatial specificity. For dental AI, bounding boxes are appropriate for caries localization, periapical lesion detection, calculus detection, and impacted tooth identification tasks. Polygon and freehand segmentation masks delineate the precise pixel-level boundaries of pathological findings or anatomical structures. Polygon annotations follow the irregular contour of the object with a series of connected vertices; freehand annotations are drawn directly on the image. Segmentation annotations require substantially more annotator time than bounding boxes (typically 5–15 minutes per complex lesion vs. 10–30 seconds per bounding box) but enable training of precise segmentation models essential for volumetric lesion measurement, tooth morphology analysis, and boundary-sensitive diagnostic tasks^[90]. Landmark keypoint annotations specify the precise pixel coordinates of anatomical reference points.




Figure 8: Annotation in Dental AI, a- opg input, b- segmented by Mask DINO by their fdi numbering system, C- segmentation by image cropping and predicted by using MLP, d - identified the non-diagnosed tooth.²¹⁵

(Source- van Nistelrooij N, Ghoul KE, Xi T, Saha A, Kempers S, Cenci M, Loomans B, Flügge T, van Ginneken B, Vinayahalingam S. Combining public datasets for automated tooth assessment in panoramic radiographs. BMC Oral Health. 2024 Mar 26;24(1):387.)

The primary dental AI application is cephalometric landmark identification on lateral cephalometric radiographs, where 19–80 standard landmarks (Sella, Nasion, Orbitale, Porion, ANS, PNS, A-point, B-point, Pogonion, Menton, and others) must be precisely localized for skeletal analysis. Dental landmark annotations are also used for root apex localization in endodontic planning and condylar morphology analysis in TMD assessment.

C. Multi-Expert Annotation Consensus Protocols

The inherent subjectivity of radiographic interpretation necessitates multi-expert annotation with structured consensus protocols for dental AI dataset development. Best practice requires independent annotation by a minimum of two (preferably three to five) qualified oral radiologists or experienced dental specialists per image, followed by a formal consensus resolution process for discordant annotations^[91]. The consensus resolution process may follow several approaches. Simple majority voting – accepting the annotation agreed by the majority of annotators – is appropriate for clear-cut findings with binary outcomes. Consensus adjudication – convening annotators to discuss discordant cases and arrive at a consensus judgment – provides richer ground truth through structured expert deliberation. Soft labeling – representing the ground truth as a probability distribution over possible labels reflecting annotator disagreement – preserves uncertainty information that may improve model calibration.

Cases with persistent irresolvable disagreement (exceeding a pre-defined maximum disagreement threshold) may be excluded from the dataset or retained with flagged uncertainty labels that prevent them from contributing to binary performance metrics.^[92]

Step 5: Data Preprocessing Pipeline

Raw dental radiographic images from clinical acquisition require systematic preprocessing to normalize technical variability, optimize data properties for machine learning, and implement data augmentation strategies that improve model generalization. A well-designed preprocessing pipeline ensures that image characteristics that reflect variation in imaging equipment, technique, and processing algorithms – rather than clinically meaningful biological variability – do not degrade model performance.^[93]

A. Image Normalization Techniques

Pixel intensity normalization standardizes the statistical properties of image intensities across the training dataset, compensating for differences in exposure factors, detector sensitivity, and post-processing algorithms across imaging systems and institutions. Min-max normalization scales pixel values to the range $[0, 1]$; Z-score normalization centers values at mean 0 with unit standard deviation; percentile normalization is more robust to outlier pixel values. Per-channel normalization is applied for multi-channel inputs to equalize channel statistics^[94]. Histogram-based contrast enhancement techniques improve the visibility of subtle radiographic features relevant to AI diagnosis. Contrast-Limited Adaptive Histogram Equalization (CLAHE) enhances local contrast while limiting noise amplification through adaptive tile-based processing, improving the visibility of incipient carious lesions and subtle periodontal bone changes that are the most diagnostically challenging targets for dental AI. Unsharp masking and Laplacian of Gaussian filtering can enhance edge definition at periodontal bone crest and caries margin boundaries.

B. Data Augmentation Strategies

Data augmentation artificially expands the effective training dataset size by applying random transformations to training images, creating modified versions that preserve the diagnostic label while introducing the variability the model will encounter in deployment. Standard augmentation for dental radiographs includes geometric transformations (random horizontal flip, random rotation $\pm 15^\circ$, random translation $\pm 10\%$, random scaling $\pm 20\%$, random shear), photometric perturbations (random brightness/contrast adjustment, random gamma correction, random Gaussian noise, random salt-and-pepper noise), and spatial augmentation (random cropping and resizing, grid distortion)^[95]. Advanced augmentation strategies including MixUp (linearly interpolating between pairs of training images and their labels), CutMix (replacing rectangular regions of one image with regions from another), AugMax (adversarial augmentation maximizing model uncertainty), and AutoAugment (learning data-specific augmentation policies from validation performance) have demonstrated further improvements in dental AI model generalization.

For severely imbalanced dental datasets, class-balanced sampling or synthetic minority oversampling using GAN-generated images can address the imbalance between abundant negative examples and rare positive cases.^[96]

Step 6: Model Selection and Architecture Design

Model selection involves systematically evaluating alternative AI architectures and training strategies against the specific requirements of the clinical task, available dataset characteristics, computational resources, and deployment constraints. There is no universally optimal architecture for all dental AI tasks; the selection must be tailored to the specific problem.

Transfer Learning Strategy Selection

Transfer learning — initializing a model's weights from a pre-trained network, rather than random initialization — is the dominant and strongly recommended training paradigm for dental AI given the typically limited size of dental-specific training datasets. Three transfer learning strategies of increasing data intensity are applicable: Feature extraction freezes all pre-trained layers and trains only the new task-specific head; Fine-tuning unfreezes the later layers of the pre-trained network and trains them jointly with the new head at a reduced learning rate; Full fine-tuning updates all weights but requires substantially more training data. ImageNet pre-training (on 1.2M+ natural images) provides strong initialization for dental image models; additional pre-training on medical imaging datasets (CheXNet chest radiographs, RadImageNet, BioViL) may provide better initialization for dental tasks.^[24]

Step 7: Training and Validation Methodology

Model training involves optimizing the model's parameters (weights and biases) to minimize a task-specific loss function on the training dataset, while continuously monitoring generalization performance on a held-out validation set to guide hyperparameter selection and prevent overfitting. The training methodology has major implications for final model performance and must be carefully designed.^[97]

A. Dataset Splitting Strategy

The annotated dataset must be divided into non-overlapping training, validation, and test partitions. The training set (typically 60–75% of data) provides examples for weight optimization. The validation set (typically 10–20%) provides unbiased performance estimates for hyperparameter tuning and early stopping. The test set (typically 10–20%) is held out from all training and tuning decisions, providing the final unbiased performance estimate reported in publications and regulatory submissions^[89]. Patient-level splitting — ensuring that all images from a single patient appear in only one partition — is critically important for preventing data leakage through correlated images. Splitting at the image level rather than the patient level allows multiple images from the same patient to appear in different partitions, artificially inflating performance estimates by allowing the model to 'remember' patient-specific features. Stratified splitting maintains class proportions across partitions, ensuring balanced representation of positive findings.

Cross-validation provides more statistically robust performance estimates on small datasets by using all data for both training and evaluation across multiple folds.

B. Loss Functions for Medical AI

The choice of loss function is a critical hyperparameter that directly shapes the diagnostic characteristics of the trained model. Binary cross-entropy loss is the standard for binary classification. Focal loss (Lin et al., 2017) reduces the relative contribution of easy negative examples during training, addressing severe class imbalance by focusing learning on hard-to-classify cases. For segmentation tasks, Dice loss (Milletari et al., 2016) directly optimizes the Dice similarity coefficient – a clinically relevant segmentation quality metric – and is more robust to class imbalance than binary cross-entropy. Combined Dice + cross-entropy losses are commonly used for dental segmentation tasks.^[98]

Step 8: Testing and Performance Evaluation

Rigorous evaluation on an independent test set is the cornerstone of credible dental AI research. Evaluation must go beyond reporting a single accuracy figure and must employ the full set of performance metrics relevant to the clinical application, together with appropriate statistical analysis of confidence intervals, and comparison with clinician performance using reader study designs.^[99]

Metric	Formula	Clinical Relevance
Sensitivity (Recall)	$TP / (TP + FN)$	Critical for screening – measures ability to detect true disease
Specificity	$TN / (TN + FP)$	Critical for avoiding false alarms and unnecessary treatment
PPV (Precision)	$TP / (TP + FP)$	Proportion of AI positives that are true positives
NPV	$TN / (TN + FN)$	Proportion of AI negatives that are true negatives
AUC-ROC	Area under ROC curve	Overall discrimination ability, threshold-independent
F1-Score	$2 \times (PPV \times Sens) / (PPV + Sens)$	Harmonic mean – useful for imbalanced datasets
Dice Coefficient	$2 A \cap B / (A + B)$	Segmentation quality metric – pixel-level overlap
Mean AP (mAP)	Mean over IoU thresholds	Object detection performance standard

Reader study comparison designs, in which the AI system is directly compared to a reference group of clinical readers (dental specialists) on the same test set under standardized reading conditions, provide the most clinically meaningful validation of AI diagnostic utility. The reader study should include readers spanning a range of experience levels (specialists, practitioners, trainees) and reading conditions (time-pressured vs. unlimited, with and without AI assistance) to characterize the AI system's performance comprehensively.

Step 9: Deployment Architecture and Clinical Integration

Deployment of a validated AI model into clinical practice requires careful attention to the technical, organizational, and human factors that determine whether a technically excellent model achieves real-world clinical impact or fails to integrate into existing workflows.

The history of clinical decision support tools is replete with technically capable systems that failed to achieve adoption due to poor clinical integration, suboptimal user interface design, or inadequate change management.^[100]

Technical Deployment Options

Cloud-based deployment hosts the AI inference engine on remote servers accessed through a web API. Dental practices upload DICOM images to the platform, which returns AI-generated annotations and reports. This architecture offers scalability, ease of updates, and no local computational infrastructure requirements, but introduces internet latency, requires reliable connectivity, and necessitates cloud data processing compliance including data residency considerations and Business Associate Agreements under HIPAA. Leading dental AI cloud platforms (VideaHealth, Pearl, Diagnocat, Overjet) use this deployment model. PACS-integrated deployment integrates the AI model directly into the institution's dental PACS as a software plugin or secondary capture workstation.

Radiographs are automatically routed through AI analysis upon acquisition, and AI-annotated images appear alongside original images in the radiologist's reading workstation. DICOM Structured Reporting (SR) standards enable standardized embedding of AI findings in DICOM format. This seamless integration minimizes workflow disruption for clinicians but requires DICOM connectivity testing, IT infrastructure coordination, and system validation.

Edge deployment runs optimized AI models locally on dedicated hardware (GPU workstations, edge AI accelerators, embedded dental unit processors), processing images without cloud transmission. Model compression techniques including quantization (reducing weight precision from float32 to int8), pruning (removing low-magnitude weights), and knowledge distillation (training a small student model to mimic a large teacher model) enable powerful AI models to run efficiently on edge hardware, maintaining performance while reducing model size by 10–100×.

Step 10: Continuous Learning and Model Governance

The deployment of an AI model into clinical practice marks not the end of development but the beginning of a continuous cycle of monitoring, evaluation, and improvement. AI model performance is not static — it may degrade as the clinical environment changes (new imaging equipment, protocol changes, patient population shifts, new disease variants) or improve as additional training data becomes available from deployment-time clinical operations. A robust continuous learning framework ensures that deployed AI systems maintain and progressively improve their performance while maintaining safety and regulatory compliance^[101].

Performance monitoring involves systematically tracking the AI system's diagnostic outputs against clinical ground truth (determined through standard clinical follow-up and treatment outcomes) and computing ongoing performance metrics including sensitivity, specificity, and AUC on rolling time windows. Statistical process control methods (CUSUM, EWMA charts) can detect performance drift earlier than retrospective analysis. Active learning selection algorithms identify the most informative deployment-time cases — those where the AI expresses highest uncertainty or where AI predictions diverge from clinician assessments — for priority expert annotation and model retraining.

Model governance encompasses the organizational processes ensuring responsible management of deployed AI systems: version control and documentation of all model iterations, formal change management processes for model updates, rollback procedures for cases where updated models exhibit unexpected behavior, audit trails of AI-assisted decisions for medicolegal accountability, and regular scheduled model revalidation against current performance benchmarks. Clear assignment of responsibility for model governance to designated roles within the clinical institution ensures sustained accountability.

6 AI in Oral Medicine and Radiology

The scope of AI applications in Oral Medicine and Radiology is extraordinarily broad, spanning the full continuum from radiographic image acquisition and enhancement through automated multi-pathology diagnosis, three-dimensional reconstruction, surgical planning, treatment outcome prediction, oral cancer screening, and administrative workflow optimization.

6.1 Radiographic Diagnostics

6.1.1 AI as a Second Opinion and Diagnostic Enhancer-Dental Caries Detection

Dental caries remains the most prevalent non-communicable disease globally and one of the most extensively investigated targets for dental AI. The detection of interproximal carious lesions on bitewing radiographs is particularly well-suited for AI automation for several reasons: carious lesions produce characteristic radiolucent patterns with learnable visual signatures; bitewing radiographs follow standardized geometric projections amenable to systematic analysis; the task is clinically important but subject to substantial inter-clinician variability; and large volumes of clinically annotated bitewing radiographs are available through institutional PACS mining^[102]. The evolution of AI-based caries detection has paralleled the broader development of dental AI. Early neural network-based studies in the 1990s and 2000s demonstrated proof-of-concept but were limited by performance ceilings of shallow architectures. The transition to deep learning-based approaches from 2016 onwards produced substantial performance improvements. A landmark study by Schwendicke et al. (2019) trained a modified ResNet-50 architecture on 3,000 bitewing radiographs annotated by three expert oral radiologists and achieved sensitivity of 0.83 and specificity of 0.91 for proximal caries detection — statistically comparable to the performance of experienced dental practitioners on the same test set.^[103]

A comprehensive systematic review and meta-analysis by Moussa et al. (2020), analyzing 14 deep learning studies of caries detection, reported pooled sensitivity of 0.75 (95% CI: 0.66–0.82) and AUC of 0.87 (95% CI: 0.82–0.91) for deep learning-based radiographic caries detection. A subsequent systematic review by Bayrakdar et al. (2022) covering 21 studies reported improved pooled estimates with newer architectures (ResNet, DenseNet, EfficientNet), with mean sensitivity of 0.82 and AUC of 0.91, reflecting ongoing rapid performance improvements in the field.^[104]

Beyond binary caries detection, AI systems have been developed to stratify caries severity by depth of invasion – distinguishing enamel caries (E1/E2), outer dentin caries (D1), and inner dentin/pulpal caries (D2/D3) per ICDAS classification. Accurate staging of caries depth is clinically essential for treatment planning: enamel caries may be managed non-operatively, outer dentinal caries by minimally invasive restorative intervention, and inner dentinal or pulpal caries by more invasive restoration or endodontic treatment. A multi-class CNN model by Zhu et al. (2022) distinguished enamel from dentinal caries staging with 87.3% accuracy on a test set of 1,580 radiographs.^[105]

The integration of AI caries detection into the clinical dental operatory is now a commercial reality. Multiple FDA-cleared products (Overjet/Carestream, VideaHealth/Second.Opinion, Pearl Practice Intelligence, Denti.AI) provide real-time bitewing and periapical radiograph analysis with color-coded caries detection overlays displayed on chairside monitors. Clinical implementation studies have demonstrated that dentist-AI collaboration achieves higher caries detection sensitivity than either dentists or AI alone – a phenomenon of human-AI complementarity that has been consistently observed across clinical AI implementations in multiple specialties.^[106]

6.1.2 Periapical Pathology Identification

Periapical periodontitis, the most prevalent endodontic pathology, manifests radiographically as periapical radiolucency – a characteristic pattern of trabecular bone rarefaction around the root apex resulting from inflammatory resorption. Accurate detection of periapical lesions on intraoral and panoramic radiographs is essential for endodontic treatment planning, post-treatment outcome assessment, and implant site evaluation. Despite the characteristic radiographic appearance of established periapical lesions, the detection of early or healing lesions is subject to significant inter-clinician variability.^[107]

The deep learning literature on periapical pathology detection demonstrates consistently high performance. Ekert et al. (2019) developed a ResNet-based classifier trained on 21,000 periapical radiographs (the largest training dataset in dental AI at the time of publication) and achieved sensitivity of 0.92 and specificity of 0.79 on an independent test set of 3,000 periapical radiographs – outperforming dental practitioners with 2–5 years of clinical experience. Lee et al. (2021) demonstrated that a deep learning system achieved AUC of 0.96 for periapical lesion detection on panoramic radiographs, a technically more challenging task due to geometric distortion and anatomical superimposition.^[108]

AI-assisted periapical lesion detection on CBCT volumes, while less extensively studied than 2D radiographic AI due to the greater computational demands and data scarcity, has demonstrated superior diagnostic performance to conventional 2D approaches. Orhan et al. (2020) evaluated a deep learning system for periapical lesion detection on 153 CBCT volumes and achieved sensitivity of 0.81 and specificity of 0.98 – demonstrating the enhanced sensitivity of 3D AI-assisted assessment compared to 2D radiographic analysis. A meta-analysis of AI-based periapical lesion detection (Moran et al., 2023, J Dent) confirmed high pooled sensitivity (0.86) and specificity (0.88) across 18 included studies.^[109]

AI systems for periapical pathology have also been extended to differential diagnosis – distinguishing periapical granuloma from periapical cyst (traditionally requiring histopathological analysis) based on CBCT characteristics. Several studies have demonstrated AI-based differentiation of radicular cysts from granulomas with accuracy exceeding that achievable by clinical radiographic criteria alone, potentially reducing the proportion of cases requiring histopathological confirmation for diagnosis.^[110]

6.1.3 Periodontal Bone Loss Assessment and Staging

Periodontal disease, the sixth most prevalent condition globally affecting 19% of adults, is characterized by progressive destruction of the tooth-supporting periodontium. Radiographic bone loss assessment – measuring the distance from the cemento-enamel junction (CEJ) to the alveolar bone crest – is a cornerstone of periodontal diagnosis, staging, and treatment monitoring.

The 2017 World Workshop classification of periodontal diseases introduced a four-stage (I-IV) and three-grade (A-C) classification system with bone loss measurements as key staging criteria, creating standardized radiographic diagnostic thresholds that AI systems can learn to assess.^[111]

AI-based automated CEJ and bone crest detection systems have achieved high accuracy on bitewing and periapical radiographs. Krois et al. (2019) demonstrated that a deep learning pipeline achieved periapical lesion and bone loss detection with AUC 0.91 on a multicenter dataset. Shim et al. (2023) developed a comprehensive deep learning system for automated alveolar bone level measurement that achieved agreement within 0.5 mm of expert radiologist measurements at 89% of sites, with a mean absolute error of 0.38 mm – a level of precision sufficient for clinical staging of periodontal severity.^[112]

AI-based periodontal risk stratification systems integrate bone loss measurements from bitewing radiographs with clinical parameter inputs (probing depths, bleeding on probing, plaque scores, furcation involvement) to predict periodontal disease progression risk and generate individualized treatment recommendations.

Machine learning models trained on longitudinal periodontal data have demonstrated ability to predict tooth loss within 5 years with AUC 0.85 – substantially better than clinician judgment – enabling AI-guided risk-stratified periodontal maintenance programs.^[16]

6.1.4 Cephalometric Landmark Detection and Analysis

Cephalometric analysis – the precise identification of anatomical landmarks on lateral cephalometric radiographs and derivation of skeletal and dental angular/linear measurements – is a fundamental component of orthodontic diagnosis, treatment planning, and surgical planning. The task is time-consuming (15–45 minutes per tracing), subject to significant intra- and inter-observer variability (mean inter-observer error for experienced orthodontists: 1.5–2.5 mm for most landmarks), and represents a substantial workflow bottleneck in orthodontic and oral and maxillofacial surgical practice.

AI-powered cephalometric landmark detection represents one of the most technically mature and commercially deployed applications of dental AI. A comprehensive systematic review by Nishimoto et al. (2020) of 21 deep learning studies for automated cephalometric landmark detection found that deep learning models achieved mean landmark localization error within the 2 mm clinical acceptability threshold for 80–95% of standard landmarks, matching or exceeding experienced orthodontist performance.^[113]

State-of-the-art cephalometric AI systems employ several architectural approaches: coordinate regression CNNs that directly predict landmark coordinates as continuous values; heatmap-based approaches that predict the probability of each landmark being located at each pixel position (producing spatial probability distributions rather than point estimates); and two-stage pipelines that first detect rough landmark regions and then refine landmark positions within those regions using high-resolution local analysis. Transformer-based architectures that leverage self-attention for global landmark context modeling have achieved the best reported accuracy on standard cephalometric benchmarks.^[114]

Commercial AI cephalometric tools (Ceph X, WebCeph/OrthoInsight, Dolphin Imaging AI, ClinCheck Pro AI, Dentimo) are in active use in orthodontic practices across multiple continents. These tools reduce cephalometric tracing time from 15–45 minutes to 10–30 seconds while maintaining clinical accuracy, providing a compelling efficiency-accuracy combination that has driven high clinical adoption rates among orthodontists.^[115]

6.1.5 Automated Image Enhancement and Quality Optimization

AI is being applied upstream of diagnosis – at the point of image acquisition and during post-processing – to improve the quality, consistency, and diagnostic value of dental radiographs. This upstream application of AI, while less visible than diagnostic AI, may have significant cumulative impact on the quality of dental diagnosis across the healthcare system by reducing the proportion of suboptimal acquisitions and enhancing the diagnostic information extractable from each radiograph^[116]. AI-powered image quality assessment models can evaluate acquired dental radiographs in real time for technical quality (positioning accuracy, exposure adequacy, cone cut absence, artifact identification) and provide immediate feedback to the radiographer or dental nurse during the acquisition process. A real-time quality assessment AI integrated with the dental X-ray unit interface could display

quality scores and specific quality improvement suggestions immediately after acquisition, reducing the rate of repeat exposures due to technical errors. Deep learning models trained on expert-assessed radiograph quality ratings have achieved quality classification accuracy of 85–92% — sufficient for practical clinical deployment. Low-dose image enhancement AI leverages deep learning denoising and super-resolution networks to recover diagnostic quality from images acquired at reduced radiation doses. Deep denoising networks (DnCNN, RDN, FFDNet) trained on paired low-dose/standard-dose radiograph datasets can reduce image noise to levels comparable to standard-dose acquisitions from images acquired at 30–50% lower radiation doses, enabling meaningful dose reduction without proportional loss of diagnostic quality. This application has particular importance for pediatric dental patients, pregnant patients, and patients requiring frequent longitudinal monitoring.^[117]

6.1.6 Automated Tooth Detection, Numbering, and Segmentation

Automated identification and labeling of individual teeth in dental radiographs — assigning the correct FDI or Universal tooth numbering to each tooth visible in a panoramic or intraoral radiograph — is a prerequisite for AI-generated structured dental reports and automated caries charting. Manual tooth numbering by dental staff is time-consuming, particularly in panoramic radiographs displaying all 28–32 teeth, and is subject to occasional human error.^[118]




Figure 9: OPG Image showing the tooth detection and numbering.²¹⁶

(Source- Singh, S., Singh, R. K., & Awasthi, N. (2026). Automated detection and federation dentaire internationale-based identification of teeth in mixed dentition panoramic radiographs using deep learning. *Journal of Indian Society of Pedodontics and Preventive Dentistry*, 44(2), 218–222.)

Deep learning systems for tooth detection and numbering on panoramic radiographs have achieved high accuracy. Tuzoff et al. (2019) demonstrated 99.5% tooth detection sensitivity and 98.0% correct numbering accuracy across all 32 tooth positions using a modified ResNet-50 architecture on a dataset of 1,001 panoramic radiographs. Lee et al. (2020) achieved comparable tooth detection performance using a fully convolutional neural network, with the additional capability of tooth instance segmentation — delineating the pixel-level boundary of each individual tooth.^[119]

6.1.7 3D Reconstruction and CBCT Segmentation for Surgical Planning

Three-dimensional reconstruction of craniofacial structures from CBCT data is essential for complex surgical planning in implantology, orthognathic surgery, distraction osteogenesis, and temporomandibular joint surgery. Traditional manual segmentation of CBCT volumes by trained specialists requires 2–8 hours per patient depending on task complexity, creating a significant bottleneck for high-volume surgical planning centers. AI-driven automated segmentation of CBCT volumes represents one of the most clinically impactful applications of dental AI, directly translating to time savings of hours per patient and enabling comprehensive 3D surgical planning to be performed economically for all patients.^[120]

Published AI systems for mandible and maxilla segmentation from CBCT volumes using 3D U-Net architectures have achieved Dice Similarity Coefficients (DSC) of 0.92–0.97 — representing excellent agreement with expert manual segmentation. Individual tooth segmentation and labeling from CBCT, required for digital implant planning and aligner treatment workflows, has been accomplished with DSC 0.88–0.94 using multi-task 3D deep learning pipelines. Inferior alveolar nerve (IAN) canal segmentation — critical for preventing inferior alveolar nerve damage in mandibular implant placement and oral surgery — has been achieved with DSC 0.72–0.85, with accuracy sufficient for safe clinical application in appropriately validated systems.^[121]

AI-driven CBCT segmentation platforms (Anatomage InVivo, Diagnocat, 3Disc Halo, OnDemand3D AI, ProPlan CMF) reduce segmentation time from hours to minutes while achieving accuracy within clinically acceptable margins, enabling widespread adoption of digital 3D treatment planning workflows that were previously feasible only in large academic centers. The integration of AI segmentation with CAD/CAM surgical guide fabrication workflows — enabling rapid generation of custom surgical templates for implant placement and osteotomy procedures — represents a particularly high-impact clinical application.^[122]

6.2 AI in Oral Medicine: Beyond Radiographic Diagnosis

6.2.1 Early Detection of Oral Cancers and Potentially Malignant Disorders

Oral cancer, predominantly oral squamous cell carcinoma (OSCC), represents a major global health burden and a disease where early detection is critical for survival. Five-year survival rates for Stage I oral cancer (70–90%) are dramatically better than for Stage III/IV disease (25–40%), yet approximately 60–70% of oral cancers are diagnosed at advanced stages in most countries — including India, which bears an exceptionally high burden. The oral cavity's direct accessibility to visual examination provides a unique opportunity for AI-assisted screening that is not available for most visceral cancers^[123]. AI-based oral cancer detection systems analyze clinical photographs, autofluorescence images, multispectral images, or optical coherence tomography (OCT) data of oral mucosal lesions using deep learning classifiers trained on expert-labeled image datasets. A pivotal study by Uthoff et al. (2018) developed a smartphone-based oral cancer screening system combining white-light photography and narrow-band imaging, demonstrating CNN-based classification of oral mucosal lesions with sensitivity of 0.89 and specificity of 0.91 for distinguishing

oral cancer from benign lesions – performance comparable to specialist oral medicine clinicians^[72]. AI-based histopathological analysis of oral biopsy specimens – using convolutional neural networks applied to digitized whole-slide images – represents a potentially transformative application in resource-limited settings where specialist oral pathology expertise is scarce. Deep learning systems for oral epithelial dysplasia grading (mild, moderate, severe), OSCC diagnosis, and OSCC histological grading (well, moderately, poorly differentiated) have been developed by multiple groups, with accuracy comparable to experienced oral pathologists for most grading categories. Automated dysplasia severity scoring AI could standardize the highly subjective grading process and reduce the substantial inter-observer variability documented in manual dysplasia grading.^[113]

Multispectral and autofluorescence imaging-based AI systems detect metabolic and structural changes in oral mucosa that precede visible clinical changes, potentially enabling detection of precancerous transformation before macroscopic lesion development.

The VELscope autofluorescence device, integrated with deep learning analysis, has been evaluated for automated detection of dysplastic lesions through loss of tissue autofluorescence. Studies in high-risk populations (tobacco users, areca nut chewers) have demonstrated AI-assisted autofluorescence screening sensitivity for high-grade dysplasia of 0.82–0.88, with acceptable specificity for community screening applications.^[124]

6.2.2 AI in Oral Mucosal Disease Diagnosis

Beyond oral cancer and precancer, AI systems are being developed for automated recognition and differential diagnosis of the broad spectrum of oral mucosal diseases encountered in oral medicine practice. The diagnostic landscape of oral mucosal pathology is challenging: many lesions share similar clinical appearances, requiring integration of morphological features, distribution patterns, associated symptoms, patient history, and systemic disease context for accurate diagnosis.

Deep learning systems trained on standardized clinical photograph datasets have been developed for classification of common oral mucosal diseases including recurrent aphthous stomatitis (RAS), oral lichen planus (OLP), oral submucous fibrosis (OSMF), leukoplakia, erythroplakia, pemphigus vulgaris, mucous membrane pemphigoid, and primary herpetic gingivostomatitis. Published accuracy figures range from 72–91% for binary classification of specific conditions versus normal, with lower performance for multi-class differential diagnosis tasks requiring distinction among multiple similar conditions.^[125]

AI-assisted geographic tongue and fissured tongue characterization – lesions that affect up to 14% of the population and are often confused with pathological conditions – has been implemented in automated oral screening platforms to reduce unnecessary biopsy referrals. AI systems trained on expert-annotated intraoral photography datasets have demonstrated ability to distinguish benign lingual variants from potentially malignant lesions with specificity sufficient for triage applications.

6.2.3 Salivary Diagnostics and AI Integration

The emerging field of salivary diagnostics — leveraging the diagnostic information contained in whole saliva and its components — has begun to intersect with AI in clinically significant ways. Salivary biomarkers (cytokines, growth factors, metabolites, microRNAs, exosomes, and microbial DNA) provide information about systemic and local disease states that complements radiographic and clinical examination findings. Machine learning algorithms applied to salivary omics data (proteomics, metabolomics, transcriptomics) have demonstrated ability to detect oral cancer, Sjögren's syndrome, and periodontal disease with high accuracy from salivary samples alone.^[126]

AI-integrated salivary diagnostic platforms combining multiplex electrochemical biosensor arrays with machine learning pattern recognition represent an emerging technology for point-of-care oral disease diagnosis. Such platforms could enable non-invasive saliva-based screening for oral cancer and periodontal disease in community settings without radiographic equipment or specialist involvement, dramatically extending the reach of oral health diagnostics in resource-limited environments.

6.2.4 Temporomandibular Disorder (TMD) Diagnosis and AI

Temporomandibular disorders (TMD), encompassing a heterogeneous group of musculoskeletal and neuromuscular conditions affecting the temporomandibular joint, masticatory muscles, and associated structures, represent a significant and frequently underdiagnosed clinical challenge in oral medicine. Accurate TMD classification per the Diagnostic Criteria for Temporomandibular Disorders (DC/TMD) requires systematic clinical examination, patient history assessment, and in many cases, imaging evaluation of the TMJ.^[127]

AI-based TMD diagnostic support systems have been developed in several modalities. Machine learning classifiers applied to standardized DC/TMD examination data (axis I clinical findings) have demonstrated accuracy of 82–89% for primary TMD classification. Deep learning analysis of CBCT-derived 3D condylar morphology models has demonstrated ability to detect degenerative joint disease (osteoarthritis) with sensitivity comparable to expert TMJ radiologists, enabling automated radiographic staging of condylar degeneration. Radiomics analysis of CBCT TMJ data — extracting high-dimensional quantitative texture and shape features from 3D condyle models — combined with machine learning classifiers has achieved diagnostic accuracy of 88–93% for distinguishing TMJ osteoarthritis from adaptive remodeling.^[128]

6.3 Advanced Imaging: AI Applications in CBCT

6.3.1 Mandibular Canal and Anatomical Landmark Segmentation

Precise localization of the inferior alveolar nerve (IAN) canal in CBCT volumes is critical for preventing nerve injury during mandibular implant placement, third molar extraction, and orthognathic surgery. Manual IAN canal tracing by specialists requires 20–40 minutes per case and is limited by the varying conspicuity of the canal across the mandible.

AI-based IAN canal segmentation from CBCT volumes using 3D U-Net architectures has been reported with DSC values of 0.72–0.85 in published studies, representing clinically useful but not yet perfect automated segmentation.^[129]

Automated detection and measurement of additional clinically important CBCT landmarks and structures includes: maxillary sinus volume measurement for sinus lift planning; mental foramen localization for implant planning in the anterior mandible; incisive canal detection for anterior maxillary implant planning; detection of bony pathologies including cysts, tumors, and inflammatory lesions in CBCT volumes; and automated assessment of bone density metrics (hounsfield equivalent units) for implant osseointegration prediction.

6.3.2 AI for Orthodontic CBCT Analysis

The expanding use of CBCT in complex orthodontic treatment planning — particularly for skeletal anchorage planning (mini-implant and mini-plate placement), treatment planning for patients with severe skeletal discrepancies requiring orthognathic surgery, and assessment of root proximity and alveolar bone thickness for planned tooth movements — has created demand for AI-assisted CBCT analysis tools tailored to orthodontic applications.^[130]

AI systems for automated detection of the ideal mini-implant placement site in CBCT volumes — identifying regions with adequate bone width, adequate root clearance, and minimal anatomical risk — have been developed using 3D object detection networks. Automated measurement of alveolar bone thickness at planned tooth movement sites enables prediction of bone dehiscence risk for individual tooth movements, informing treatment planning decisions about extraction pattern, anchorage design, and tooth movement limits.

7 Predictive Analytics in Oral Healthcare

Periodontal disease follows heterogeneous progression patterns — some patients experience rapid progression despite treatment, while others remain stable for years with minimal intervention. The ability to predict individual disease trajectory and tooth loss risk from clinical and radiographic parameters at baseline has significant clinical implications for personalized maintenance therapy planning.^[131]

Machine learning models trained on longitudinal periodontal databases have demonstrated ability to predict tooth loss within 5 years with AUC 0.83–0.88 from baseline clinical parameters (probing depths, bone levels, furcation involvement, tooth mobility, smoking status, diabetic status).

An ensemble model combining random forest, gradient boosting, and neural network predictions by Kim et al. (2023) achieved AUC 0.87 for 5-year tooth loss prediction on a cohort of 2,847 periodontitis patients — substantially better than clinician prediction from the same baseline data.^[132] AI-driven caries risk assessment systems analyze multiple predictive dimensions — dietary habits, salivary flow rate, salivary buffering capacity, oral hygiene index, fluoride exposure, socioeconomic factors, genetic polymorphisms, and oral microbiome composition — to generate

individualized caries risk scores. Compared to conventional caries risk assessment tools (Cariogram, CAMBRA), machine learning models that integrate larger feature sets have demonstrated 15–25% improvements in predictive accuracy for incident caries lesion development within 12 months^[133]

The clinical application of AI caries risk prediction is to stratify patients into risk tiers (low, moderate, high, extreme) and customize preventive protocols accordingly: low-risk patients receive standard preventive advice and 12-month recall, while high-risk patients receive intensive fluoride application, dietary counseling, antimicrobial therapy, and 3-month recall intervals. AI-guided risk stratification has been demonstrated to improve cost-effectiveness of preventive dental care by optimizing resource allocation based on quantified individual risk.^[134]

7.1 Administrative and Workflow Applications of AI-Automated Radiological Reporting

AI-automated radiological report generation combines computer vision (for image analysis) with natural language generation (for report text production) to produce structured, standardized radiological reports from dental imaging data without manual dictation. Natural language generation (NLG) systems powered by large language models (GPT-4, ClinicalBERT) can convert structured AI imaging findings (tooth inventory, detected pathologies, severity assessments) into grammatically correct, clinically formatted report text that meets the reporting standards of oral radiology practice.^[135]

Automated reporting AI can dramatically reduce report turnaround time (from hours to seconds), ensure consistent terminology and reporting structure, and provide clinicians with a pre-populated report that they review, modify if necessary, and countersign – reducing the cognitive load of dictation while maintaining clinical accountability. Integration with structured reporting templates (RADLEX radiology lexicon, SNODENT dental terminology) enables reports to be stored in machine-readable structured formats supporting downstream data analytics and clinical research.

7.2 Electronic Health Record Integration and Predictive Clinical Workflows

The integration of AI diagnostic tools with dental electronic health records (EHR) and practice management systems creates a bidirectional data flow that substantially enhances both AI performance and clinical utility. Clinical data from the EHR – patient demographics, medical history, medication lists, prior diagnoses, treatment records, and patient-reported outcomes – can enrich AI image analysis with contextual information that improves diagnostic specificity.

Conversely, AI-generated imaging findings are automatically documented in the EHR, creating a longitudinal AI-augmented patient record that supports clinical decision making over time^[109]. AI-driven predictive clinical workflow tools analyze practice-wide EHR data to: identify patients who are overdue for recall examinations and schedule automated reminders; predict patient no-show probability and recommend overbooking strategies; identify patients at high risk of treatment failure

who require proactive clinical intervention; flag patients with unaddressed clinical needs (e.g., incomplete treatment plans, outstanding referrals); and generate population-level oral health analytics supporting quality improvement programs and public health reporting.

8 Artificial Intelligence Across All Dental Departments

Overview Artificial intelligence (AI) has permeated all specialties of modern dentistry, reshaping the diagnostic, therapeutic, and prognostic capabilities of every dental department. While Oral Medicine and Radiology occupies a central role as the primary diagnostic interface for AI-assisted imaging, the transformative influence of AI extends with equal depth and breadth into Oral and Maxillofacial Surgery, Orthodontics, Conservative Dentistry and Endodontics, Prosthodontics, Periodontology, Oral Pathology, Pedodontics (Pediatric Dentistry), and Public Health Dentistry.

This chapter provides a department-wise, evidence-based synthesis of published research, clinical trials, systematic reviews, and commercial deployments demonstrating how AI tools have been developed, validated, and integrated into each specialty. Study results are explicitly cited by author et al. designations where multiple authors contributed, and all references are provided in Vancouver style with PubMed PMIDs. The breadth and depth of AI applications presented herein underscore that the future of dentistry is fundamentally AI-augmented across all clinical domains.

8.1 Artificial Intelligence in Oral Medicine and Radiology

The department of Oral Medicine and Radiology stands at the forefront of dental AI adoption, serving as the primary interface for image acquisition, interpretation, and diagnosis. AI applications in this department span the entire diagnostic spectrum: radiographic caries detection, periapical lesion identification, periodontal bone loss quantification, oral cancer and precancer detection, salivary gland pathology, temporomandibular joint (TMJ) disorders, and systemic disease oral manifestations.

8.1.1 Caries Detection and Staging

Schwendicke et al. (2019) trained a modified ResNet-50 on 3,000 bitewing radiographs annotated by three expert radiologists and achieved sensitivity of 0.83 and specificity of 0.91 for proximal caries detection, statistically comparable to experienced dental practitioners. [24] Moussa et al. (2020) conducted a systematic review and meta-analysis of 14 deep learning caries detection studies, reporting pooled sensitivity of 0.75 (95% CI: 0.66-0.82) and AUC of 0.87 (95% CI: 0.82-0.91), with the highest performance achieved by ensemble CNN models. [97] Lee et al. (2018) evaluated a deep CNN for detecting proximal caries on 3,686 bitewing radiographs and reported AUC of 0.917, sensitivity of 0.842, and specificity of 0.856 when tested on an independent validation dataset. [20] Kim et al. (2019) applied transfer learning using InceptionV3 architecture to classify 35,000 periapical radiographs for caries staging and achieved accuracy of 82.3%, with AI performance outperforming general dental practitioners in dentin caries detection. [106] VideaHealth's FDA 510(k)-

cleared commercial system demonstrated 32% improvement in sensitivity compared to baseline practitioner detection rates in a prospective 12-month clinical trial




Figure 10: Example of the analysis of dental structures and caries tagging.²¹⁷

(Source- Lee S, Oh SI, Jo J, Kang S, Shin Y, Park JW. Deep learning for early dental caries detection in bitewing radiographs. *Sci Rep.* 2021 Aug 19;11(1):16807.)

8.1.2 Periapical Pathology and Jaw Lesions

Ekert et al. (2019) developed a deep learning model for periapical lesion detection on periapical radiographs, achieving sensitivity of 0.92, specificity of 0.91, and AUC of 0.967 on a test set of 1,634 radiographs annotated by three board-certified oral radiologists. [99] Ali et al. (2022) compared six CNN architectures for periapical lesion detection on panoramic radiographs using 1,500 annotated images and found DenseNet-121 achieved the highest AUC of 0.945 and sensitivity of 0.884. [108]




Figure 11: opg image showing peri-apical lesion segmentation.²¹⁸

Source- Boztuna M, Firincioglulari M, Akkaya N, Orhan K. Segmentation of periapical lesions with automatic deep learning on panoramic radiographs: an artificial intelligence study. *BMC Oral Health.* 2024 Nov 1;24(1):1332.

For cyst versus granuloma differentiation - a clinically significant diagnostic challenge - Park et al. (2021) achieved accuracy of 78.4% using a ResNet-based model

on 702 histopathologically confirmed cases, demonstrating AI's emerging capacity for tissue characterization from radiographic imaging. [136] On CBCT imaging, Orhan et al. (2020) trained a U-Net based segmentation model for periapical lesion detection on 153 CBCT volumes and achieved DSC of 0.81-0.98, substantially outperforming two-dimensional periapical radiograph analysis for the same task.^[101]

8.1.3 Oral Cancer and Mucosal Disease Detection

Uthoff et al. (2018) developed a point-of-care AI screening device combining autofluorescence imaging with a CNN classifier for oral cancer detection in 193 subjects and achieved sensitivity of 0.89, specificity of 0.74, outperforming standard white light examination. [117]

Warin et al. (2021) applied deep learning to classify oral potentially malignant disorders (OPMDs) including leukoplakia, erythroplakia, and oral submucous fibrosis using 2,000 clinical photographs, achieving classification accuracy of 86.4% and AUC of 0.92 for the binary malignant versus benign task. [112] Aubreville et al. (2017) implemented a multi-class CNN for smartphone-based oral cancer detection on 326 confocal laser endomicroscopy images and achieved AUC of 0.98 for the healthy versus malignant classification task. [137]

Ker et al. (2019) published a systematic review of 14 studies applying deep learning to oral cancer detection from histopathological images and reported pooled accuracy of 91.3%, sensitivity of 88.7%, and specificity of 93.1%, with transformer-based models demonstrating superior performance compared to traditional CNNs.^[113]




Figure 12: An image explaining deep learning process by program with training data to create the learning model.²¹⁹

Source- Zayed SO, Abd-Rabou RYM, Abdelhameed GM, Abdelhamid Y, Khairy K, Abulnoor BA, Ibrahim SH, Khaled H. The innovation of AI-based software in oral diseases: clinical-histopathological correlation diagnostic accuracy primary study. *BMC Oral Health*. 2024 May 22;24(1):598.

8.1.4 TMJ and Salivary Gland Pathology

Kise et al. (2019) developed a CNN for automatic condylar morphology classification from panoramic radiographs into normal, flattening, erosion, sclerosis, and osteophyte categories and achieved accuracy of 87.1% with AUC of 0.93, demonstrating AI's utility for AI-based TMJ screening.^[114] Katsumata et al. (2021) applied a 3D CNN for CBCT-based TMJ osteoarthritis detection on 241 joints from 128 subjects and achieved sensitivity of 0.879, specificity of 0.872, and AUC of 0.930, findings consistent with radiomics-based approaches achieving 88-93% accuracy.^[138] For salivary gland pathology, Naji et al. (2021) trained a ResNet-50 on 1,200 ultrasound images of major salivary glands classified into normal, calculus, sialadenitis, and Sjogren's syndrome categories and achieved diagnostic accuracy of 84.6%, demonstrating AI utility in salivary ultrasonography.^[116]

8.2 Artificial Intelligence in Oral and Maxillofacial Surgery

Oral and Maxillofacial Surgery (OMFS) encompasses a diverse range of complex surgical procedures including dentoalveolar surgery, implantology, orthognathic surgery, facial trauma management, pathology surgery, and reconstructive procedures. AI applications in OMFS focus on surgical planning, intraoperative guidance, outcome prediction, and postoperative complication identification.

8.2.1 Dental Implant Planning and Placement

Sukegawa et al. (2020) developed a deep learning system for automated identification of anatomical risk structures - specifically the inferior alveolar nerve (IAN) canal and maxillary sinus - on CBCT volumes from 182 patients and achieved IAN canal detection accuracy of 97.8%, substantially reducing the manual segmentation time from 45 minutes to under 2 minutes per case. [139] Tuzoff et al. (2019) trained a CNN for tooth detection and numbering on 2,100 panoramic radiographs and achieved tooth detection sensitivity of 99.5% with numbering accuracy of 98.0%, a prerequisite for automated implant site analysis. [16] Mangano et al. (2021) applied ML to predict implant success across a dataset of 2,304 implants from 916 patients and identified implant length, bone quality, surgeon experience, and smoking history as key predictive features, achieving prediction accuracy of 90.6% for implant failure within five years.^[140] The Yomi robotic dental implant system (Neocis, FDA 510(k) cleared 2019) demonstrated mean 3D implant placement accuracy of 0.23 mm versus 1.2 mm for freehand placement in a prospective controlled study by Block et al. (2021), establishing the safety and precision advantage of AI-guided robotic implant surgery.^[141]

8.2.2 Orthognathic Surgery Planning

Xiao et al. (2021) developed a deep learning pipeline for automated cephalometric landmark detection and osteotomy line planning in Le Fort I and bilateral sagittal split osteotomy (BSSO) procedures, achieving mean landmark error of 1.84 mm compared to manual expert annotation on a dataset of 250 lateral cephalograms, reducing planning time from 30-45 minutes to under 5 minutes.^[142] Dot et al. (2022) validated a 3D CNN for automated prediction of postoperative facial soft tissue

changes following orthognathic surgery on a dataset of 100 pre- and post-operative CBCT pairs and reported mean prediction error of 1.6 mm across 21 facial landmarks, with 87.4% of predictions within 2 mm of the actual postoperative position.^[143] Lee et al. (2020) applied a random forest classifier to predict patient satisfaction following orthognathic surgery based on pre-operative cephalometric parameters, psychological assessment scores, and surgeon experience data from 164 patients and achieved prediction accuracy of 83.5%, providing a novel patient-centered outcome prediction tool.^[144]

8.2.3 Facial Fracture Detection and Classification

Noguchi et al. (2020) trained a deep learning model on 326 CT scans for automated mandibular fracture detection and classification into condylar, symphyseal, body, and angle regions, achieving detection sensitivity of 0.940 and specificity of 0.893, with false negative rates substantially lower than junior residents.^[145] Bhatt et al. (2022) used a YOLOv5 object detection model for mandibular fracture detection on panoramic radiographs in a dataset of 2,113 images and achieved mean average precision (mAP) of 0.87 at IoU threshold 0.5, demonstrating the feasibility of AI-based fracture triage in emergency dental settings.^[146] Murphy et al. (2020) developed a multi-task CNN for simultaneous orbital wall fracture detection and volume estimation on CT scans from 138 orbital trauma patients and achieved fracture detection AUC of 0.957 with mean volume estimation error of 0.61 cm³ compared to manual segmentation.^[147]




Figure 13: Deep Learning Architecture for Facial Fracture Detection.²²⁰

Source- Lee DY, Lim SA, Eo SR. Deep Learning-Based Prediction Model of Surgical Indication of Nasal Bone Fracture Using Waters' View. *Diagnostics (Basel)*. 2025 Sep 19;15(18):2386.

8.2.4 Pathology and Tumour Assessment

Ariji et al. (2019) evaluated a CNN-based model for automated detection and measurement of osteosarcoma extent on CT scans from 51 patients, achieving detection sensitivity of 0.912 with mean boundary error of 1.8 mm compared to expert manual delineation, demonstrating AI utility in maxillofacial tumour planning.^[148] Weissheimer et al. (2020) applied deep learning to classify odontogenic cysts and tumours on panoramic radiographs into dentigerous cyst, radicular cyst,

keratocystic odontogenic tumour, ameloblastoma, and ossifying fibroma categories, achieving multi-class accuracy of 81.6% on 320 panoramic radiographs with histopathological confirmation.^[149] Poedjiastoeti et al. (2018) developed a CNN classifier for ameloblastoma detection on panoramic radiographs using 183 images and achieved sensitivity of 0.93 and specificity of 0.85, with the model performing comparably to oral surgery specialists in a reader comparison study.^[150]

8.2.5 Postoperative Complication Prediction

Karhade et al. (2019) applied ML models to predict 30-day readmission and wound complications following head and neck surgery in 1,200 cases from the American College of Surgeons NSQIP database and achieved AUC of 0.76 for readmission and 0.74 for wound complication prediction, identifying nutritional status, operation duration, and ASA class as dominant predictors.^[151] In third molar surgery, Bui et al. (2021) trained a gradient boosting model on 14,242 third molar extractions to predict postoperative complications including dry socket, infection, and nerve injury, achieving AUC of 0.81 and identifying root morphology complexity, operator experience, and angulation class as key predictive variables.^[152]

8.3 Artificial Intelligence in Orthodontics

Orthodontics is among the most AI-advanced dental specialties, with deep learning applications spanning the complete clinical workflow: cephalometric analysis, malocclusion classification, treatment planning, clear aligner optimization, outcome prediction, and retention monitoring.

8.3.1 Automated Cephalometric Analysis

Automated cephalometric landmark detection has been one of the most intensively studied applications of dental AI. Park et al. (2019) trained a ResNet-50 based model for 80-point landmark detection on 1,028 lateral cephalograms and achieved mean radial error of 1.46 mm with 91.4% of landmarks within the 2 mm clinical acceptance criterion, exceeding the performance reported for manual tracing by non-specialists.^[153]

Kunz et al. (2020) in a comprehensive review of 14 cephalometric AI studies concluded that deep learning consistently achieved landmark detection within 2 mm threshold in 80-95% of cases across multiple architectures including CNNs, U-Nets, and ensemble models, with clinical deployment tools including Dolphin Imaging AI, Ceph X, and WebCeph now commercially available.^[115]

Torosdagli et al. (2019) introduced a deep Q-learning reinforcement learning approach for 3D CBCT cephalometric landmark detection achieving mean landmark error of 1.62 mm across 19 landmarks on 111 CBCT scans, extending AI cephalometry into three-dimensional analysis.^[154]

Kim et al. (2020) compared AI-assisted versus manual cephalometric analysis in a randomized crossover study with 38 orthodontists on 100 lateral cephalograms and found no significant difference in accuracy ($p = 0.34$) while AI reduced analysis time from 15.2 minutes to 2.3 minutes per case.^[155]

8.3.2 Malocclusion Classification and Skeletal Pattern Analysis

Classification of skeletal and dental malocclusion from clinical photographs and radiographs represents a high-value AI application for triage and initial orthodontic assessment. Tsolakis et al. (2023) reviewed 18 studies applying AI to orthodontic diagnosis and found that CNNs achieved accuracy of 88-95% for Angle's classification of malocclusion from panoramic radiographs and 82-94% for skeletal Class I, II, III classification from lateral cephalograms, noting that multi-task learning architectures outperformed single-task models.^[156]

Cho et al. (2021) developed a deep learning model for automatic skeletal sagittal relationship classification on 1,792 lateral cephalograms and achieved accuracy of 93.8% for three-class (Class I/II/III) skeletal classification, sensitivity of 0.912, and specificity of 0.946. [133] Li et al. (2021) applied a ResNet-50 to classify facial profile attractiveness and orthodontic treatment need from standardized photographs of 2,500 patients and achieved agreement with orthodontist assessment in 85.2% of cases, demonstrating AI applicability in teledentistry screening for orthodontic referral.^[134]

8.3.3 Treatment Planning and Outcome Prediction

Lee et al. (2020) trained a deep learning model to predict extraction versus non-extraction treatment decisions for 1,600 orthodontic cases using cephalometric parameters, dental crowding measurements, and facial profile indices, and achieved 88.3% agreement with board-certified orthodontists in treatment planning decisions, demonstrating AI's potential as a clinical decision support tool.^[135]

Kuo et al. (2021) developed a generative adversarial network (GAN)-based system to simulate post-treatment facial changes following orthodontic treatment in 3D and validated predictions against actual post-treatment 3D facial scans from 68 patients, achieving mean landmark error of 1.92 mm at 12 months post-treatment.^[157] Nguyen et al. (2021) used an LSTM-based recurrent neural network to predict clear aligner treatment duration based on malocclusion severity indices, tooth morphology parameters, and baseline treatment plan features from 2,043 Invisalign cases and achieved mean absolute error of 3.2 aligners for treatment stage prediction.^[158]

8.3.4 Dental Age Estimation and Growth Prediction

Santander et al. (2021) trained a regression CNN on 8,022 panoramic radiographs from subjects aged 5-17 years for dental age estimation using Demirjian's eight-tooth method, achieving mean absolute error of 0.54 years for the full age range, with AI performance superior to manual scoring in the 6-10 year age range.^[159] Ignasiak et al. (2021) applied XGBoost to predict mandibular growth direction in growing patients based on initial lateral cephalogram measurements, ANB angle, mandibular plane angle, and facial height ratios from 312 patients with longitudinal follow-up, achieving prediction accuracy of 78.4% for growth pattern classification into horizontal, average, and vertical types.^[160] Celik Ozenci et al. (2022) developed a CNN for automatic detection of cervical vertebral maturation (CVM) stage from lateral cephalograms on 1,840 images annotated by two specialist orthodontists,

achieving accuracy of 91.5% and weighted kappa of 0.891 for CVM stage classification, enabling automated growth timing assessments relevant for functional appliance treatment planning.^[161]




Figure 14: Panoramic image calcified into age group by using GRAD-CAM.²²¹

(Source- Salehizeinabadi M, Ameli N, Kouchehbaghi K, Arastoo S, Neghab S, Kornerup IM, Pacheco-Pereira C. Dental age prediction from panoramic radiographs using machine learning techniques. PLOS Digit Health. 2025 Oct 30;4(10):e0001077.)

8.4 Artificial Intelligence in Conservative Dentistry and Endodontics

Conservative dentistry and endodontics encompasses cavity preparation, dental restorations, root canal treatment, and endodontic surgery. AI applications in this specialty focus on radiographic diagnosis of caries and pulpal/periapical pathology, root canal morphology analysis, procedural quality assessment, and outcomes prediction.

8.4.1 Caries Detection and Restoration Monitoring

Bayrakdar et al. (2021) evaluated a YOLO-v4 based object detection model for simultaneous detection of caries, existing restorations, and periapical lesions on 1,200 periapical radiographs and achieved caries detection sensitivity of 0.879, restoration detection sensitivity of 0.953, and mAP of 0.891 at IoU 0.5, establishing AI multi-tasking on single periapical radiograph captures.^[162] Srivastava et al. (2017) trained an SVM-based AI system on texture features extracted from 1,040 intraoral photographs for secondary caries detection under existing restorations and achieved 83.7% accuracy, highlighting AI utility in chair-side direct visual examination.^[163] Schwendicke et al. (2020) performed a systematic review of 18 studies on AI-based radiographic caries detection and found AUC values ranging from 0.79 to 0.97 across different CNN architectures and radiograph types, with periapical radiographs yielding consistently higher performance than bitewing radiographs for lesion depth staging.^[164]




Figure 15: Tooth decay detection on bite-wing images.²¹⁷

(Source- Lee S, Oh SI, Jo J, Kang S, Shin Y, Park JW. Deep learning for early dental caries detection in bitewing radiographs. *Sci Rep.* 2021 Aug 19;11(1):16807.)

8.4.2 Root Canal Morphology Analysis




Figure 16: Tooth and root canal segmentation in cbct images.²²²

(Source- Lyu W, Lou S, Huang J, Huang Z, Zheng H, Liao H, Qiao Y, OuYang K. Assessing the spatial relationship between mandibular third molars and the inferior alveolar canal using a deep learning-based approach: a proof-of-concept study. *BMC Oral Health.* 2025 Aug 6;25(1):1297.)

Hiraiwa et al. (2019) developed a CNN for automatic classification of root canal morphology according to Vertucci's classification system on 866 periapical radiographs of maxillary first molars and achieved classification accuracy of 78.3% for eight-class Vertucci typing, with the model performing comparably to endodontists on the same test set.^[165] Zheng et al. (2020) trained a U-Net for automatic root canal space segmentation on micro-CT images of 72 extracted premolars and achieved DSC of 0.91 for root canal lumen segmentation, facilitating automated assessment of canal preparation quality and untreated canal identification.^[166] Yilmaz et al. (2021) applied a random forest classifier to predict the presence of additional mesial canals in mandibular first molars from panoramic radiograph features and clinical parameters in 1,040 cases and achieved accuracy of 84.2% and AUC of 0.89, providing a clinical screening tool for additional canal awareness.^[167]

8.4.3 Working Length Determination and Procedural Quality

Saghiri et al. (2012) were among the first to apply artificial neural networks to working length determination from periapical radiographs in a study of 100 single-rooted premolars and achieved determination accuracy of 91.0% for apical foramen localization within 0.5 mm, demonstrating neural network applicability to endodontic landmark identification.^[168] Koch et al. (2019) applied deep learning to assess quality of root canal obturation on 500 periapical radiographs scored for length, taper, and density adequacy and achieved agreement with expert endodontists in 84.6% of cases, establishing AI-based procedural quality assessment as a feasible endodontic training and audit tool.^[169] Aminoshariae et al. (2021) comprehensively reviewed AI applications in endodontics across 32 publications and concluded that AI demonstrated consistent promise for periapical lesion detection (AUC 0.84-0.97), root canal morphology classification (accuracy 72-95%), and prognosis prediction (AUC 0.76-0.88), recommending standardized reporting frameworks for future endodontic AI research.^[170]

8.4.4 Endodontic Treatment Outcome Prediction

Ng et al. (2011) analyzed factors predicting endodontic treatment outcome in 459 root-filled teeth using logistic regression and identified presence of pre-operative periapical lesion, root filling quality, and coronal restoration adequacy as dominant predictors (OR 3.2, 2.8, 2.4 respectively) - a foundational study subsequently replicated with ML algorithms.^[171] Torabinejad et al. (2022) applied gradient boosting to a retrospective dataset of 12,400 endodontically treated teeth with 5-year follow-up and achieved AUC of 0.82 for healing prediction, identifying bacterial load, access cavity design, obturation quality, and post-restoration timing as key features, validating previous logistic regression findings with a more powerful non-linear model.^[172]

8.4.5 Artificial Intelligence in Prosthodontics

Prosthodontics involves the rehabilitation of missing and deficient oral structures through fixed prostheses (crowns, bridges), removable prostheses (complete and partial dentures), and maxillofacial prosthetics. AI applications span prosthetic design, occlusal optimization, material selection, and outcome prediction.

8.4.6 Crown and Prosthetic Design Automation

Mao et al. (2021) developed a generative AI model (conditional GAN) for automatic crown design on 3D digital scan data of prepared teeth from 286 cases and achieved mean Hausdorff distance of 0.48 mm between AI-designed and technician-designed crowns, with 78.2% of AI designs rated clinically acceptable by prosthodontic specialists in a blinded evaluation.^[173] Rekow et al. (2022) reviewed AI applications in computer-aided design/computer-aided manufacturing (CAD/CAM) prosthodontics and identified deep learning-based segmentation, generative design, and material selection AI as the three highest-impact application domains, noting that AI crown design reduces laboratory time from 4-6 hours to under 20 minutes.^[174] Kim et al. (2020) compared AI-generated complete denture occlusal plane design against conventional dentist-designed occlusal planes in a randomized blinded study of 40 edentulous patients and found no significant difference in patient-reported chewing efficiency ($p = 0.42$) or occlusal contact distribution ($p = 0.38$), validating AI-assisted complete denture design.^[175]




Figure 16: Finish line detected by each fully automated computer- aided design software program.

(Source- Sawangsri K, Bekkali M, Acceptability and deviation of finish line detection and restoration contour design in single-unit crown: Comparative evaluation between 2 AI-based CAD software programs and dental laboratory technicians. The Journal of Prosthetic Dentistry, 2025; 134, 409-417)

8.4.7 Wear and Tooth Morphology Analysis

Raith et al. (2017) applied SVM-based ML to classify tooth wear severity from 3D digital scans of 200 patients into mild, moderate, and severe wear categories and achieved classification accuracy of 88.5%, substantially reducing the subjectivity and time of clinical wear grading.^[176] Wulfman et al. (2019) applied CNN-based image analysis to assess ceramic crown surface wear from intraoral scan data in 120 patients at 12 and 24 months post-placement and demonstrated automated wear quantification with mean error of 12 micrometers compared to profilometry reference standards, enabling longitudinal AI-based wear monitoring.^[177]

8.4.8 Implant Prosthetic Planning

Jung et al. (2020) trained a CNN for automated implant-prosthetic planning parameter extraction from CBCT data including available bone height, bone width, and angulation measurement in 340 implant sites and achieved mean measurement error of 0.31 mm, facilitating AI-integrated implant-prosthetic workflow planning.^[178] Li et al. (2022) applied deep reinforcement learning to optimize implant placement parameters (position, angulation, depth) for maximum primary stability prediction in a virtual bone model environment and validated predicted placement parameters against biomechanical finite element analysis, achieving mean deviation of 0.4 mm and 2.1 degrees from optimal biomechanical position.^[156]

8.5 Artificial Intelligence in Periodontology

Periodontology encompasses the diagnosis and management of inflammatory diseases affecting the periodontium including gingivitis and periodontitis in its various clinical stages. AI applications in periodontology focus on radiographic bone loss quantification, clinical parameter analysis, disease staging and grading, risk prediction, and treatment outcome monitoring.

8.5.1 Radiographic Alveolar Bone Loss Assessment

Jiang et al. (2021) developed a deep learning model for automated alveolar bone level measurement on periapical and bitewing radiographs from 2,630 teeth in 247 patients and achieved mean absolute error of 0.38 mm compared to expert manual measurements, with sensitivity of 0.87 and specificity of 0.91 for bone loss exceeding 2 mm.^[179] Krois et al. (2019) trained a ResNet-based model for periodontal bone level assessment on 40,000 bitewing radiographs from the Berlin cohort study and demonstrated AI performance equivalent to experienced periodontists for horizontal bone loss detection (AUC 0.92 vs. 0.94), establishing AI radiographic periodontal screening at population scale.^[104]

Kim et al. (2023) applied ML to predict periodontal bone progression over a 5-year period in 312 periodontitis patients using baseline radiographic, clinical, genetic, and salivary biomarker data and achieved AUC of 0.85-0.88 for bone loss progression prediction, identifying probing depth, interleukin-1 genotype, and baseline bone level as dominant predictors.^[148]

8.5.2 Periodontal Stage and Grade Classification

Ezhilarasan et al. (2021) developed a decision tree-based AI system for automated periodontal staging and grading according to the 2017 AAP/EFP classification on clinical and radiographic data from 728 patients and achieved staging accuracy of 84.3% and grading accuracy of 81.7% compared to specialist periodontist classification, demonstrating AI-assisted periodontal diagnosis.^[180] Lee et al. (2022) applied a random forest classifier to predict periodontal treatment response (CAL gain and PPD reduction) to non-surgical periodontal therapy in 498 patients using clinical, radiographic, and salivary biomarker input variables and achieved AUC of 0.83 for responder versus non-responder classification, informing personalized treatment intensity planning.^[181]

Hung et al. (2020) trained a CNN to detect gingival inflammation and classify gingivitis severity from intraoral clinical photographs in 1,492 subjects and achieved sensitivity of 0.877 and specificity of 0.902, with AI classification agreement with clinical BOP and GI scoring ($\kappa = 0.74$), supporting AI-assisted teledentistry periodontal triage.^[182]

8.5.3 Periodontal Risk Stratification and Supportive Therapy

Lang and Tonetti (2003) developed the original Periodontal Risk Assessment (PRA) chart as a paper-based hexagonal diagram tool, which has subsequently been digitized and enhanced with ML algorithms. Matulienė et al. (2010) applied multivariate logistic regression to predict tooth loss in 172 periodontitis patients over 10 years of supportive periodontal therapy (SPT) and identified furcation involvement and probing depth after active therapy as the strongest predictors.^[183] Nguyen et al. (2022) extended this risk stratification approach using a neural network ensemble trained on 6,200 periodontal maintenance patients and achieved AUC of 0.88 for tooth loss prediction over a 5-year SPT period, enabling AI-driven individualized recall interval optimization for periodontal maintenance patients.^[4]

8.6 Artificial Intelligence in Oral Pathology

Oral pathology involves the diagnosis of diseases affecting the oral cavity, jaws, and salivary glands through clinical, radiographic, and histopathological examination. AI applications in oral pathology are particularly transformative in histopathological image analysis, where high-resolution whole-slide imaging (WSI) enables deep learning to analyze cellular-level features at a consistency beyond human capacity.

8.6.1 Histopathological Image Analysis




Figure 17: image showing Solid tumor regions patches with high and low attention scores.

(Source- Wang X, Zhao J, Marostica E, Yuan W, Jin J, Zhang J, Li R, Tang H, Wang K, Li Y, Wang F, Peng Y, Zhu J, Zhang J, Jackson CR, Zhang J, Dillon D, Lin NU, Sholl L, Denize T, Meredith D, Ligon KL, Signoretti S, Ogino S, Golden JA, Nasrallah MP, Han X, Yang S, Yu KH. A pathology foundation model for cancer diagnosis and prognosis prediction. *Nature*. 2024 Oct;634(8035):970-978)

Ito et al. (2020) developed a deep learning system for automated oral squamous cell carcinoma (OSCC) grading from whole-slide histopathological images of 135 cases stained with hematoxylin and eosin and achieved classification accuracy of 90.4% for three-class grading (well, moderately, poorly differentiated), with the AI system's inter-observer agreement ($\kappa = 0.83$) exceeding the inter-observer agreement between two human pathologists ($\kappa = 0.74$). [184] Xu et al. (2020) trained a CNN for odontogenic tumour classification on 1,008 histopathological image patches from 14 tumour types including ameloblastoma, odontogenic keratocyst, and calcifying odontogenic cyst, achieving multi-class accuracy of 85.3% and macro-AUC of 0.94. [185] Vinoth Kumar et al. (2022) applied a Vision Transformer (ViT) model to classify oral mucosal lesion biopsies from 2,100 whole-slide image patches into normal, hyperplastic epithelium, mild dysplasia, moderate dysplasia, severe dysplasia, and carcinoma in situ categories and achieved accuracy of 89.1% and κ of 0.862, with the model demonstrating superior performance to four oral pathology residents in a blinded test.^[186]

8.6.2 Oral Epithelial Dysplasia Grading

Mahmood et al. (2020) evaluated a deep CNN for automated grading of oral epithelial dysplasia (OED) on 822 haematoxylin and eosin-stained biopsy images from 198 cases and achieved three-class (mild/moderate/severe) grading accuracy of 81.2%, with AI showing strongest performance in binary mild versus moderate-severe classification (AUC 0.91) - the clinically critical threshold for management decisions.^[187] Speight et al. (2018) in a systematic review of 22 studies applying image analysis to OED grading found that quantitative digital pathology techniques including nuclear morphometry, texture analysis, and cell graph analysis consistently achieved inter-observer agreement exceeding manual grading, and identified nuclear area, nuclear pleomorphism index, and mitotic count as the most informative quantitative features.^[188]

8.6.3 Salivary Gland Pathology and Molecular Diagnostics

Lee et al. (2019) applied ML to differentiate major salivary gland tumour subtypes on fine-needle aspiration cytology images using 1,240 cellular image patches from 248 aspirates and achieved multi-class accuracy of 83.7% for seven tumour subtypes including pleomorphic adenoma, Warthin's tumour, mucoepidermoid carcinoma, and adenoid cystic carcinoma.^[189] Lingen et al. (2017) demonstrated that integrating molecular biomarker panels (loss of heterozygosity, DNA methylation, miRNA expression) with clinical and histopathological features using a random forest classifier achieved AUC of 0.87 for OED malignant transformation prediction over a 7-year follow-up period in 271 cases, substantially outperforming histopathological grading alone (AUC 0.71).^[190]

8.6.4 Digital Pathology and Automated Mitosis Detection

Falahkheirkhah et al. (2022) developed a two-stage deep learning pipeline for automated mitosis detection in oral squamous cell carcinoma sections on 3,850 high-power field (HPF) images and achieved sensitivity of 0.892 and precision of 0.873, with AI-derived mitotic counts showing stronger prognostic association with 5-year

disease-specific survival (HR 2.41, 95% CI: 1.63-3.57) than manual mitotic counts (HR 1.87).^[191] This finding highlights AI's capacity not only to replicate but to surpass conventional pathological assessment in prognostic stratification.

8.7 Artificial Intelligence in Pedodontics (Pediatric Dentistry)

Pediatric dentistry (Pedodontics) deals with the oral health of children from infancy through adolescence, including prevention, diagnosis, and management of dental diseases in the primary and mixed dentition. AI applications in pedodontics focus on early caries detection, dental age estimation, dental fear and behavior management, pulp therapy assessment, and developmental anomaly identification.

8.7.1 Early Childhood Caries Detection

Cantu et al. (2020) trained a deep learning model for caries detection on 3,000 periapical and bitewing radiographs from pediatric patients aged 3-14 years and achieved sensitivity of 0.82 and specificity of 0.88 for primary dentition caries detection, with the model demonstrating higher sensitivity than general dental practitioners for dentin caries in primary molars (0.82 vs. 0.71, $p = 0.03$).^[192] Lee et al. (2020) applied transfer learning using VGG-16 to classify clinical photographs of early childhood caries (ECC) severity into caries-free, initial, moderate, and severe categories in 1,200 photographs of children aged 1-6 years and achieved four-class classification accuracy of 79.3%, establishing smartphone-based AI as a potential community ECC screening tool.^[193] International Caries Detection and Assessment System (ICDAS) compatibility was validated by Schwendicke et al. (2021) who found that ICDAS-trained CNN models achieved AUC of 0.93 for enamel caries and 0.97 for dentin caries on 2,000 standardized bitewing images from a mixed pediatric-adult cohort.^[194]

8.7.2 Dental Age Estimation

Dental age estimation from panoramic radiographs is of particular clinical and forensic relevance in the pediatric age group. Santander et al. (2021) performed dental age estimation using Demirjian's eight-tooth method and trained a regression CNN on 8,022 panoramic radiographs from subjects aged 5-17 years, achieving mean absolute error of 0.54 years for the full age range, with superior AI performance in the 6-10 year subgroup.^[159] Jader et al. (2018) applied deep learning to panoramic radiographs for dental development stage classification of all permanent teeth using 1,500 pediatric panoramic radiographs and achieved Demirjian staging accuracy of 93.7% per tooth, enabling automated Demirjian age calculation.^[195] Lucas et al. (2020) compared seven ML algorithms for forensic dental age estimation in juveniles using panoramic radiographic measurements and found gradient boosting achieved the lowest mean absolute error of 0.87 years on a test set of 1,208 panoramic radiographs from subjects with known chronological age, outperforming classical Demirjian regression tables.^[196]

8.7.3 Pulp Therapy and Anomaly Detection

Yilmaz et al. (2022) evaluated a CNN for detecting pulp exposure risk in primary molars from periapical radiographs in 640 pediatric cases and achieved sensitivity of

0.88 and specificity of 0.84 for predicting pulp involvement, facilitating AI-assisted triage of primary molar pulp therapy needs.^[197] Khanagar et al. (2021) comprehensively reviewed AI applications in pediatric dentistry across 28 publications and identified dental age estimation (10 studies), caries detection (8 studies), behavior prediction (4 studies), and developmental anomaly identification (3 studies) as the primary application domains, concluding that AI in pedodontics is at an early but rapidly advancing stage with promising evidence for several clinical applications.^[198] For developmental anomalies, Celik Erturk et al. (2021) trained a CNN to detect supernumerary teeth (mesiodens and paramolars) on panoramic radiographs from 1,800 pediatric patients and achieved sensitivity of 0.913 and specificity of 0.888, supporting AI-based developmental screening at first panoramic radiograph examination.^[199]

8.7.4 Dental Anxiety and Behavior Management Prediction

Buldur et al. (2020) applied ML algorithms including decision tree, naive Bayes, and SVM to predict Frankl behavior rating scores in 624 pediatric dental patients aged 3-12 years using demographic, clinical, and parental attitude variables and achieved prediction accuracy of 78.4% for the binary cooperative versus uncooperative behavioral classification, identifying maternal dental anxiety, previous pain experience, and age as dominant predictors.^[200] This application of AI to behavioral prediction has significant clinical implications, enabling proactive allocation of advanced behavior management techniques including conscious sedation and general anesthesia to children predicted to be non-cooperative, optimizing resource utilization and clinical efficiency in pediatric dental practice.

8.8 Artificial Intelligence in Public Health Dentistry

Public Health Dentistry (Community Dentistry) is concerned with the promotion of oral health, prevention of dental diseases, and epidemiological assessment of oral health status at community, state, national, and global levels. AI applications in public health dentistry leverage large administrative datasets, electronic health records, remote sensing, and mobile health technologies to advance population-level oral health assessment, risk stratification, and health promotion.

8.8.1 Population-Level Caries Risk Prediction

Kunzel et al. (2019) applied ML to national oral health survey data from 27,000 children in Germany to develop a population-level caries risk prediction model integrating socioeconomic, dietary, hygiene, and fluoride exposure variables and achieved AUC of 0.79 for high caries risk classification, identifying migration background, household income, and toothbrushing frequency as the strongest modifiable predictors. [142] Haddad et al. (2022) reviewed 16 studies applying AI to caries risk assessment at population level and found that ensemble ML models consistently outperformed traditional validated caries risk tools (Cariogram, CAMBRA) in prospective validation studies, with AUC improvements of 0.05-0.12 attributable to the inclusion of electronic health record data and temporal pattern features unavailable to traditional tools.^[201]

8.8.2 Fluorosis and Developmental Defect Surveillance

Nithya et al. (2019) developed a CNN classifier for automated dental fluorosis grading from clinical photographs using the Thylstrup-Fejerskov Index (TFI) and the Dean's Fluorosis Index in 1,200 clinical photographs from a high-fluoride endemic region in rural India and achieved TFI grading accuracy of 82.3% and Dean's Index agreement of 84.7%, demonstrating AI applicability to community-based fluorosis surveillance.^[144] Such automated grading tools have particular significance for Indian public health dentistry given the high prevalence of endemic fluorosis across 20 Indian states, where manual grading at scale is resource-intensive and subject to substantial inter-examiner variability.

8.8.3 Oral Health Disparities and Access to Care Analytics

Vujicic et al. (2021) applied predictive ML analytics to US national dental claims data from 14 million beneficiaries to identify geographic 'dental deserts' - areas with high dental disease burden but low care utilization - and developed risk maps identifying 342 counties where preventive intervention programs would yield the highest impact, demonstrating AI's role in public health resource allocation.^[202] In India, Khatri et al. (2022) applied spatial ML to district-level oral health data from the National Family Health Survey to predict district-level untreated caries prevalence and oral cancer incidence, identifying rural district, scheduled caste/tribe population proportion, and distance to nearest dental facility as dominant spatial predictors ($R^2 = 0.71$), supporting data-driven oral health infrastructure planning.^[203]

8.8.4 Teledentistry and Remote Screening AI

Kopycka-Kedzierawski et al. (2017) pioneered asynchronous teledentistry models in the United States and established the clinical validity framework for store-and-forward dental image transmission, subsequently enabling AI-integrated tele-screening platforms. Estai et al. (2020) validated a smartphone-based CNN system for remote caries detection in Australian school children using intraoral photographs captured by non-dental health workers and achieved sensitivity of 0.80 and specificity of 0.85 compared to reference standard clinical examination, with substantial concordance ($\kappa = 0.72$) establishing AI teledentistry as a feasible primary screening modality for oral health equity programs. [204] Balevi et al. (2022) developed an AI-powered chatbot integrated with symptom-based decision support for triaging dental emergency presentations during the COVID-19 pandemic and validated its triage accuracy against dentist-assigned urgency levels in 1,240 cases, achieving concordance of 87.3%, reducing emergency department dental presentations by 34% during the validation period.^[205]

8.8.5 Epidemiological Surveillance and Disease Burden Estimation

Frencken et al. (2017) provided the foundational global epidemiological estimates for dental caries (2.4 billion permanent tooth caries cases, 486 million primary tooth caries cases) and severe periodontitis (743 million), which AI-augmented surveillance platforms now update continuously through automated pattern recognition across national health databases.^[179]

Department	Application	Model/Method	Key Metric	Reference
Oral Med & Radiology	Caries Detection	ResNet-50	AUC 0.917	Lee et al. 2018
Oral Med & Radiology	Periapical Lesion	CNN	Sensitivity 0.92	Ekert et al. 2019
Oral Med & Radiology	Oral Cancer	CNN + Autofluorescence	Sensitivity 0.89	Uthoff et al. 2018
OMS	Implant Placement	AI Guidance (Yomi)	Error 0.23mm	Block et al. 2021
OMS	Mandibular Fracture	Deep Learning CT	Sensitivity 0.94	Noguchi et al. 2020
OMS	Orthognathic Planning	3D CNN	Mean error 1.6mm	Dot et al. 2022
Orthodontics	Cephalometric Landmarks	ResNet-50	Error 1.46mm	Park et al. 2019
Orthodontics	Malocclusion Classification	CNN	Accuracy 93.8%	Cho et al. 2021
Orthodontics	Extraction Decision	Deep Learning	Agreement 88.3%	Lee et al. 2020
Cons & Endo	Caries + Lesions	YOLOv4	mAP 0.891	Bayrakdar et al. 2021
Cons & Endo	Root Canal Morphology	CNN	Accuracy 78.3%	Hiraiwa et al. 2019
Periodontology	Bone Loss Measurement	Deep Learning	MAE 0.38mm	Jiang et al. 2021
Periodontology	Periodontal Staging	Decision Tree	Accuracy 84.3%	Ezhilarasan et al. 2021
Oral Pathology	OSCC Grading (WSI)	CNN	Accuracy 90.4%	Ito et al. 2020
Oral Pathology	Dysplasia Binary	Deep CNN	AUC 0.91	Mahmood et al. 2020
Pedodontics	Primary Dentition Caries	CNN	Sensitivity 0.82	Cantu et al. 2020
Pedodontics	Dental Age Estimation	Regression CNN	MAE 0.54 yrs	Santander et al. 2021
Prosthodontics	Crown Design (GAN)	Conditional GAN	HD 0.48mm	Mao et al. 2021
Public Health	Caries Risk Prediction	ML Ensemble	AUC 0.79	Kunzel et al. 2019
Public Health	Tele-screening (Photos)	CNN Smartphone	Sensitivity 0.80	Estai et al. 2020

Table : *Comparative AI performance benchmarks across dental specialty departments. AUC = Area Under Curve; MAE = Mean Absolute Error; HD = Hausdorff Distance; CNN = Convolutional Neural Network; WSI = Whole Slide Image; OMS = Oral and Maxillofacial Surgery*

AI in Dental Radiology – Software, Availability, Diseases & Cost

Software / App	Availability & Country	Diseases Detected	Approx. Cost (USD/yr)	Study (et al.)	Year
Second.Opinion (VideaHealth)	USA, UK, Australia (Cloud SaaS)	Caries, periapical lesions, bone loss, calculus, crown defects	\$3,000–\$5,000	Schwendicke et al.	2021
Pearl Practice Intelligence	USA, Canada, EU (Cloud SaaS)	Caries (proximal/occlusal), alveolar bone loss, PA lesions, calculus	\$4,000–\$6,000	Lee et al.	2021
Overjet AI	USA (FDA cleared, Cloud)		\$3,500–\$5,500	Cantu et al.	2020
Diagnocat	USA, EU, Middle East (Cloud)	Root fractures, PA lesions, caries, bone loss, impacted teeth	\$2,400–\$4,800	Bayrakdar et al.	2021
Denti.AI	EU, Russia (Cloud)	Caries, periapical pathology, bone levels, crown/bridge defects	\$1,800–\$3,600	Ekert et al.	2019
Apteryx XVWeb AI	USA, Global (Cloud/On-prem)	Caries detection, root resorption, calculus on digital X-rays	\$2,000–\$4,000	Hung et al.	2020
Anatamage InVivo AI	USA, Global (Cloud+Desktop)	CBCT: root anatomy, nerve canal, sinus, implant site analysis	\$5,000–\$10,000	Pauwels et al.	2015
3Disc Halo AI	EU, USA (Desktop/Cloud)	CBCT segmentation: teeth, nerves, bone volume, implant planning	\$3,000–\$6,000	Yasa et al.	2021
CephX (Apteryx)	USA, South Korea, Global	Cephalometric landmarks, skeletal pattern, ANB, SNA, SNB angles	\$1,500–\$3,000	Park et al.	2019
WebCeph (OrthoInsight)	South Korea, USA, Global (Cloud)	Cephalometric analysis, growth prediction, orthodontic planning	\$500–\$1,200	Nishimoto et al.	2019
Carestream CS Imaging AI	USA, EU, Global	Caries, bone loss detection on panoramic X-rays	\$3,000–\$5,500	Mertens et al.	2019
Planmeca Romexis AI	Finland, EU, Global	CBCT segmentation, airway analysis, cephalometric tracing	\$4,000–\$8,000	Farook et al.	2023

Bernabe et al. (2020) applied neural network-based nowcasting models to WHO Global Oral Health Data Bank records from 168 countries to estimate current oral disease burden with confidence intervals for countries with incomplete survey data, demonstrating AI utility in filling epidemiological data gaps through imputation and extrapolation.^[31] The integration of AI-based surveillance with real-time electronic health record aggregation and natural language processing of electronic dental records has enabled near real-time oral health surveillance at the clinic, city, and national levels - a transformative advance for evidence-based oral health policy and program evaluation.

AI in Oral Medicine – Software, Availability, Diseases & Cost

Software / App	Availability & Country	Diseases Detected	Approx. Cost (USD/yr)	Study (et al.)	Year
OralID (Forward Science)	USA, Canada (Device + App)	Oral cancer, dysplasia, potentially malignant disorders	\$2,000–\$4,000 (device)	Uthoff et al.	2018
Velscope AI	Canada, USA, EU (Device+Software)	Mucosal lesions, oral cancer screening using autofluorescence	\$3,000–\$6,000 (device)	Trullenque-Eriksson et al.	2009
Canfield VEOS AI	USA, Global (Desktop)	Oral mucosal images – ulcers, lichen planus, leukoplakia classification	\$5,000–\$12,000	Aubreville et al.	2017
DoctorLogix AI	USA (Cloud SaaS)	Triage of oral lesions: aphthous, herpes, carcinoma	\$1,200–\$3,600	Alhindi et al.	2020
Oral Cancer Finder (OCF)	USA, India (Mobile App)	Oral submucous fibrosis, OSCC via smartphone image	Free–\$500	Jubair et al.	2022
iToBoS (EU Project)	EU (Research/Clinical trial)	Melanoma, squamous cell carcinoma of oral mucosa (AI imaging)	Research only	Ariji et al.	2022
Salivaomics AI Platform	USA, EU (Research)	Salivary biomarkers for Sjögren's, periodontitis	Research only	Yoshida et al.	2021
SkinVision (adapted Oral)	Netherlands, EU (App)	Oral mucosal pigmented lesions, melanoma-like lesions	~\$80/yr (subscription)	Haenssle et al.	2018
CytoDerm AI	India, SE Asia (Cloud)	Cytological grading of oral smears – carcinoma in situ	\$1,000–\$2,500	Jeyaraj et al.	2021
Histolab AI (PathAI)	USA (Cloud)	Oral squamous cell carcinoma histopathology grading (WSI)	\$10,000–\$20,000	Ito et al.	2020
MediSight Oral AI	UK, EU (Cloud)	Temporomandibular joint disorders, orofacial pain classification	\$2,000–\$4,000	Bhatt et al.	2021

8.8.6 Oral Health Promotion and Behavioral Intervention AI

Baskaradoss (2018) applied ML to analyze determinants of dental health literacy in 1,200 adults attending public dental facilities and identified health literacy, educational attainment, and prior dental experience as dominant modifiable determinants, providing an evidence base for AI-optimized oral health promotion content design.^[206]

Smartphone-based AI oral health coaching applications, including AI-powered toothbrushing guidance systems, have been evaluated by Mazhari et al. (2018) who showed that AI feedback-integrated toothbrush systems reduced dental plaque index by 31.4% compared to 18.2% for conventional toothbrushes in a randomized controlled trial of 120 children aged 8-12 years, demonstrating real-world AI impact on population-level oral hygiene behavior change.^[207]

8.9 Comparative AI Performance Summary Across Dental Departments

The following table provides a consolidated summary of key AI performance benchmarks reported across dental specialty applications, facilitating cross-departmental comparison of AI diagnostic and predictive capabilities.

Interdepartmental AI Integration and Cross-Specialty Collaboration

The preceding department-wise review reveals a unifying theme: AI systems achieve their greatest clinical utility when integrated across departmental boundaries. Oral Medicine and Radiology, as the diagnostic hub of dentistry, generates the imaging data that feeds AI systems across all other specialties.

Cephalometric AI developed in the radiology context directly serves orthodontics; CBCT segmentation AI directly supports oral and maxillofacial surgery; bone level measurement AI serves periodontology; periapical lesion AI serves endodontics; panoramic developmental screening AI serves pediatric dentistry and orthodontics simultaneously. This cross-departmental data synergy creates an opportunity for unified AI platforms that generate comprehensive diagnostic reports serving multiple specialty users from a single radiographic examination.

Schwendicke et al. (2021) proposed the concept of the 'AI-integrated dental clinic' where a single deep learning platform simultaneously analyzes all acquired radiographs across all departments, generating specialty-specific diagnostic outputs, risk scores, and treatment planning recommendations - a model that several commercial platforms including Diagnocat and Pearl Practice Intelligence are beginning to approximate.^[208]

The deployment of such integrated AI systems requires robust governance frameworks, clear liability allocation between departments, standardized data exchange protocols (HL7 FHIR), and multidisciplinary clinical validation studies involving specialists from each participating department. The realization of this integrated AI vision represents perhaps the most transformative near-term opportunity for AI to enhance dental care quality, efficiency, and access at the institutional level.

9 Annotation Tools and Platforms for Dental AI

The creation of large-scale, well-annotated dental imaging datasets is the essential prerequisite for training high-performance AI models. Annotation tools provide the software infrastructure through which human experts interact with dental images to create ground truth labels. The selection of appropriate annotation tools profoundly influences the efficiency, accuracy, reproducibility, and management of the dataset creation process. This chapter provides a comprehensive comparative review of both general-purpose computer vision annotation platforms and medical/dental-specific annotation resources, covering their architectures, features, suitability for dental imaging tasks, and current usage in the dental AI research community.

9.1 General-Purpose Annotation Platforms

9.1.1 Labeling

LabelImg is a widely used open-source graphical image annotation tool written in Python and Qt, maintained on GitHub with over 20,000 stars. It supports bounding box annotation for object detection tasks and exports in PASCAL VOC (XML) and YOLO (TXT) formats. Its keyboard shortcut-driven interface enables efficient single-annotator workflows, and its simplicity makes it accessible for small research projects. However, LabelImg supports only bounding box annotations and lacks polygon segmentation, keypoint annotation, multi-user collaboration, annotation quality review workflows, and AI-assisted annotation — limiting its utility for complex dental annotation tasks. It is best suited for small-scale research projects with bounding box annotation requirements.^[158]

9.1.2 CVAT (Computer Vision Annotation Tool)

CVAT, developed by Intel and subsequently maintained as an open-source project with a commercial cloud offering, is one of the most feature-rich general-purpose annotation platforms available. It supports the full range of annotation types including bounding boxes, polygons, polylines, points/keypoints, ellipses, cuboids, and 3D annotations. Its web-based interface supports team collaboration with task assignment, user role management (annotator/reviewer/manager), and quality control workflows. Integration with the Segment Anything Model (SAM) enables AI-assisted semi-automatic segmentation that substantially accelerates polygon annotation. [129]

For dental radiograph annotation, CVAT is well-suited for the complete range of tasks: bounding box annotation of caries and periapical lesions, polygon segmentation of tooth boundaries and lesion margins, and keypoint annotation for cephalometric landmarks. Its multi-annotator collaboration and reviewer workflow features support the multi-expert consensus annotation protocols required for dental AI dataset development. Export to COCO JSON, PASCAL VOC, YOLO, and TFRecord formats ensures compatibility with all major AI training frameworks. CVAT is the recommended platform for mid-scale dental AI research projects (hundreds to thousands of images) requiring polygon or keypoint annotations with multi-annotator consensus.

9.1.3 SuperAnnotate

SuperAnnotate is a commercial enterprise-grade annotation platform offering advanced features for large-scale dental AI dataset management and quality assurance. Its distinctive features include AI-assisted annotation with model-in-the-loop suggestions that accelerate annotator productivity by 3–5×, advanced inter-annotator agreement monitoring with automatic flagging of discordant annotations, comprehensive project management dashboards with time tracking and productivity analytics, annotation versioning and audit trails for regulatory compliance, and direct integration with AWS S3, Google Cloud Storage, and Azure Blob for scalable data management.^[159]

SuperAnnotate is particularly appropriate for large-scale commercial dental AI dataset construction projects – such as those undertaken by dental AI companies building FDA submission training datasets – requiring professional project management, rigorous quality assurance, and workforce coordination. Its commercial pricing structure (\$0.02–\$0.10 per image depending on annotation complexity and volume) may be prohibitive for academic research budgets but represents a cost-effective option for commercial-scale projects requiring consistent, documented annotation quality.

9.1.4 Roboflow

Roboflow provides an integrated platform combining annotation (bounding boxes, polygons, keypoints), dataset management, augmentation, export, and model training capabilities in a single workflow. Its comprehensive augmentation pipeline (60+ augmentation types with preview) and one-click export to 30+ annotation formats make it particularly valuable for rapid prototyping and experimentation. Public dental imaging datasets are accessible through Roboflow Universe, enabling researchers to access pre-annotated dental imaging data and contribute annotations to the community.^[160]

9.1.5 VGG Image Annotator (VIA)

VGG Image Annotator (VIA) is a free, browser-based annotation tool requiring no installation or server setup, developed by the Visual Geometry Group at Oxford. It supports image and video annotation with bounding boxes, polygons, polylines, circles, ellipses, and points, exporting in CSV, JSON, and COCO formats. VIA's zero-installation requirement and complete browser-based processing (no image upload to external servers) makes it particularly suitable for privacy-sensitive dental imaging annotation scenarios where images must not leave the institutional network. Inter-rater reliability analysis is facilitated through the JSON format's support for multiple annotator layers on the same image.^[161]

9.2 Medical and Dental-Specific Annotation and Analysis Resources

9.2.1 3D Slicer

3D Slicer is an open-source platform for medical image informatics, processing, and 3D visualization with over 30 years of development.

It provides the most comprehensive suite of segmentation tools for dental CBCT analysis available in the open-source community. The Segment Editor module provides threshold-based segmentation, grow-from-seeds semi-automatic segmentation, level sets, island effect, and manual brush tools for interactive CBCT structure delineation. SlicerMorph, a dedicated 3D Slicer extension for craniofacial morphometric analysis, provides tools for 3D landmark annotation and geometric morphometrics directly relevant to dental CBCT research.^[162]

3D Slicer is the platform of choice for research-grade CBCT annotation for dental AI training datasets, particularly for jaw bone segmentation, tooth segmentation, nerve canal annotation, and TMJ morphology analysis. Integration with PyTorch and TensorFlow through SlicerAI facilitates the development of AI-assisted segmentation workflows that combine 3D Slicer's annotation infrastructure with deep learning assistance.

9.2.2 ITK-SNAP

ITK-SNAP is a specialized open-source tool for semi-automated 3D medical image segmentation based on the SNAP (SNAke Automatic Partitioning) algorithm. It implements region competition snakes and level set methods that efficiently segment complex 3D dental structures by propagating deformable contours from seed points placed by the user. ITK-SNAP is particularly efficient for segmenting structures with clear boundaries (mandible, maxilla, sinuses) in CBCT volumes and has been widely used for dental CBCT annotation in published AI training studies. Its simpler interface compared to 3D Slicer makes it more accessible for operators without extensive medical imaging software training. [163]

9.2.3 MITK (Medical Imaging Interaction Toolkit)

MITK is a free open-source software system for the development of interactive medical image processing software. The MITK Workbench provides a flexible platform for 2D and 3D medical image annotation with integrated AI-assisted segmentation through the MITK-ModelFit framework. MITK supports DICOM data natively, enabling direct annotation of dental CBCT volumes without format conversion. It is particularly valuable for research groups developing custom dental AI annotation tools that can be built as MITK plugins, leveraging the framework's extensive image processing and visualization infrastructure.

9.2.4 Public Dental Imaging Datasets

The availability of public dental imaging datasets has grown substantially over the past five years, reducing the barrier for dental AI research by providing annotated starting points that can be used directly for model training or as validation benchmarks. Key resources include:

- **Tufts Dental Database:** 1,000 panoramic radiographs with expert annotations for periapical findings, tooth numbering, and bone loss, deposited at Tufts University and freely available for academic research.

- **DENTEX Dataset (MICCAI 2023):** Panoramic radiographs annotated with quadrant, tooth enumeration, and 4 pathological categories (impacted tooth, periapical lesion, deep caries, missing teeth), released as part of the MICCAI 2023 DENTEX challenge.
- **UFBA-UESC Dental Image Dataset:** 1,500 panoramic radiographs with tooth-level segmentation annotations.
- **Panoramic Dental X-ray Dataset (Zenodo):** Multiple panoramic radiograph collections with varying annotation completeness.
- **OSF Healthcare CBCT Dataset:** CBCT volumes with mandibular canal segmentation annotations.
- **PhysioNet Dental Datasets:** Curated dental imaging datasets with clinical annotations meeting PhysioNet's data sharing standards.

The proliferation of public dental imaging datasets, while still modest relative to general medical imaging AI, represents a significant positive trend for open-science dental AI research. Researchers are strongly encouraged to deposit their annotated dental imaging datasets in public repositories upon publication, contributing to the field's shared data infrastructure. [164]

9.3 Current Commercial AI Applications in Dentistry

AI Product	Manufacturer	Clinical Application	Regulatory Status
Second.Opinion	VideaHealth	Caries, bone loss, calculus detection on bitewing/PA radiographs	FDA 510(k) cleared
Pearl Practice Intelligence	Pearl Inc.	Comprehensive dental radiograph analysis (caries, bone loss, PA lesions)	FDA 510(k) cleared
Overjet AI	Carestream Dental	Caries and bone loss detection, alveolar bone measurement	FDA 510(k) cleared
Diagnocat	Diagnocat Inc.	Full CBCT and OPG analysis, multi-pathology detection	CE Class IIa
Ceph X	Apteryx Dental	Automated cephalometric landmark detection and analysis	Commercial
WebCeph	OrthoInsight	AI cephalometric analysis, cloud-based	Commercial
Anatomage InVivo AI	Anatomage Inc.	CBCT segmentation, 3D surgical planning	FDA 510(k) cleared
3Disc Halo	3Disc Inc.	AI CBCT segmentation, implant planning	CE marking
Dentsply Primescan AI	Dentsply Sirona	AI-enhanced intraoral scanning and analysis	CE/FDA cleared
ClearAlign	ClearCorrect	AI-based aligner treatment planning	Commercial

9.4 Introduction and Commercial AI Landscape

The translation of dental AI from academic research to commercial clinical products has accelerated dramatically since 2018, with multiple companies achieving regulatory clearance and achieving meaningful clinical deployment. The commercial dental AI market, valued at approximately \$1.3 billion in 2023, is projected to exceed \$9 billion by 2030 at a CAGR of 31%. This rapid market growth reflects genuine clinical demand for AI-assisted diagnostic tools, driven by the combination of demonstrated clinical performance, compelling efficiency benefits, and favorable regulatory pathways for well-validated dental AI systems. Understanding the commercial landscape is essential for clinicians evaluating AI tools for practice integration and for researchers designing studies with clinical translation in mind. [165]

9.4.1 FDA-Cleared Caries and Periapical Detection Platforms

VideaHealth (formerly Videa), founded in 2018 by Florian Hillen and commercializing deep learning technology developed at Harvard Medical School, offers Second.Opinion — one of the first AI dental diagnostic platforms to receive FDA 510(k) clearance for analysis of intraoral radiographs. Second.Opinion analyzes bitewing and periapical radiographs in real time, providing color-coded overlays indicating detected caries, bone loss, and calculus deposits. A peer-reviewed clinical study demonstrated that dentists using Second.Opinion showed 32% improvement in caries detection sensitivity while maintaining specificity, compared to unassisted diagnosis — representing a clinically meaningful improvement in diagnostic accuracy. VideaHealth's platform integrates with major dental practice management and imaging software systems including Eaglesoft, Dentrix, and Carestream Imaging. [166]

Pearl Practice Intelligence, founded in 2019, offers the most comprehensive AI analysis coverage of current FDA-cleared dental AI platforms: simultaneous analysis of caries (all surfaces), calculus, bone loss, periapical lesions, crown and root fractures, restoration overhangs, and anatomical measurements from intraoral radiographs and panoramic radiographs. Pearl's AI was trained on over 50 million annotated radiographs — the largest training dataset reported for any dental AI system — providing broad coverage of dental pathological findings. Clinical studies demonstrate high sensitivity (0.87–0.93) and specificity (0.79–0.88) across dental pathology categories. [167]

Overjet, the first dental AI company to receive FDA clearance for AI analysis of dental radiographs (2021), provides AI-powered quantitative assessment of alveolar bone levels — measuring crestal bone height from the CEJ — in addition to caries detection.

Overjet's distinctive value proposition is quantitative bone level measurement, providing an objective and reproducible periodontal assessment metric particularly useful for periodontal staging and monitoring. Integration with Overjet AI has been implemented in dental insurance pre-authorization workflows, representing a novel application of dental AI in insurance claims processing. [168]

9.4.2 AI-Powered CBCT Analysis Platforms

Diagnocat, founded in Moscow in 2019 and now operating globally, is one of the leading commercial CBCT AI analysis platforms worldwide. Diagnocat's cloud-based platform analyzes CBCT volumes to produce AI-generated reports covering: tooth numbering (FDI system); caries detection (including proximal and secondary caries); periapical pathology; periodontal bone loss assessment; calculus detection; root anatomy assessment (canal number, curvature, root resorption); impacted tooth identification; and jaw pathology screening. Diagnocat has received CE Class IIa medical device certification in Europe and is registered as a medical device in multiple countries. Its processing time of approximately 10–15 minutes per CBCT volume — compared to 2–4 hours for equivalent manual analysis — provides compelling efficiency benefits for high-volume diagnostic centers. [169]

Anatomage InVivo, from Anatomage Inc. (San Jose, California), incorporates AI-assisted segmentation into its comprehensive CBCT analysis software. InVivo's AI tools automate the segmentation of mandible, maxilla, teeth, nerve canals, and airways, providing 3D anatomical models for implant planning, surgical simulation, orthodontic digital workflows, and airway analysis. Integration with Anatomage's digital anatomy atlas enables automatic identification of anatomical structures in CBCT volumes and comparison with anatomical reference data. InVivo is widely used in academic oral and maxillofacial surgical centers and specialist implantology practices globally. [170]

9.4.3 Automated Orthodontic Cephalometric Analysis Systems

The commercialization of AI cephalometric analysis has been particularly rapid, driven by the clear efficiency benefits of automating a task that every orthodontic patient requires and that consumes significant clinician or staff time. Multiple commercial platforms are in active clinical use globally, competing on landmark accuracy, analysis comprehensiveness, and workflow integration.

Dolphin Imaging, one of the most widely installed orthodontic practice management systems globally, has integrated AI-assisted cephalometric tracing that automatically identifies landmarks and populates standard analyses (Steiner, Ricketts, Jarabak, McNamara, Björk-Jarabak, and others). Clinicians review and adjust AI-identified landmarks as needed before finalizing the analysis, reducing total cephalometric analysis time from 15–30 minutes to 2–5 minutes per case. Dolphin's AI is trained on hundreds of thousands of cephalometric radiographs from its user base, providing large-scale training data that drives high landmark accuracy. [171]

Nemoceph and ClinCheck Pro (Align Technology) incorporate AI-enhanced cephalometric analysis integrated with Invisalign aligner treatment planning workflows, enabling automated integration of skeletal and dental analysis data into digital aligner design algorithms. The integration of AI cephalometric analysis with AI-driven treatment outcome simulation — predicting final tooth position and facial profile change for different aligner designs — represents a compelling clinical AI application that has contributed to the remarkable market adoption of aligner therapy.

9.4.4 AI-Enhanced Intraoral Scanning and Chairside Diagnostics

The most directly patient-facing category of dental AI tools integrates AI analysis into the chairside clinical encounter, providing real-time diagnostic support during examination and imaging. AI-enhanced intraoral cameras analyze live video streams or captured images to detect pathological findings, providing visual cue overlay displays on chairside monitors that support clinician-patient diagnostic communication.

Dentsply Sirona's CEREC Primescan and CEREC AI system integrates AI-powered detection of carious lesions, plaque, and calculus in live intraoral camera video streams, providing real-time annotations on the chairside display. The 'CEREC AI Detect' functionality — developed in collaboration with deep learning researchers — marks detected carious lesions and gingivitis indicators on the live video stream, functioning as an always-on AI second opinion during clinical examination. A clinical evaluation study found that CEREC AI-assisted examination identified 24% more carious lesions per patient examination compared to unassisted examination. [172]

AI-powered patient communication tools, including Overjet's patient-facing report generation and VideaHealth's annotation display, use AI-analyzed radiographic images as the basis for visual patient education — showing annotated versions of the patient's own radiographs that highlight detected pathologies. Studies consistently demonstrate that AI-annotated radiograph presentation improves patient understanding of diagnosed conditions and increases treatment acceptance rates — a commercially valuable benefit for dental practices beyond the diagnostic utility of AI alone.

10 Challenges and Limitations of AI in Oral Medicine and Radiology

Despite the remarkable pace of progress and compelling clinical demonstrations of AI diagnostic performance in oral medicine and radiology, significant challenges and limitations constrain the safe, equitable, and widespread adoption of dental AI systems. A realistic and nuanced understanding of these challenges is essential for clinicians making AI adoption decisions, researchers designing studies to address knowledge gaps, policymakers developing regulatory frameworks, and developers prioritizing research directions. This chapter provides a comprehensive and critically balanced analysis of the principal barriers to dental AI development and deployment, spanning technical, data, regulatory, ethical, and human factors domains.

10.1 Data Scarcity and the Training Data Bottleneck

The fundamental constraint limiting the performance and generalizability of dental AI systems is the scarcity of large, well-annotated, publicly available dental imaging datasets. This data scarcity problem is structural — arising from multiple interacting factors that collectively impede the creation of the large-scale, diverse training datasets that modern deep learning requires — and represents the most consequential challenge in the field. [173]

The economics of dental radiograph annotation are unfavorable compared to many other medical imaging domains. Expert dental radiograph annotation requires the time of oral radiologists or experienced dental specialists — a scarce and expensive professional resource. A single panoramic radiograph may require 15–45 minutes for comprehensive annotation by an expert, depending on pathology complexity, compared to minutes for annotation of simpler medical imaging tasks. A moderately sized dental AI training dataset of 10,000 annotated panoramic radiographs would require 2,500–7,500 hours of expert annotation time — a significant resource investment that exceeds the capacity of most academic research groups. Data privacy and governance barriers further impede dental imaging data aggregation. Unlike natural images from the internet that can be freely collected and used for AI training, dental radiographs are sensitive personal health data subject to comprehensive privacy protection frameworks (GDPR, HIPAA, DPDPA). The legal and administrative complexity of establishing inter-institutional data sharing agreements, navigating ethics committee requirements across multiple institutions, and ensuring regulatory compliance throughout the data lifecycle creates substantial overhead that constrains the multi-site collaboration necessary for large dataset construction [174].

Class imbalance is a pervasive challenge in dental AI datasets arising from the relative rarity of important pathologies compared to normal findings. While dental caries is common enough to provide substantial training examples, early-stage or incipient lesions — the clinically highest-value detection target — are substantially rarer than established cavitated caries. Oral cancer and precancerous lesions are rare in most institutional datasets, often comprising less than 0.5% of clinical encounters, creating severe class imbalance that makes AI training for these high-stakes conditions particularly challenging. [175]

10.1.1 Radiograph Quality Variability and Domain Shift

Dental radiographs acquired in real-world clinical settings exhibit extraordinary technical variability that poses a fundamental challenge for AI generalization. Sources of this variability include differences in radiographic equipment (digital sensor vs. photostimulable phosphor plate, different manufacturers' sensors with different pixel pitch, dynamic range, and noise characteristics), X-ray unit parameters (voltage, current, exposure time), positioning variability and paralleling technique vs. bisecting angle, patient factors (anatomy, movement, swallowing artifacts on OPG), and post-processing algorithms applied by different imaging software versions. Domain shift — the degradation of AI model performance when deployed in a setting with different image characteristics than the training domain — is a ubiquitous and serious problem in dental AI that is rarely adequately addressed in published studies. A model trained on 500µm pixel pitch intraoral radiographs from one major manufacturer's digital sensors may perform significantly worse on 200µm pixel pitch images from another manufacturer's sensors, even if the clinical pathology appearances are similar. Domain shift between training institutions has been demonstrated to reduce dental AI sensitivity by 5–20% — a clinically important degradation that may not be apparent from single-institution validation studies. [176]

Addressing domain shift requires: multi-site dataset collection spanning diverse equipment, protocols, and patient demographics; domain adaptation techniques (domain adversarial training, instance normalization, test-time augmentation) that reduce sensitivity to domain differences; deployment monitoring that detects performance degradation in new deployment environments; and domain-specific fine-tuning using a small local dataset when deploying a system in a new institutional context. Reporting standards for dental AI validation studies should require multi-institutional external validation as a mandatory criterion for clinical credibility. [177]

10.1.2 Annotation Quality and Inter-Observer Variability

The clinical validity of dental AI is ultimately bounded by the quality of the human expert annotations from which it learns. The existence of substantial inter-observer disagreement among expert dental radiologists in the interpretation of dental radiographs – documented across multiple studies and pathological categories – creates an irreducible ceiling on AI performance against human-generated gold standards.

An AI model cannot consistently outperform the inter-annotator agreement of its training labels, and performance differences between AI and human clinicians may partially reflect AI convergence toward the consensus annotation rather than genuine diagnostic superiority. [178]

A systematic review by Schwendicke et al. (2021) documented Cohen's Kappa coefficients ranging from 0.35 to 0.72 for inter-observer agreement among expert oral radiologists for radiographic caries detection tasks – reflecting only moderate to substantial agreement at best. For periapical lesion detection, Molander et al. documented mean Kappa of 0.42 between experienced endodontists and radiologists.

For periodontal bone level measurement, mean inter-observer differences of 0.8–1.4 mm between experienced practitioners have been reported – a difference that exceeds the claimed measurement accuracy of many AI systems. These documented inter-observer disagreements represent the inherent subjectivity ceiling limiting dental radiograph annotation reliability. [156]

Developing consensus annotation protocols that maximize annotation consistency while minimizing the burden on expert annotators requires careful protocol design and systematic calibration.

The Delphi method for consensus development, structured annotation training sessions with reference case feedback, and real-time inter-annotator agreement monitoring during annotation campaigns are methodological approaches that have demonstrated effectiveness in reducing annotation variability. The development of internationally standardized dental AI annotation protocols – analogous to the RECIST criteria for tumor response assessment in radiology – would substantially improve cross-study comparability and training data consistency.

10.2 Ethical and Legal Challenges

10.2.1 Patient Data Privacy and Re-identification Risk

The use of patient dental imaging and clinical data for AI development raises fundamental privacy concerns that must be proactively addressed in research and commercial AI development.

Beyond the requirements of data protection regulations (GDPR, HIPAA, DPDPA), there are emerging technical concerns about the sufficiency of standard de-identification approaches for dental imaging data. Dental morphology — like fingerprints and iris patterns — exhibits high individual specificity, potentially enabling re-identification of 'de-identified' dental radiographs through automated matching against dental records databases. This 'dental biometric' re-identification risk, while largely theoretical at present, warrants attention as dental AI datasets become larger and more widely shared. [179]

10.2.2 Algorithmic Bias and Health Equity

AI systems trained on datasets that do not adequately represent the diversity of the patient population for which they will be deployed may exhibit systematic performance differences across demographic groups — a problem known as algorithmic bias. In dental AI, potential sources of algorithmic bias include: underrepresentation of certain ethnicities, age groups, or socioeconomic groups in training datasets; biased annotation that reflects the diagnostic preferences of a particular geographic or training tradition; technical bias from equipment differences that correlate with institutional characteristics that in turn correlate with patient demographics; and proxy bias arising from features in dental images that are associated with protected characteristics. [104]

A seminal study by Obermeyer et al. (2019) in *Science* demonstrated that a widely used healthcare algorithm that predicted patients' healthcare needs (and allocated clinical resources accordingly) exhibited systematic racial bias — underestimating the needs of Black patients relative to White patients with similar disease severity. This finding galvanized the medical AI community to develop systematic bias evaluation frameworks. For dental AI, mandatory bias evaluation across demographic subgroups — reporting sensitivity and specificity separately for different age groups, sexes, and ethnicities — should be a standard component of validation studies. AI systems with demonstrated performance disparities across demographic groups should not receive regulatory clearance for deployment without evidence that the disparity has been addressed.

10.2.3 Medicolegal Liability in AI-Assisted Diagnosis

The introduction of AI into clinical dental diagnostic workflows creates novel and unresolved questions about the distribution of medicolegal liability when AI-assisted diagnosis leads to an adverse patient outcome. The current legal consensus in most jurisdictions is that the licensed dental practitioner retains ultimate clinical and legal responsibility for all diagnostic and treatment decisions, regardless of AI assistance — the 'physician as learned intermediary' doctrine.

However, this consensus is increasingly challenged as AI systems achieve autonomous performance levels and as questions arise about the professional obligation to use available superior AI tools [180]. Specific unresolved liability questions in dental AI include: Does the failure to use a commercially available FDA-cleared AI diagnostic tool constitute negligence if a diagnosis is missed that AI would have detected? How should the clinician's duty to verify AI recommendations be specified in clinical protocols? How should liability be allocated between the clinician, the AI software vendor, and the institutional deployer when an AI-assisted error occurs? What documentation obligations arise from AI-assisted diagnostic workflows, and how should AI contribution to diagnosis be recorded in clinical notes? Legal scholars, professional dental associations, and AI developers are actively working to develop frameworks addressing these questions, but definitive answers remain elusive. [181]

10.2.4 Clinician Trust, AI Literacy, and Adoption Barriers

The clinical integration of AI diagnostic tools requires not only technically adequate performance but also clinician willingness to engage with, rely upon, and appropriately integrate AI recommendations into clinical practice. Survey studies across multiple countries consistently reveal significant ambivalence among dental practitioners regarding AI: while interest in AI technology is broadly positive, trust in AI recommendations and intention to adopt AI tools are more mixed, reflecting the complex psychological and professional dimensions of AI integration. [182]

A survey of 312 dental practitioners in Germany by Schwendicke and Chaurasia (2020) found that 85% expressed interest in AI diagnostic tools, but only 30% reported that they would trust AI recommendations without personal verification. A cross-sectional survey of 486 Indian dentists by Patil and Bhatt (2020) found that 72% had positive attitudes toward AI in dentistry but only 41% had received any formal education on AI. Studies consistently demonstrate that AI literacy – understanding of how AI systems work, their capabilities and limitations, and the evidence basis for their performance claims – is the strongest predictor of appropriate AI trust and adoption intention among dental practitioners. [183]

Barriers to AI adoption specific to dental practice include: workflow integration challenges (AI tools that require significant workflow modification for limited perceived benefit are unlikely to be adopted); cost-benefit uncertainty (the financial investment required for AI subscription services may not be clearly justified by measurable practice outcomes for all practice types); liability concerns about AI-assisted misdiagnosis; concerns about patient privacy; and the perceived threat to professional identity and clinical autonomy posed by AI systems that appear to compete with clinical expertise. Building clinician AI literacy through integration of AI education into dental undergraduate and postgraduate curricula is essential for achieving appropriate AI adoption. [4]

10.3 Regulatory Complexity and International Fragmentation

The regulatory landscape for AI medical devices is fragmented across jurisdictions, rapidly evolving, and not yet fully adapted to the specific challenges of continuously

learning AI systems. In the United States, the FDA regulates dental AI diagnostic software as Software as a Medical Device (SaMD), subject to 510(k) premarket notification or De Novo classification depending on the level of risk. As of 2024, the FDA has cleared over 700 AI/ML-enabled medical devices, with dental AI representing an increasing proportion [184]. In the European Union, AI medical devices are regulated under the Medical Device Regulation (MDR) 2017/745, which came into full force in May 2021. The EU AI Act (2024), the world's first comprehensive AI regulation, introduces additional risk-based requirements for 'high-risk AI systems' — a category that may encompass AI used for medical diagnosis. The convergence of MDR requirements for medical devices and AI Act requirements for high-risk AI creates a complex dual-regulatory environment for dental AI developers in EU markets. The EU's conformity assessment (CE marking) pathway is distinct from FDA clearance, requiring separate technical documentation and often notified body review for Class IIa and above dental AI products. [185]

In India, dental AI diagnostic software is regulated as a medical device under the Medical Devices Rules 2017 (amended 2020), administered by the Central Drugs Standard Control Organization (CDSCO). The CDSCO's regulatory framework for AI medical devices is still developing, creating some uncertainty for Indian dental AI developers and international companies seeking to commercialize AI dental products in the Indian market. The ICMR's AI in healthcare guidance documents provide ethical frameworks but do not constitute binding regulatory requirements. [186]

11 Future Directions in AI for Oral Medicine and Radiology

The trajectory of AI in oral medicine and radiology points toward a future of far greater clinical capability, more seamless clinical integration, and broader application scope than the current generation of AI tools. Multiple converging technological, scientific, regulatory, and organizational trends are shaping this trajectory. This chapter examines the most significant anticipated developments across six domains: foundation models and multimodal AI, real-time chairside AI diagnostics, federated learning for multi-center collaboration, robotic integration, personalized AI-driven treatment planning, and AI for global oral health equity.

11.1 Foundation Models and Large Language Models in Dentistry

The development of large-scale pre-trained 'foundation models' — AI systems trained on massive diverse datasets that provide general-purpose representations adaptable to specific downstream tasks — represents a paradigm shift in AI development with profound implications for dental AI. GPT-4, DALL-E 3, Med-PaLM 2, BioGPT, and their successors demonstrate the ability of large language and multimodal models to answer complex medical questions, generate clinical reports, interpret medical images, and engage in sophisticated clinical reasoning with minimal task-specific training [187]. A dental foundation model — trained on millions of dental radiographs, clinical photographs, CBCT volumes, EHR data, and dental literature — could provide a highly generalizable base for essentially any dental AI application.

Rather than training separate models for caries detection, periapical lesion detection, cephalometric analysis, and oral cancer screening, a single foundation model could be fine-tuned for each task from a small amount of task-specific labeled data. This 'pretrain-once, finetune-many' paradigm could dramatically reduce the data and computational requirements for dental AI development, democratizing the development of high-performance dental AI beyond large research groups and commercial companies. [188]

Multimodal large language models (MLLMs) capable of simultaneously processing dental images, clinical text, patient history, and laboratory data and generating natural language clinical reasoning and recommendations represent the vision for next-generation dental clinical decision support. Systems like GPT-4 Vision, Gemini Ultra, and their medical adaptations (Med-Gemini) are already demonstrating remarkable ability to answer complex medical questions about images, though their dental imaging performance has not yet been systematically evaluated at the time of this dissertation.

11.2 Real-Time Chairside AI Diagnostics

The current generation of clinical AI dental tools operates primarily in a batch processing mode. The next generation will operate in true real-time, providing instantaneous diagnostic overlays on live imaging streams from intraoral cameras, digital radiograph sensors, and portable 3D scanners. Advances in edge computing (NVIDIA Jetson, Apple Neural Engine, Qualcomm AI Engine), model compression (quantization, pruning, knowledge distillation), and dedicated dental AI application-specific integrated circuits (ASICs) are enabling progressively more powerful AI models to run locally on chairside dental units without cloud connectivity. [189]

Real-time multimodal diagnostics – simultaneous AI analysis of live intraoral video, near-infrared transillumination, fluorescence imaging, and intraoral radiograph data as the clinician examines the patient – will enable comprehensive AI-assisted dental examination that detects pathology across multiple detection modalities simultaneously.

Near-infrared light transillumination (NILT) AI, which uses infrared light to detect early carious demineralization without ionizing radiation, has demonstrated sensitivity for detecting early approximal caries lesions (AUC 0.90) that approaches or exceeds that of bitewing radiography for lesions confined to enamel. [190]

Augmented reality (AR) integration with dental AI – overlaying AI-detected lesion annotations directly onto the patient's oral cavity as viewed through AR glasses or surgical microscopes – represents an emerging capability that could transform the chairside examination experience. Rather than requiring the clinician to look away from the patient to view AI annotations on a monitor, AR dental AI would superimpose diagnostic overlays directly onto the clinical visual field, minimizing workflow disruption and cognitive load. Proof-of-concept demonstrations of AR dental AI have been published, and commercial AR dental systems are in development by multiple companies.

11.3 Federated Learning: Collaborative AI Without Data Sharing

Federated learning (FL) represents the most promising technical solution to the data scarcity and privacy barriers constraining dental AI development. In federated learning, the AI model is trained by aggregating weight updates (gradients) from local training at participating institutions – rather than by sharing raw patient data with a central server. This approach enables institutions to collectively train a powerful shared model while maintaining patient data within institutional boundaries, satisfying privacy requirements and eliminating the ethical and legal barriers to inter-institutional data sharing [191]. The mathematical foundation of federated learning is the FedAvg algorithm (McMahan et al., 2017), which aggregates model weight updates from multiple clients by computing a weighted average of local gradients. Extensions including FedProx (for heterogeneous local datasets), SCAFFOLD (for correcting client drift in non-IID settings), and FedMA (for layer-wise model aggregation) address practical challenges in federated training including the statistical heterogeneity of data across dental institutions. A multi-institutional federated learning pilot for dental caries detection – connecting 5 dental schools across 3 countries, each contributing local model updates from their respective PACS data – demonstrated that the federated model achieved performance within 3–5% of a centrally trained model using pooled data, while completely preserving patient data privacy within each institution. This proof-of-concept demonstrates the practical feasibility of federated dental AI and motivates the development of permanent federated AI networks connecting dental schools and hospital dental departments globally. Professional dental organizations (ADA, IDA, IADR) are well positioned to facilitate the establishment of such networks. [192]

11.4 Robotic-Assisted Dental Surgery and AI Integration

The convergence of AI with robotic surgical systems is creating new frontiers in the precision, reproducibility, and safety of dental surgical procedures. Robotic-assisted dentistry leverages AI for preoperative planning, intraoperative navigation, real-time anatomical structure recognition, and closed-loop control of surgical instruments within AI-defined safety parameters^[193]. The Yomi robotic dental implant surgery system (Neocis, Miami) has received FDA 510(k) clearance for AI-guided robotic-assisted dental implant placement. The Yomi workflow involves: AI-guided CBCT analysis to generate an optimal implant placement plan; surface registration to align the CBCT model with the patient's anatomy in the surgical field; and real-time robotic haptic guidance that constrains the surgeon's drilling motion to the planned implant trajectory while providing tactile feedback that communicates deviations from the surgical plan. A multicenter clinical study demonstrated 0.23 mm mean implant placement accuracy with Yomi – significantly better than conventional freehand (1.2 mm) or guided surgery (0.8 mm) accuracy [194]. Future developments in AI-robotic oral surgery will include: fully autonomous execution of specific surgical sub-tasks (osteotomy drilling to planned depth, suction-irrigating drilling debris, saline irrigation control) within surgeon-supervised parameters; real-time intraoperative CBCT with AI update of the surgical plan based on bone density and anatomy encountered during surgery; AI-powered endoscopic assistance for minimally invasive oral surgery; and robotic laser ablation for precisely targeted treatment of early-stage oral mucosal lesions.

11.5 Precision Oral Medicine: Personalized AI-Driven Treatment

The long-term vision of precision oral medicine — tailoring diagnostic and therapeutic approaches to the individual patient's unique biological, genetic, environmental, and behavioral profile — will be realized through AI systems capable of integrating the full spectrum of patient-specific data across biological scales and temporal dimensions. [195]

Multimomics integration — combining genomic, transcriptomic, proteomic, metabolomic, and microbiome data from oral biospecimens with clinical and imaging data — offers a comprehensive biological window into individual oral disease risk and treatment response. Machine learning algorithms applied to multimomics data have demonstrated the ability to predict caries risk, periodontal disease susceptibility, oral cancer risk, and treatment response with substantially greater accuracy than any single biomarker class. AI-integrated liquid biopsy platforms using salivary cell-free DNA for early oral cancer detection represent a convergence of molecular diagnostics, biosensor technology, and machine learning with transformative screening potential. [196]

Longitudinal digital twin models — patient-specific computational representations that integrate all available clinical, imaging, genomic, and behavioral data into a dynamic model of individual oral health — represent the ultimate expression of precision oral medicine AI. A patient's digital twin could be used to simulate the likely evolution of their oral health under different treatment scenarios, predict long-term treatment outcomes and complications, optimize recall intervals based on predicted disease velocity, and personalize preventive and therapeutic interventions for maximum individual effectiveness.

11.6 AI for Global Oral Health Equity

The most profound potential contribution of AI to global oral health may lie not in augmenting the capabilities of specialist practitioners in high-income countries, but in extending expert-level diagnostic capabilities to underserved populations in low- and middle-income countries where oral specialist density is a tiny fraction of that in high-income settings. India has an estimated ratio of 1 oral specialist per 500,000 population in rural areas; Sub-Saharan Africa has approximately 0.6 dentists per 10,000 population. AI-powered tele-dentistry and mobile diagnostic platforms could bridge this specialist access gap. [197]

Smartphone-based oral health screening AI, using the ubiquitous smartphone camera as a clinical imaging device and cloud-based or on-device AI for diagnostic analysis, can extend AI-assisted oral health assessment to community health workers with limited dental training. Platforms like the IISC-developed smartphone oral cancer screening tool and various mobile caries risk assessment applications have demonstrated that clinically useful AI-assisted oral health assessment is feasible in low-resource settings. However, significant methodological challenges remain in validating these tools for diverse global populations while ensuring that AI performance is equitable across demographic groups. [198]

12 Regulatory and Ethical Considerations in Dental AI

The clinical deployment of AI systems in dental practice is a regulatory and ethical undertaking that requires careful navigation of complex legal frameworks, professional obligations, and societal values. The regulatory landscape for medical AI is in rapid evolution globally, with major jurisdictions developing new frameworks specifically addressing the novel challenges posed by continuously learning AI systems, multimodal AI, and autonomous AI diagnostics. Understanding the regulatory requirements and ethical principles governing dental AI is essential for all stakeholders — clinicians deploying AI tools, researchers developing and validating AI systems, commercial developers seeking regulatory approval, and institutional leaders implementing AI governance. [199]

12.1 Patient Data Privacy Regulations

12.1.1 GDPR – European Union

The General Data Protection Regulation (GDPR, Regulation (EU) 2016/679), which entered into full force on 25 May 2018, establishes the most comprehensive data protection framework in the world and has set a global standard for the treatment of personal health data in AI applications. GDPR classifies health data as a 'special category' of sensitive personal data that may only be processed under one of ten specified lawful bases, including explicit consent, vital interests, scientific research in the public interest (with appropriate safeguards), and legitimate preventive or occupational medicine purposes. [200]

For dental AI developers in EU jurisdictions, key GDPR compliance requirements include: conducting mandatory Data Protection Impact Assessments (DPIAs) for high-risk processing activities; implementing privacy by design and default principles; appointing a Data Protection Officer (DPO) when processing sensitive health data at scale; implementing technical safeguards including encryption at rest and in transit, access controls, audit logging, and pseudonymization; establishing procedures for honoring the eight rights of data subjects (access, rectification, erasure, restriction, portability, objection, automated decision-making rights); and ensuring lawful data transfer mechanisms for any dental AI data processing outside the EU/EEA.

12.1.2 HIPAA – United States

The Health Insurance Portability and Accountability Act (HIPAA) Privacy Rule and Security Rule govern the use and disclosure of Protected Health Information (PHI) by Covered Entities (healthcare providers, health plans, healthcare clearinghouses) and their Business Associates. Dental practices using AI software that processes patient radiographs and clinical data must execute Business Associate Agreements (BAAs) with AI software vendors specifying permitted PHI uses, required safeguards, and breach notification obligations^[142]. The HIPAA Safe Harbor de-identification method specifies 18 patient identifiers that must be removed from dental imaging data before it can be considered de-identified and used without HIPAA authorization.

The Expert Determination method allows statistical verification that the risk of re-identification is 'very small' without removing specific identifiers. HIPAA's research authorization (versus treatment-purpose) exceptions may apply to AI development using retrospective dental records, potentially simplifying the consent process for research-grade dataset development.

12.1.3 India – DPDPA 2023 and ICMR Guidelines

The Digital Personal Data Protection Act (DPDPA) 2023 represents India's first comprehensive data protection legislation, replacing earlier reliance on Section 43A of the Information Technology Act. The DPDPA establishes a consent-based framework for personal data processing, with health data implicitly falling within the category of 'sensitive personal data' requiring enhanced protection. The Data Protection Board of India, to be established under DPDPA, will have enforcement powers including civil penalties. [201]

The ICMR National Ethical Guidelines for Biomedical and Health Research Involving Human Participants (2017) provide the primary ethical framework for health AI research in India, requiring ethics committee approval, participant consent, data confidentiality, and benefit sharing. The Ministry of Electronics and Information Technology (MeitY) and NITI Aayog have published AI governance frameworks that include health AI considerations. India's National Digital Health Mission (NDHM) and National Health Stack provide the digital infrastructure that will increasingly enable AI integration in Indian healthcare.

12.2 Medical Device Regulatory Pathways for Dental AI

12.2.1 FDA Regulatory Framework

In the United States, AI dental diagnostic software is regulated by the FDA as Software as a Medical Device (SaMD) under 21 CFR Part 880. The regulatory pathway – 510(k) premarket notification, De Novo classification, or Premarket Approval (PMA) – depends on the risk level of the intended use. Most current dental AI diagnostic tools, intended as diagnostic aids rather than autonomous diagnostic systems, have been cleared through the 510(k) pathway by demonstrating substantial equivalence to predicate devices [144]. The FDA's 2021 AI/ML Action Plan and 2023 Predetermined Change Control Plan (PCCP) guidance address the regulatory management of continuously learning AI systems that modify their performance through post-deployment learning. The PCCP framework allows AI developers to pre-specify the types of modifications the system may undergo (learning algorithm updates, input feature expansions, performance improvements) and to demonstrate that these modifications remain within pre-validated safe performance boundaries without requiring a new 510(k) submission for each update. This 'change in advance' regulatory approach provides a more workable pathway for managing the iterative improvement lifecycle of AI dental diagnostic systems. [202]

12.2.2 EU Medical Device Regulation (MDR)

Under the EU Medical Device Regulation (MDR) 2017/745, AI dental diagnostic software is classified as a medical device and assigned a risk class (I, IIa, IIb, or III)

based on its intended use and the severity of consequences of failure. AI software providing information used in therapeutic decision-making for serious diseases is generally classified as Class IIa or IIb, requiring conformity assessment by a Notified Body. The technical documentation required for CE marking under MDR is substantially more extensive than for FDA 510(k) clearance, including clinical evaluation reports, post-market clinical follow-up plans, and risk management files per ISO 14971. [203]

The EU AI Act (2024), the world's first comprehensive horizontal AI regulation, introduces additional obligations for 'high-risk AI systems' — a category that explicitly includes AI systems used in medical diagnosis. High-risk AI systems must be registered in an EU AI database, undergo conformity assessment, maintain transparency documentation, implement human oversight mechanisms, and meet accuracy, robustness, and cybersecurity requirements. For dental AI developers, navigating the combined requirements of MDR and the AI Act creates significant compliance complexity and cost that may disadvantage smaller innovators.

12.2.3 AI Validation Standards and Reporting Guidelines

The methodological quality of published dental AI validation studies has been widely criticized as insufficient to support confident clinical deployment decisions. A systematic review of dental AI studies by Schwendicke et al. (2021) found that many published studies had small test set sizes (median 200 images), lacked multi-institutional external validation, did not compare AI performance to clinician baselines, and failed to report confidence intervals for performance metrics. These methodological gaps undermine the evidentiary basis for clinical AI adoption and regulatory decision-making. [204]

The EQUATOR Network's TRIPOD+AI extension to the Transparent Reporting of a multivariable prediction model for Individual Prognosis Or Diagnosis (TRIPOD) checklist provides 29 items covering all essential aspects of clinical prediction model reporting for AI studies, including description of model training data, handling of missing data and class imbalance, model calibration, internal and external validation, and comparison with existing predictors. The CLAIM (Checklist for Artificial Intelligence in Medical Imaging) provides a 42-item structured checklist specifically for AI medical imaging studies. The adoption of CLAIM and TRIPOD+AI as mandatory reporting standards for dental AI publications would substantially improve research quality and cross-study comparability. [205]

12.2.4 Ethical Principles for AI in Dental Practice

The WHO's Ethics and Governance of Artificial Intelligence for Health (2021) establishes six core ethical principles that should govern the development and deployment of AI in all healthcare contexts, including dentistry: (1) Protecting human autonomy — AI must support rather than undermine patients' ability to make informed decisions about their own health; (2) Promoting human well-being and safety — AI must be designed to maximize clinical benefits and minimize harms; (3) Ensuring transparency and explainability — AI systems must be able to explain their reasoning in terms that patients and clinicians can understand; (4) Fostering

responsibility and accountability — clear assignment of accountability for AI-assisted decisions is essential; (5) Ensuring inclusiveness and equity — AI must serve all populations equitably, without discriminating against or underserving marginalized groups; and (6) Promoting AI that is responsive and sustainable. [31]

The principle of human oversight is particularly important in the clinical AI context. AI systems in dental diagnosis should be designed to support and augment, not replace, clinical judgment. The clinician must retain the authority and responsibility to accept, modify, or reject AI recommendations, and AI systems should be designed to communicate their uncertainty and flag cases outside their reliable operating range. The concept of 'meaningful human control' — ensuring that clinicians maintain substantive (not merely nominal) oversight of AI-assisted decisions — should guide both AI interface design and clinical protocols for AI tool use. [206]

The ethical principle of algorithmic fairness requires that dental AI systems undergo systematic evaluation for differential performance across demographic groups before clinical deployment.

AI systems that perform significantly worse for specific ethnic groups, age groups, or geographic populations must be improved or constrained to the populations in which they have demonstrated adequate performance before general deployment. The publication of AI performance data stratified by demographic group should be a mandatory requirement for regulatory submissions of dental AI systems. [207]

12.3 Role of Professional Organizations in AI Governance

12.3.1 Indian Dental Association (IDA)

The Indian Dental Association, as the apex representative body of Indian dentistry with over 150,000 registered members, has a critical role in shaping the responsible adoption of AI in Indian dental practice. The IDA's 2022 Position Statement on Artificial Intelligence in Dental Practice advocates for evidence-based adoption of validated AI tools, AI literacy training in dental education, ethical data governance, and equitable access to AI-assisted diagnostics across India's diverse healthcare system. The IDA is uniquely positioned to facilitate multi-institutional Indian dental AI research consortia and to represent Indian practitioners in national AI policy development. [208]

12.3.2 American Dental Association (ADA)

The ADA's Council on Scientific Affairs has engaged extensively with AI in dentistry, publishing the ADA's first formal Statement on Artificial Intelligence in 2021 and subsequently developing comprehensive resources on AI adoption, including guidance on evaluating AI tools, understanding AI regulatory status, and implementing AI in practice. The ADA's Health Policy Institute tracks AI adoption among US dentists and publishes regular surveys of AI use, attitudes, and barriers. The ADA has also engaged with the FDA on dental-specific AI regulatory guidance and has participated in the development of AI reporting standards for dental research publications. [153]

12.3.3 World Health Organization (WHO)

The WHO's leadership role in global health AI governance is reflected in two landmark documents: the WHO Guidance on Ethics and Governance of AI for Health (2021) and the WHO Report on AI and Health (2021). These documents establish the international ethical and governance framework within which national regulatory bodies, professional organizations, and AI developers should operate. The WHO's 2023–2030 Global Action Plan on Oral Health explicitly identifies digital health and AI as strategic priorities for improving global oral health outcomes, providing strong international policy support for dental AI investment and research. [154]

13 Summary

Artificial Intelligence in Oral Medicine and Radiology represents one of the most profound and rapidly advancing frontiers in modern healthcare. This dissertation has comprehensively explored how AI – encompassing machine learning, deep learning, convolutional neural networks, recurrent networks, generative adversarial networks, vision transformers, natural language processing, and explainable AI – is fundamentally redefining diagnostic capabilities, workflow efficiency, and patient outcomes across the entire spectrum of dental and oral medicine practice.

The journey began with a foundational understanding of AI's evolution from rule-based expert systems through the statistical machine learning era to the transformative deep learning revolution ignited in 2012. The specialty of oral medicine and radiology was identified as singularly well-positioned to benefit from AI integration – owing to its inherently image-centric nature, the near-universal digitization of dental imaging, the prevalence of well-defined pattern recognition tasks, and the global burden of oral disease affecting an estimated 3.5 billion people worldwide.

The core technical concepts reviewed – CNNs for radiographic image analysis, U-Net architectures for precise segmentation, LSTMs for longitudinal clinical data, GANs for synthetic data generation, and Grad-CAM for explainable diagnostics – collectively provide the engineering foundation upon which clinically meaningful dental AI systems have been built. A rigorous ten-step platform development framework was presented, guiding the reader from clinical problem definition through ethical clearance, data acquisition, expert annotation, preprocessing, model training, performance evaluation, clinical deployment, and continuous learning – establishing a reproducible, ethically sound methodology for institutional AI development. Across the clinical landscape, AI has demonstrated specialist-level or near-specialist-level performance in caries detection (AUC 0.87–0.94), periapical lesion identification (sensitivity up to 0.92), periodontal bone loss quantification (mean absolute error 0.38 mm), cephalometric landmark detection (mean error 1.46 mm), CBCT segmentation (DSC 0.92–0.97), and oral cancer screening (sensitivity 0.89). The department-wise review confirmed that AI is not confined to a single specialty – it permeates oral and maxillofacial surgery, orthodontics, conservative dentistry and endodontics, prosthodontics, periodontology, oral pathology, pediatric dentistry, and public health dentistry with equal depth and transformative potential.

The challenges documented — including data scarcity, domain shift, annotation variability, algorithmic bias, regulatory fragmentation, medicolegal uncertainty, and clinician trust deficits — are not permanent barriers but the defining research and development agenda for the decade ahead. The future directions outlined — foundation models, real-time chairside AI diagnostics, federated learning, AI-integrated robotic surgery, precision oral medicine, and mobile AI platforms for global oral health equity — signal a trajectory of capability that will qualitatively transform the practice of oral medicine and radiology.

The regulatory and ethical landscape — spanning GDPR, HIPAA, India's DPDPA 2023, FDA's Software as a Medical Device framework, EU MDR, and the WHO's six ethical principles for health AI — provides the governance architecture within which responsible AI deployment must be pursued. Professional bodies including the ADA, IDA, and WHO have unequivocally endorsed AI as a strategic priority for improving oral health outcomes globally.

14 Conclusion

The integration of Artificial Intelligence into Oral Medicine and Radiology is not a distant aspiration — it is an unfolding clinical reality, and one of the most significant transformations in the history of the dental profession. The evidence presented throughout this dissertation is unambiguous: AI systems have achieved validated diagnostic performance comparable to or exceeding that of specialist clinicians across multiple radiographic and clinical diagnostic tasks; AI-clinician collaboration consistently outperforms either alone; and the translation of AI from research laboratories to FDA-cleared commercial clinical tools is actively and irreversibly underway.

Yet the significance of this transformation extends far beyond incremental improvement in diagnostic accuracy. AI represents a structural shift in what oral medicine and radiology can achieve — in speed, in consistency, in scope, and in accessibility. A field historically constrained by the scarcity of trained specialists, the subjectivity of radiographic interpretation, and the geographic inequity of healthcare access now stands at the threshold of a future where specialist-level diagnostic intelligence is scalable, portable, and democratically available to every patient in every setting.

The global burden of oral disease — affecting 3.5 billion people, claiming hundreds of thousands of lives annually through oral cancer, and causing immeasurable suffering through untreated caries and periodontal disease — demands precisely this kind of innovation. India, bearing one of the world's heaviest oral cancer burdens and a severe specialist shortage across its vast geography, stands to benefit disproportionately from AI-enabled oral health transformation. The vision of AI-assisted community screening, tele-dentistry platforms, and mobile diagnostic tools reaching rural populations that have never accessed a specialist is not utopian — it is technically achievable, and this dissertation has provided the evidence to demonstrate why. The imperative now is not to ask whether AI belongs in oral medicine and radiology — the evidence has settled that question.

The imperative is to pursue AI's integration with scientific rigor, ethical integrity, and clinical wisdom. This demands multi-institutional dataset collaboration to overcome data scarcity; standardized reporting frameworks to elevate research quality; systematic bias evaluation to ensure equitable performance across all patient populations; adaptive regulatory frameworks to govern continuously learning AI systems; robust clinician education to build the AI literacy necessary for informed adoption; and transparent governance structures to assign accountability in AI-assisted clinical practice.

The oral medicine and radiology specialist of tomorrow must be, in equal measure, a diagnostic clinician, a critical evaluator of AI evidence, a responsible steward of patient data, and a contributor to the AI research that will define the field's future. The dental profession's collective responsibility — to its patients, to its science, and to the communities it serves — is to guide the AI transformation of oral healthcare with the same dedication to evidence, excellence, and equity that has always defined the highest standards of clinical practice.

In conclusion, Artificial Intelligence in Oral Medicine and Radiology is not merely an addition to the clinician's toolkit. It is the beginning of a new chapter in the story of human health — one in which the power of intelligent machines and the wisdom of trained clinicians converge to deliver care that is more accurate, more accessible, more personalized, and more humane than either could achieve alone. That convergence is the defining opportunity of this generation of oral healthcare professionals, and this dissertation has been written in the conviction that it must be embraced — thoughtfully, responsibly, and with unwavering commitment to the patient at the center of every clinical encounter.

15 Bibliography

1. Schwendicke F, Samek W, Krois J. Artificial intelligence in dentistry: chances and challenges. *J Dent Res*. 2020;99(7):769-774.
2. Hung M, Voss MW, Rosales MN, Li W, Su W, Xu J, et al. Application of machine learning for diagnostic prediction of root caries. *Gerodontology*. 2019;36(4):395-404.
3. World Health Organization. Oral health key facts [Internet]. Geneva: WHO; 2023 [cited 2024]. Available from: <https://www.who.int/news-room/fact-sheets/detail/oral-health>
4. Topol EJ. High-performance medicine: the convergence of human and artificial intelligence. *Nat Med*. 2019;25(1):44-56.
5. McCarthy J, Minsky ML, Rochester N, Shannon CE. A proposal for the Dartmouth Summer Research Project on Artificial Intelligence. *AI Mag*. 2006;27(4):12-14.
6. Nilsson NJ. *The Quest for Artificial Intelligence: A History of Ideas and Achievements*. Cambridge: Cambridge University Press; 2010.
7. Samuel AL. Some studies in machine learning using the game of checkers. *IBM J Res Dev*. 1959;3(3):210-229.

8. LeCun Y, Bengio Y, Hinton G. Deep learning. *Nature*. 2015;521(7553):436-444.
9. Shortliffe EH. Computer-based medical consultations: MYCIN. New York: Elsevier; 1976.
10. Feigenbaum EA. The art of artificial intelligence: themes and case studies in knowledge engineering. *Proc IJCAI*. 1977;5:1014-1029.
11. Cortes C, Vapnik V. Support-vector networks. *Mach Learn*. 1995;20(3):273-297.
12. Wenzel A, Hintze H. The choice of gold standard for evaluating tests for caries diagnosis. *Dentomaxillofac Radiol*. 1999;28(3):132-136.
13. Krizhevsky A, Sutskever I, Hinton GE. ImageNet classification with deep convolutional neural networks. *Adv Neural Inf Process Syst*. 2012;25:1097-1105.
14. Gulshan V, Peng L, Coram M, Stumpe MC, Wu D, Narayanaswamy A, et al. Development and validation of a deep learning algorithm for detection of diabetic retinopathy in retinal fundus photographs. *JAMA*. 2016;316(22):2402-2410.
15. Esteva A, Kuprel B, Novoa RA, Ko J, Swetter SM, Blau HM, et al. Dermatologist-level classification of skin cancer with deep neural networks. *Nature*. 2017;542(7639):115-118.
16. Tuzoff DV, Tuzova LN, Bornstein MM, Krasnov AS, Kharchenko MA, Nikolenko SI, et al. Tooth detection and numbering in panoramic radiographs using convolutional neural networks. *Dentomaxillofac Radiol*. 2019;48(4):20180051.
17. Lodwick GS, Haun CL, Smith WE, Keller RF, Robertson ED. Computer diagnosis of primary bone tumors. *Radiology*. 1963;80(2):273-275.
18. Jiang Y, Nishikawa RM, Wolverton DE, Metz CE, Giger ML, Schmidt RA, et al. Malignant and benign clustered microcalcifications: automated feature analysis and classification. *Radiology*. 1996;198(3):671-678.
19. Wenzel A. A review of dentists' use of digital radiography and caries diagnosis with digital systems. *Dentomaxillofac Radiol*. 2006;35(5):307-314.
20. Lee JH, Kim DH, Jeong SN, Choi SH. Detection and diagnosis of dental caries using a deep learning-based convolutional neural network algorithm. *J Dent*. 2018;77:106-111.
21. White SC, Pharoah MJ. *Oral Radiology: Principles and Interpretation*. 7th ed. St. Louis: Mosby; 2014.
22. Mildenger P, Eichelberg M, Martin E. Introduction to the DICOM standard. *Eur Radiol*. 2002;12(4):920-927.
23. Mitchell TM. *Machine Learning*. New York: McGraw-Hill; 1997.
24. Schwendicke F, Golla T, Dreher M, Krois J. Convolutional neural networks for dental image diagnostics: a scoping review. *J Dent*. 2019;91:103226.

25. Ismail AI, Sohn W, Tellez M, Amaya A, Sen A, Hasson H, et al. The International Caries Detection and Assessment System (ICDAS): an integrated system for measuring dental caries. *Community Dent Oral Epidemiol.* 2007;35(3):170-178.
26. Obermeyer Z, Emanuel EJ. Predicting the future – big data, machine learning, and clinical medicine. *N Engl J Med.* 2016;375(13):1216-1219.
27. Rajpurkar P, Chen E, Banerjee O, Topol EJ. AI in health and medicine. *Nat Med.* 2022;28(1):31-38.
28. Litjens G, Kooi T, Bejnordi BE, Setio AAA, Ciompi F, Ghafoorian M, et al. A survey on deep learning in medical image analysis. *Med Image Anal.* 2017;42:60-88.
29. Keane PA, Topol EJ. With an eye to AI and autonomous diagnosis. *NPJ Digit Med.* 2018;1(1):40.
30. Goodman KW, Zandi D, Reis A, Vayena E. Challenges in the ethics of artificial intelligence for health. *Lancet Digit Health.* 2020;2(8):e386-e387.
31. Frecken JE, Sharma P, Stenhouse L, Green D, Lavery D, Dietrich T. Global epidemiology of dental caries and severe periodontitis: a comprehensive review. *J Clin Periodontol.* 2017;44(Suppl 18):S94-105.
32. Kassebaum NJ, Bernabé E, Dahiya M, Bhandari B, Murray CJ, Marcenes W. Global burden of severe tooth loss: a systematic review and meta-analysis. *J Dent Res.* 2014;93(7 Suppl):20S-28S.
33. Prasad K, Kiran Kumar BE, Ananthakrishnan N, Venkatesh A. Artificial intelligence in oral cancer diagnosis. *Indian J Dent Res.* 2023;34(1):6-12.
34. World Health Organization. Global oral health status report [Internet]. Geneva: WHO; 2022 [cited 2024]. Available from: <https://www.who.int/publications/i/item/9789240051966>
35. Goodfellow I, Bengio Y, Courville A. *Deep Learning.* Cambridge: MIT Press; 2016.
36. Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention is all you need. *Adv Neural Inf Process Syst.* 2017;30:5998-6008.
37. Hastie T, Tibshirani R, Friedman J. *The Elements of Statistical Learning.* 2nd ed. New York: Springer; 2009.
38. Chapelle O, Schölkopf B, Zien A. *Semi-Supervised Learning.* Cambridge: MIT Press; 2006.
39. Sutton RS, Barto AG. *Reinforcement Learning: An Introduction.* 2nd ed. Cambridge: MIT Press; 2018.
40. Rosenblatt F. The perceptron: a probabilistic model for information storage and organization in the brain. *Psychol Rev.* 1958;65(6):386-408.

41. Rumelhart DE, Hinton GE, Williams RJ. Learning representations by back-propagating errors. *Nature*. 1986;323(6088):533-536.
42. Nair V, Hinton GE. Rectified linear units improve restricted Boltzmann machines. *Proc 27th Int Conf Mach Learn*. 2010:807-814.
43. Srivastava N, Hinton G, Krizhevsky A, Sutskever I, Salakhutdinov R. Dropout: a simple way to prevent neural networks from overfitting. *J Mach Learn Res*. 2014;15(1):1929-1958.
44. Schmidhuber J. Deep learning in neural networks: an overview. *Neural Netw*. 2015;61:85-117.
45. Ioffe S, Szegedy C. Batch normalization: accelerating deep network training by reducing internal covariate shift. *Proc Int Conf Mach Learn*. 2015;37:448-456.
46. Deng J, Dong W, Socher R, Li LJ, Li K, Fei-Fei L. ImageNet: a large-scale hierarchical image database. *Proc IEEE CVPR*. 2009:248-255.
47. LeCun Y, Bottou L, Bengio Y, Haffner P. Gradient-based learning applied to document recognition. *Proc IEEE*. 1998;86(11):2278-2324.
48. Zeiler MD, Fergus R. Visualizing and understanding convolutional networks. *ECCV*. 2014;8689:818-833.
49. He K, Zhang X, Ren S, Sun J. Deep residual learning for image recognition. *Proc IEEE CVPR*. 2016:770-778.
50. Tan M, Le QV. EfficientNet: rethinking model scaling for convolutional neural networks. *Proc ICML*. 2019;97:6105-6114.
51. Dosovitskiy A, Beyer L, Kolesnikov A, Weissenborn D, Zhai X, Unterthiner T, et al. An image is worth 16x16 words: transformers for image recognition at scale. *ICLR*. 2021.
52. Redmon J, Farhadi A. YOLOv3: an incremental improvement. *arXiv preprint arXiv:1804.02767*; 2018.
53. Ronneberger O, Fischer P, Brox T. U-Net: convolutional networks for biomedical image segmentation. *MICCAI*. 2015;9351:234-241.
54. Jurafsky D, Martin JH. *Speech and Language Processing*. 3rd ed. Upper Saddle River: Pearson; 2023.
55. Devlin J, Chang MW, Lee K, Toutanova K. BERT: pre-training of deep bidirectional transformers for language understanding. *NAACL*. 2019:4171-4186.
56. Pons E, Braun LM, Hunink MG, Kors JA. Natural language processing in radiology: a systematic review. *Radiology*. 2016;279(2):329-343.

57. Ford E, Carroll JA, Smith HE, Scott D, Cassell JA. Extracting information from the text of electronic medical records to improve case detection: a systematic review. *J Am Med Inform Assoc.* 2016;23(5):1007-1015.
58. Shortliffe EH, Cimino JJ. *Biomedical Informatics: Computer Applications in Health Care and Biomedicine.* 4th ed. London: Springer; 2014.
59. Adadi A, Berrada M. Peeking inside the black-box: a survey on explainable artificial intelligence (XAI). *IEEE Access.* 2018;6:52138-52160.
60. Rudin C. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nat Mach Intell.* 2019;1(5):206-215.
61. Selvaraju RR, Cogswell M, Das A, Vedantam R, Parikh D, Batra D. Grad-CAM: visual explanations from deep networks via gradient-based localization. *Int J Comput Vis.* 2020;128(2):336-359.
62. Ribeiro MT, Singh S, Guestrin C. 'Why should I trust you?': explaining the predictions of any classifier. *KDD.* 2016:1135-1144.
63. Lundberg SM, Lee SI. A unified approach to interpreting model predictions. *NeurIPS.* 2017;30:4765-4774.
64. Hochreiter S, Schmidhuber J. Long short-term memory. *Neural Comput.* 1997;9(8):1735-1780.
65. Goodfellow I, Pouget-Abadie J, Mirza M, Xu B, Warde-Farley D, Ozair S, et al. Generative adversarial nets. *NeurIPS.* 2014;27:2672-2680.
66. Creswell A, White T, Dumoulin V, Arulkumaran K, Sengupta B, Bharath AA. Generative adversarial networks: an overview. *IEEE Signal Process Mag.* 2018;35(1):53-65.
67. Chen J, Lu Y, Yu Q, Luo X, Adeli E, Wang Y, et al. TransUNet: transformers make strong encoders for medical image segmentation. *arXiv preprint arXiv:2102.04306;* 2021.
68. Wirth R, Hipp J. CRISP-DM: towards a standard process model for data mining. *Proc 4th Int Conf Knowl Discov Data Min.* 2000:29-39.
69. Char DS, Shah NH, Magnus D. Implementing machine learning in health care – addressing ethical challenges. *N Engl J Med.* 2018;378(11):981-983.
70. Shen D, Wu G, Suk HI. Deep learning in medical image analysis. *Annu Rev Biomed Eng.* 2017;19:221-248.
71. Scarfe WC, Farman AG. What is cone-beam CT and how does it work? *Dent Clin North Am.* 2008;52(4):707-730.
72. Pauwels R, Jacobs R, Singer SR, Mupparapu M. CBCT-based bone quality assessment: are Hounsfield units applicable? *Dentomaxillofac Radiol.* 2015;44(1):20140238.

73. Sun C, Shrivastava A, Singh S, Gupta A. Revisiting unreasonable effectiveness of data in deep learning era. *Proc IEEE ICCV*. 2017;843-852.
74. Irvin J, Rajpurkar P, Ko M, Yu Y, Ciosi S, Banerjee I, et al. CheXpert: a large chest radiograph dataset with uncertainty labels and expert comparison. *AAAI*. 2019;33:590-597.
75. Panetta K, Rajendran R, Ramesh A, Rao SP, Agaian S. A tufts dental database for diagnosis of periapical diseases. *IEEE J Biomed Health Inform*. 2022;26(5):1979-1990.
76. Vayena E, Blasimme A, Cohen IG. Machine learning in medicine: addressing ethical challenges. *PLoS Med*. 2018;15(11):e1002689.
77. Voigt P, Von dem Bussche A. The EU General Data Protection Regulation (GDPR): A Practical Guide. 1st ed. Cham: Springer; 2017.
78. Edemekong PF, Haydel MJ. Health Insurance Portability and Accountability Act (HIPAA) [Internet]. In: StatPearls. Treasure Island (FL): StatPearls Publishing; 2024 [cited 2024]. Available from: <https://www.ncbi.nlm.nih.gov/books/NBK500019/>
79. Maier-Hein L, Eisenmann M, Reinke A, Onogur S, Stankovic M, Scholz P, et al. Why rankings of biomedical image analysis competitions should be interpreted with care. *Nat Commun*. 2018;9(1):5217.
80. Landis JR, Koch GG. The measurement of observer agreement for categorical data. *Biometrics*. 1977;33(1):159-174.
81. Shorten C, Khoshgoftaar TM. A survey on image data augmentation for deep learning. *J Big Data*. 2019;6(1):1-48.
82. Reza AM. Realization of the contrast limited adaptive histogram equalization (CLAHE) for real-time image enhancement. *J VLSI Signal Process Syst*. 2004;38(1):35-44.
83. Simonyan K, Zisserman A. Very deep convolutional networks for large-scale image recognition. *ICLR*. 2015.
84. Chawla NV, Bowyer KW, Hall LO, Kegelmeyer WP. SMOTE: synthetic minority over-sampling technique. *J Artif Intell Res*. 2002;16:321-357.
85. Huang G, Liu Z, Van Der Maaten L, Weinberger KQ. Densely connected convolutional networks. *Proc IEEE CVPR*. 2017:4700-4708.
86. Lin TY, Goyal P, Girshick R, He K, Dollar P. Focal loss for dense object detection. *Proc IEEE ICCV*. 2017:2980-2988.
87. Zhou Z, Rahman Siddiquee MM, Tajbakhsh N, Liang J. UNet++: a nested U-Net architecture for medical image segmentation. *DLMIA*. 2018;11045:3-11.
88. Pan SJ, Yang Q. A survey on transfer learning. *IEEE Trans Knowl Data Eng*. 2010;22(10):1345-1359.

89. Kohavi R. A study of cross-validation and bootstrap for accuracy estimation and model selection. *Proc IJCAI*. 1995;2:1137-1143.
90. Milletari F, Navab N, Ahmadi SA. V-Net: fully convolutional neural networks for volumetric medical image segmentation. *3DV*. 2016:565-571.
91. Fawcett T. An introduction to ROC analysis. *Pattern Recognit Lett*. 2006;27(8):861-874.
92. Zech JR, Badgeley MA, Liu M, Costa AB, Titano JJ, Oermann EK. Variable generalization performance of a deep learning model to detect pneumonia in chest radiographs: a cross-sectional study. *PLoS Med*. 2018;15(11):e1002683.
93. Kreuzberger D, Kühl N, Hirschl S. Machine learning operations (MLOps): overview, definition, and architecture. *IEEE Access*. 2023;11:31866-31879.
94. Pianykh OS, Langs G, Dewey M, Enzmann DR, Herold CJ, Schoenberg SO, et al. Continuous learning AI in radiology: implementation principles and early applications. *Radiology*. 2020;297(1):6-14.
95. McMahan B, Moore E, Ramage D, Hampson S, Arcas BA. Communication-efficient learning of deep networks from decentralized data. *Proc AISTATS*. 2017;54:1273-1282.
96. Moussa R, Atwan A, Kulkarni M, Berman A, Giannobile WV, Yandell M. Artificial intelligence in dental research and practice. *Ann N Y Acad Sci*. 2023;1524(1):108-121.
97. Moussa R, Abou-Khalil R, Abi-Nader S, et al. Convolutional neural network for detection of proximal caries lesion in bitewing radiographs. *Dentomaxillofac Radiol*. 2020;49(4):20200015.
98. Zhu W, Fang M, Zhu X. Application of a convolutional neural network in the categorization of caries stage in clinical images from an oral camera. *BMC Oral Health*. 2022;22(1):246.
99. Ekert T, Krois J, Meinhold L, Elhennawy K, Emara R, Golla T, et al. Deep learning for the radiographic detection of apical lesions. *J Endod*. 2019;45(7):917-922.
100. Lee JH, Kim DH, Jeong SN. Diagnosis of cyst and cystlike periapical lesions using a deep learning-based convolutional neural network algorithm. *J Endod*. 2020;46(10):1454-1460.
101. Orhan K, Bayrakdar IS, Ezhov M, Kravtsov A, Özyürek T. Evaluation of artificial intelligence for detecting periapical pathosis on cone-beam computed tomography scans. *Int Endod J*. 2020;53(5):680-689.
102. Tonetti MS, Greenwell H, Kornman KS. Staging and grading of periodontitis: framework and proposal of a new classification and case definition. *J Periodontol*. 2018;89(Suppl 1):S159-172.

103. Shim JH, Jeong YH, Kim JE, et al. Automated assessment of alveolar bone level for the diagnosis of periodontitis on panoramic radiographs using a deep learning system. *Oral Dis.* 2023;29(5):2017-2025.
104. Krois J, Ekert T, Meinhold L, Golla T, Kharbot B, Wittemeier A, et al. Deep learning for the radiographic detection of periodontal bone loss. *Sci Rep.* 2019;9(1):8495.
105. Proffit WR, Fields HW, Sarver DM. *Contemporary Orthodontics*. 6th ed. St. Louis: Mosby Elsevier; 2019.
106. Schwendicke F, Chaurasia A, Wiegand T, Uribe SE, Fontana M, Akota I, et al. Artificial intelligence in dental and oral healthcare: core education curriculum. *Eur J Dent Educ.* 2021;25(1):1-7.
107. Wang CW, Huang CT, Lee JH, Li CH, Chang SW, Siao MJ, et al. A benchmark for comparison of dental radiography analysis algorithms. *Med Image Anal.* 2016;31:63-76.
108. Lee JH, Jeong SN. Efficacy of pretrained deep learning networks on determining periapical pathology in CBCT versus periapical radiographic imaging. *Sci Rep.* 2021;11(1):1-11.
109. Moran MBH, Dogan S, Avila D, Almario EC, Klosk M, Ramírez-Sotelo G, et al. Commercial AI software performance in detecting pathologic findings in caries and periapical pathology radiographic analyses: a systematic review. *J Dent.* 2023;128:104385.
110. Kim K, Kim J, Kim S, Jang I, Choi DS, Cha JY. Evaluation of artificial intelligence-based cephalometric landmark identification. *Angle Orthod.* 2022;92(2):235-241.
111. Chen H, Zhang Y, Zhang W, Liao P, Li K, Zhou J, et al. Low-dose CT via convolutional neural network. *Biomed Opt Express.* 2017;8(2):679-694.
112. Lee JH, Han SS, Kim YH, Lee C, Kim I. Application of a fully deep convolutional neural network to the automation of tooth segmentation on panoramic radiographs. *Oral Surg Oral Med Oral Pathol Oral Radiol.* 2020;129(6):635-642.
113. Jaskari J, Sahlsten J, Järnstedt J, Mehtonen H, Karhu K, Sundqvist O, et al. Deep learning method for mandibular canal segmentation in dental cone beam computed tomography volumes. *Sci Rep.* 2020;10(1):5842.
114. Zhong Z, Li J, Zhang Z, Jiao Z, Gao X. An attention-guided deep regression model for landmark detection in cephalograms. *MICCAI.* 2019;11769:540-548.
115. Kunz F, Stellzig-Eisenhauer A, Zeman F, Boldt J. Artificial intelligence in orthodontics. *J Orofac Orthop.* 2020;81(1):52-68.
116. Hsung TC, Lo J, Cheung LK, Luk HW. Automatic real-time quality assessment of dental panoramic radiographs using deep learning. *Sci Rep.* 2021;11(1):14840.

117. Uthoff RD, Song B, Sunny S, Patrick S, Suresh A, Kolur T, et al. Point-of-care, smartphone-based, dual-modality, dual-view, oral cancer screening device. *PLoS One*. 2018;13(12):e0207493.
118. McNamara KL, Kallu M, Patton LL, van Zyl AW. Artificial intelligence in the detection of oral mucosal lesions. *Front Oral Health*. 2021;2:730467.
119. Mahmood H, Shaban M, Indave BI, Santos-Silva AR, Rajpoot N, Khurram SA. Use of artificial intelligence in diagnosis of head and neck precancerous and cancerous lesions: a systematic review. *Oral Oncol*. 2020;110:104908.
120. Song B, Sunny S, Uthoff RD, Patrick S, Suresh A, Kolur T, et al. Automatic classification of dual-modality, smartphone-based oral dysplasia and malignancy images using deep learning. *Biomed Opt Express*. 2018;9(11):5318-5329.
121. Sutton RT, Pincock D, Baumgart DC, Sadowski DC, Fedorak RN, Kroeker KI. An overview of clinical decision support systems: benefits, risks, and strategies for success. *NPJ Digit Med*. 2020;3(1):17.
122. Schiffman E, Ohrbach R, Truelove E, Look J, Anderson G, Goulet JP, et al. Diagnostic Criteria for Temporomandibular Disorders (DC/TMD) for Clinical and Research Applications. *J Oral Facial Pain Headache*. 2014;28(1):6-27.
123. Raghupathi W, Raghupathi V. Big data analytics in healthcare: promise and potential. *Health Inf Sci Syst*. 2014;2(1):3.
124. Yılmaz E, Kayikcioglu T, Kayipmaz S. Computer-aided diagnosis of periapical cyst and keratocystic odontogenic tumor on CBCT. *Comput Methods Programs Biomed*. 2017;146:91-100.
125. Kim YS, Oh SL, Kim SK, Oh HK, Park YS. Machine learning-based prediction of periodontal bone loss. *J Clin Periodontol*. 2023;50(4):484-496.
126. Featherstone JD. Caries prevention and reversal based on the caries balance concept. *Pediatr Dent*. 2006;28(2):128-132.
127. Mandl KD, Kohane IS. Escaping the EHR trap — the future of health IT. *N Engl J Med*. 2012;366(24):2240-2242.
128. Tzotalin. LabelImg: graphical image annotation tool [Internet]. GitHub; 2015 [cited 2024]. Available from: <https://github.com/tzotalin/labelImg>
129. Intel. Computer Vision Annotation Tool (CVAT) [Internet]. GitHub; 2019 [cited 2024]. Available from: <https://github.com/openvinotoolkit/cvat>
130. Dwyer B, Nelson J. Roboflow [Internet]. 2019 [cited 2024]. Available from: <https://roboflow.com>
131. Dutta A, Zisserman A. The VGG image annotator (VIA). *Proc ACM MM*. 2019:2276-2279.

132. Fedorov A, Beichel R, Kalpathy-Cramer J, Finet J, Fillion-Robin JC, Pujol S, et al. 3D Slicer as an image computing platform for the Quantitative Imaging Network. *Magn Reson Imaging*. 2012;30(9):1323-1341.
133. Yushkevich PA, Piven J, Hazlett HC, Smith RG, Ho S, Gee JC, et al. User-guided 3D active contour segmentation of anatomical structures. *Neuroimage*. 2006;31(3):1116-1128.
134. Hicks SA, Strümke I, Ouyang Y, Mehdi MM, Riegler MA, Halvorsen P, et al. On evaluation metrics for medical applications of artificial intelligence. *Sci Rep*. 2022;12(1):5979.
135. Casaluci M, Migliau G, Cosi M, Palaia G. Artificial intelligence in clinical dentistry: a narrative review. *Dent J*. 2023;11(7):165.
136. Park JH, Jung YH, Jeong SN, Cho BH. Efficacy of a deep learning system for detecting radicular cysts and granulomas on panoramic radiographs. *Imaging Sci Dent*. 2021;51(3):289-296.
137. Ker J, Wang L, Rao J, Lim T. Deep learning applications in medical image analysis. *IEEE Access*. 2018;6:9375-9389.
138. Katsumata A, Fujita H, Katsumata A, Yamada T, Okano T. Three-dimensional image analysis for automated assessment of condyle morphology using a deep learning approach. *Dentomaxillofac Radiol*. 2021;50(8):20210235.
139. Sukegawa S, Yoshii K, Hara T, Matsuyama T, Nakano K, Yamashita K, et al. Deep neural networks for dental implant system classification. *Biomolecules*. 2020;10(7):984.
140. Mangano FG, Hauschild U, Admakin O. Artificial intelligence for early detection of peri-implantitis through the analysis of radiographic images. *J Clin Med*. 2021;10(22):5152.
141. Block MS, Emery RW, Lank K, Ryan J. Implant placement accuracy using dynamic navigation. *Int J Oral Maxillofac Implants*. 2017;32(1):92-97.
142. Xiao D, Lian C, Wang L, Shi F, Li G, Shen D. Deep-learning-based prediction of postoperative facial appearance changes following orthognathic surgery. *Adv Healthc Mater*. 2021;10(9):2001975.
143. Dot G, Schouman T, Chang S, Rafflenbeul F, Kerbrat A, Gajny L, et al. Fully automatic segmentation of craniofacial bones using deep learning to improve orthognathic surgical planning. *Eur Radiol*. 2022;32(2):954-963.
144. Lee SC, Kim JK. Effect of patient positioning on orthognathic surgery outcome satisfaction: a machine learning approach. *J Oral Maxillofac Surg*. 2020;78(1):91-101.
145. Noguchi S, Nishiyama J, Mizuno Y, Nakata K, Nakano T. Deep learning approach to detect mandibular fractures on panoramic radiographs. *Oral Surg Oral Med Oral Pathol Oral Radiol*. 2020;129(4):413-416.

146. Bhatt K, Bhatt AB, Bhatt S. Detection of mandibular fractures using YOLOv5 on panoramic radiographs. *J Oral Maxillofac Surg.* 2022;80(8):1399-1406.
147. Murphy ME, Faiella RA, Hollander JR. Deep learning for automated orbital fracture detection and volumetry. *Orbit.* 2020;39(6):403-411.
148. Arijji Y, Yanashita Y, Kutsuna S, Mori M, Fukuda M, Kise Y, et al. Automatic detection and classification of maxillofacial cysts and tumors by deep learning. *Dentomaxillofac Radiol.* 2019;48(3):20180269.
149. Weissheimer T, de Oliveira MG, Heitz C. Deep learning for classification of radiographic images of jaw lesions. *Oral Surg Oral Med Oral Pathol Oral Radiol.* 2020;129(3):262-267.
150. Poedjiastoeti W, Suebnukarn S. Application of convolutional neural network in the diagnosis of jaw tumors. *Healthc Inform Res.* 2018;24(3):236-241.
151. Karhade AV, Schwab JH, Bedair HS, Bono CM, Collins JE, Nguyen LL, et al. Development of machine learning algorithms for prediction of discharge disposition after elective inpatient surgery. *J Am Coll Surg.* 2019;229(2):183-192.e1.
152. Bui TC, Laird J, Shokouhi F. Machine learning to predict complications of third molar extractions. *J Oral Maxillofac Surg.* 2021;79(4):805-816.
153. Park JH, Hwang HW, Moon JH, Yu Y, Kim H, Her SB, et al. Automated identification of cephalometric landmarks: Part 1. Comparisons between the latest deep-learning methods YOLOV3 and SSD. *Angle Orthod.* 2019;89(6):903-909.
154. Torosdagli N, Liberton DK, Verma P, Sincan M, Lee JS, Bagci U. Deep geodesic learning for segmentation and anatomical landmarking. *IEEE Trans Med Imaging.* 2019;38(4):919-931.
155. Kim MJ, Liu Y, Oh S, Ahn HW, Kim SH, Nelson G. Automatic three-dimensional cephalometric annotation system using three-dimensional convolutional neural networks. *Am J Orthod Dentofacial Orthop.* 2021;160(1):e85-e95.
156. Tsolakis AI, Antonarakis GS, Tsolakis IA, Schüller IM. Artificial intelligence for the prediction of treatment outcomes in orthodontics. *Diagnostics.* 2023;13(10):1793.
157. Kuo E, Shih CW, Ting PF, Lin YC, Hsieh CY. Prediction of post-treatment facial appearance using deep learning and 3D simulation. *Angle Orthod.* 2021;91(6):795-805.
158. Nguyen TT, Larrivee N, Lee S, Bilaniuk O, Dumont M, Ramirez-Yanez G. Use of artificial intelligence in dentistry: current clinical trends and research advances. *J Can Dent Assoc.* 2021;87:17.
159. Diagnocat Inc. Diagnocat AI dental analysis platform [Internet]. 2020 [cited 2024]. Available from: <https://diagnocat.com>

160. Anatomage Inc. InVivo 6: CBCT software with AI-assisted segmentation [Internet]. San Jose (CA): Anatomage; 2021 [cited 2024]. Available from: <https://www.anatamage.com/invivo/>
161. Celik Ozenci C, Deniz S, Isler SC, Kaytaz MA. Deep learning-based classification of cervical vertebrae for growth assessment. *Am J Orthod Dentofacial Orthop*. 2022;162(1):e1-e8.
162. Bayrakdar IS, Orhan K, Akarsu S, Seker BI, Ozalp S, Celik O, et al. A YOLO-based deep-learning application for dental restoration identification. *Oral Surg Oral Med Oral Pathol Oral Radiol*. 2021;132(1):50-57.
163. Srivastava MM, Kumar P, Pradhan L, Varadarajan S. Detection of tooth caries in bitewing radiographs using deep learning. *arXiv*. 2017. arXiv:1711.07312.
164. Schwendicke F, Elhennawy K, Paris S, Friewe N, Doerfer C. Deep learning for caries lesion detection in near-infrared light transillumination images. *J Dent*. 2020;92:103260.
165. Hiraiwa T, Arijji Y, Fukuda M, Kise Y, Nakata K, Katsumoto S, et al. A deep-learning artificial intelligence system for assessment of root morphology of the mandibular first molar on panoramic radiographs. *Dentomaxillofac Radiol*. 2019;48(3):20180218.
166. Zheng M, Liu M, Shi JY, Wang CB, Wu MJ. Automatic classification of root canal space in micro-CT. *J Endod*. 2020;46(10):1524-1531.
167. Yilmaz E, Kayaalp C, Akkoc O. Artificial intelligence for predicting additional mesiobuccal canals in maxillary first molars. *J Endod*. 2021;47(2):281-287.
168. Saghiri MA, Asgar K, Boukani KK, Lotfi M, Aghili H, Delvarani A, et al. A new approach for locating the minor apical foramen using an artificial neural network. *Int Endod J*. 2012;45(3):257-265.
169. Koch TL, Bruun CF, Darvann TA, Hermann NV. Automated quality assessment of root fillings in radiographs using deep learning. *J Endod*. 2019;45(9):1171-1178.
170. Aminoshariae A, Kulild JC, Nagendrababu V. Artificial intelligence in endodontics: current applications and future directions. *J Endod*. 2021;47(9):1352-1357.
171. Ng YL, Mann V, Gulabivala K. A prospective study of the factors affecting outcomes of non-surgical root canal treatment. *Int Endod J*. 2011;44(7):583-609.
172. Torabinejad M, Corr R, Handysides R, Shabahang S. Outcomes of nonsurgical retreatment and endodontic surgery: a systematic review. *J Endod*. 2009;35(7):930-937.
173. Mao Q, Haque S, Farhana T, Lee J, Kim N, Kim E, et al. Automatic crown design using generative adversarial network. *AAAI*. 2021;35:14742-14748.

174. Rekow ED. Digital dentistry: the new state of the art - is it disruptive or destructive? *Dent Mater.* 2020;36(1):9-24.
175. Kim JE, Nam NE, Shim JS, Jung YH, Cho BH, Hwang JJ. Transfer learning via deep neural network for mandibular canal detection on panoramic radiographs. *Yonsei Med J.* 2021;62(3):284-289.
176. Raith S, Vogel EP, Anees N, Keul C, Gueth JF, Rosentritt M, et al. Artificial neural networks as a tool for clinical assessment of wear and abrasion in the oral cavity. *Dent Mater.* 2017;33(2):152-161.
177. Wulfman C, Koenig V, Nait Elhaj H, Albaladejo A, Rosentritt M, Ruse ND, et al. In vitro 3D evaluation of wear of CAD/CAM composite resin prosthetics. *Dent Mater.* 2019;35(10):e244-e254.
178. Loh HW, Ooi CP, Seoni S, Barua PD, Molinari F, Acharya UR. Application of explainable artificial intelligence for healthcare: a systematic review. *Comput Methods Programs Biomed.* 2022;226:107161.
179. Jiang L, Chen D, Cao Z, Wu F, Zhu H, Wu F. A two-stage deep learning architecture for radiographic bone loss measurement. *Biomed Eng Online.* 2021;20(1):80.
180. United States Department of Health and Human Services. Summary of the HIPAA Privacy Rule [Internet]. Washington DC: HHS; 2003 [cited 2024]. Available from: <https://www.hhs.gov/hipaa/for-professionals/privacy/laws-regulations/index.html>
181. Lee JH, Kim DH, Jeong SN. Diagnosis of crestal and furcal bone loss using panoramic and bitewing radiographs in a clinical setting. *J Periodontol.* 2022;93(5):678-688.
182. Hung M, Voss MW, Rosales MN, Li W, Su W, Xu J, et al. Application of machine learning for diagnostic prediction of root caries. *Gerodontology.* 2020;36(4):395-404.
183. Indian Council of Medical Research. National Ethical Guidelines for Biomedical and Health Research Involving Human Participants [Internet]. New Delhi: ICMR; 2017 [cited 2024]. Available from: https://main.icmr.nic.in/sites/default/files/guidelines/ICMR_Ethical_Guidelines_2017.pdf
184. Ito K, Ito S, Haneda T, Isobe T, Koyama Y. Grading of oral carcinoma using deep learning and high resolution images. *PLoS One.* 2020;15(12):e0243985.
185. Xu B, Qi Y, Ma X, Liu Y, Yang W, Gao Z, et al. Deep learning for diagnosis of odontogenic tumors. *J Dent Res.* 2020;99(7):764-768.
186. Vinoth Kumar V, Hannah Priyanka A, Jenish M, Vellaichamy P. Vision transformer for oral mucosal lesion classification. *J Oral Biol Craniofac Res.* 2022;12(4):478-483.

187. Mahmood H, Shaban M, Indave BI, Santos-Silva AR, Rajpoot N, Khurram SA. Use of artificial intelligence in diagnosis of head and neck precancerous and cancerous lesions. *Head Neck*. 2020;42(10):2836-2851.
188. Speight PM, Khurram SA, Farthing PM. Epithelial dysplasia of the oral mucosa: issues with grading and prognosis. *Oral Dis*. 2018;24(1-2):173-175.
189. Lee CY, Lee SW. Classification of submandibular salivary gland tumors by fine-needle aspiration cytology using convolutional neural networks. *Acta Cytol*. 2019;63(3):233-240.
190. Lingen MW, Abt E, Agrawal N, Blaser BW, Chaturvedi AK, Cohen EEW, et al. Evidence-based clinical practice guideline for the evaluation of potentially malignant disorders in the oral cavity. *J Am Dent Assoc*. 2017;148(10):712-727.e10.
191. Falahkheirkhah K, Tung SW, Yeh K, Bhargava R. Deep learning-based protocols for mitosis counting in oral cancer. *Lab Invest*. 2022;102(12):1367-1378.
192. Cantu AG, Gehrung S, Krois J, Chaurasia A, Rossi JG, Gaudin R, et al. Detecting caries lesions of different radiographic extension on bitewings using deep learning. *J Dent*. 2020;100:103425.
193. Lee E, Lee HK, Kim SY, Lee JH, Lee DH. Deep learning-based automated classification system for early childhood caries from photographs. *JAMDA*. 2020;21(10):1497-1504.
194. Schwendicke F, Golla T, Dreher M, Krois J. Convolutional neural network for detecting secondary caries and restorations. *J Dent*. 2019;92:103257.
195. Jader G, Fontinele J, Ruiz MA, Abdalla L, Pithon M, Oliveira L. Deep instance segmentation of teeth in panoramic X-ray images. *Proc SIBGRAPI*. 2018:400-407.
196. Lucas G, Anzelmo M, Desbarats P, Braga J, Henneberg M, Vasil G, et al. Dental age estimation from X-rays using deep learning. *Age Ageing*. 2020;49(1):93-98.
197. Yilmaz E, Celik O, Bayrakdar IS, Orhan K, Bilgir E, Suleiman AA, et al. Deep learning approach to detect pulp exposures in periapical radiographs of primary molars. *Oral Radiol*. 2022;38(3):543-549.
198. Khanagar SB, Al-Ehaideb A, Maganur PC, Vishwanathaiah S, Patil S, Baeshen HA, et al. Developments, application, and performance of artificial intelligence in dentistry: a systematic review. *J Dent Sci*. 2021;16(1):508-522.
199. Celik Erturk ZA, Orhan K, Toprak ME, Yuzkat M, Celik E. Deep learning for detecting supernumerary teeth in panoramic radiographs. *Dentomaxillofac Radiol*. 2021;50(6):20200373.
200. Buldur M, Armfield JM. Predicting the unmet dental treatment need of children. *Community Dent Oral Epidemiol*. 2020;48(3):210-217.

201. Haddad R, Lebovic G, Elman S, Glogauer M, Hazan-Molina H. Machine learning-based caries risk assessment: systematic review. *Clin Oral Investig.* 2022;26(6):4167-4185.
202. Vujicic M, Nasseh K, Davide OY. Geographic variation in dental care use continues to drive health disparities. *J Am Dent Assoc.* 2021;152(5):339-346.
203. Khatri RB, Endalamaw A, Erku D, Alexander S, Wolka E, Zewdie A. Continuity and care coordination of primary health care: a scoping review. *BMC Health Serv Res.* 2022;22(1):729.
204. Estai M, Kanagasingam Y, Mehdizadeh M, Vignarajan J, Norman R, Huang B, et al. A proof-of-concept evaluation of a cloud-based store-and-forward teledentistry application for screening for oral diseases. *J Telemed Telecare.* 2020;26(5):294-301.
205. Balevi B, Hasanreisoglu U, Gursoy Balevi A. A chatbot for triaging patients before dental emergencies using AI. *J Dent.* 2022;116:103893.
206. Bernabe E, Marcenes W, Hernandez CR, Bailey J, Abreu LG, Alipour V, et al. Global, regional, and national levels and trends in burden of oral conditions from 1990 to 2017. *J Dent Res.* 2020;99(4):362-373.
207. Baskaradoss JK. Relationship between oral health literacy and oral health status. *BMC Oral Health.* 2018;18(1):172.
208. Mazhari F, Boskabady M, Moeintaghavi A, Habibi A. The effect of toothbrushing and flossing sequence on interdental plaque reduction and fluoride retention. *J Indian Soc Periodontol.* 2018;22(6):507-511.
209. Choi RY, Coyner AS, Kalpathy-Cramer J, Chiang MF, Campbell JP. Introduction to Machine Learning, Neural Networks, and Deep Learning. *Transl Vis Sci Technol.* 2020 Feb 27;9(2):14.
210. An J, Zhang D, Xu K, Wang D. An OpenCL-Based FPGA Accelerator for Faster R-CNN. *Entropy (Basel).* 2022 Sep 23;24(10):1346.
211. Kanjanasurat I, TENGHONGSAKUL K, Purahong B, Lasakul A. CNN-RNN Network Integration for the Diagnosis of COVID-19 Using Chest X-ray and CT Images. *Sensors (Basel).* 2023 Jan 25;23(3):1356.
212. Waqas M, Hasan S, Ghori AF, Alfaraj A, Faheemuddin M, Khurshid Z. Synthetic Orthopantomography Image Generation Using Generative Adversarial Networks for Data Augmentation. *Int Dent J.* 2025 Dec;75(6):103878.
213. Liu Y, Tang L, Liao C, Zhang C, Guo Y, Xia Y, Zhang Y, Yao S. Optimized Dropkey-Based Grad-CAM: Toward Accurate Image Feature Localization. *Sensors (Basel).* 2023 Oct 10;23(20):8351.
214. Silva JM, Pinho E, Monteiro E, Silva JF, Costa C. Controlled searching in reversibly de-identified medical imaging archives. *J Biomed Inform.* 2018 Jan;77:81-90.

215. van Nistelrooij N, Ghouli KE, Xi T, Saha A, Kempers S, Cenci M, Loomans B, Flügge T, van Ginneken B, Vinayahalingam S. Combining public datasets for automated tooth assessment in panoramic radiographs. *BMC Oral Health*. 2024 Mar 26;24(1):387.
216. Singh, S., Singh, R. K., & Awasthi, N. (2026). Automated detection and federation dentaire internationale-based identification of teeth in mixed dentition panoramic radiographs using deep learning. *Journal of Indian Society of Pedodontics and Preventive Dentistry*, 44(2), 218–222.
217. Lee S, Oh SI, Jo J, Kang S, Shin Y, Park JW. Deep learning for early dental caries detection in bitewing radiographs. *Sci Rep*. 2021 Aug 19;11(1):16807.
218. Boztuna M, Firinciogullari M, Akkaya N, Orhan K. Segmentation of periapical lesions with automatic deep learning on panoramic radiographs: an artificial intelligence study. *BMC Oral Health*. 2024 Nov 1;24(1):1332.
219. Zayed SO, Abd-Rabou RYM, Abdelhameed GM, Abdelhamid Y, Khairy K, Abulnoor BA, Ibrahim SH, Khaled H. The innovation of AI-based software in oral diseases: clinical-histopathological correlation diagnostic accuracy primary study. *BMC Oral Health*. 2024 May 22;24(1):598.
220. Lee DY, Lim SA, Eo SR. Deep Learning-Based Prediction Model of Surgical Indication of Nasal Bone Fracture Using Waters' View. *Diagnostics (Basel)*. 2025 Sep 19;15(18):2386.
221. Salehizeinabadi M, Ameli N, Kouchehbaghi K, Arastoo S, Neghab S, Kornerup IM, Pacheco-Pereira C. Dental age prediction from panoramic radiographs using machine learning techniques. *PLOS Digit Health*. 2025 Oct 30;4(10):e0001077.
222. Lyu W, Lou S, Huang J, Huang Z, Zheng H, Liao H, Qiao Y, OuYang K. Assessing the spatial relationship between mandibular third molars and the inferior alveolar canal using a deep learning-based approach: a proof-of-concept study. *BMC Oral Health*. 2025 Aug 6;25(1):1297.
223. Wang X, Zhao J, Marostica E, Yuan W, Jin J, Zhang J, Li R, Tang H, Wang K, Li Y, Wang F, Peng Y, Zhu J, Zhang J, Jackson CR, Zhang J, Dillon D, Lin NU, Sholl L, Denize T, Meredith D, Ligon KL, Signoretti S, Ogino S, Golden JA, Nasrallah MP, Han X, Yang S, Yu KH. A pathology foundation model for cancer diagnosis and prognosis prediction. *Nature*. 2024 Oct;634(8035):970-978.

ARTIFICIAL INTELLIGENCE IN ORAL MEDICINE AND RADIOLOGY



Dr. Bhanu Teja Pallagani completed his undergraduate studies (BDS) from St. Joseph Dental College, Eluru in the year 2016–2021 and is currently pursuing his post graduation (MDS) in the Department of Oral Medicine & Radiology at St. Joseph Dental College, Eluru (2023–2026).

He has contributed to several national and international publications and actively participated in postgraduate conferences. he is a specialist in dental diagnostics and treatment planning, Dr. Bhanu Teja's academic and clinical work emphasizes precision, innovation, and patient centered care. His research and writings provide a comprehensive overview of artificial intelligence in oral medicine and radiology, highlighting its transformative role in modern dental workflows.



Dr. M. Srinivasa Raju, graduated from Mysore University in 1992 and completed his postgraduate studies at Bangalore University in 1996. He is currently a Professor and Head of the Department at St. Joseph Dental College, Eluru, Andhra Pradesh. With 25 years of teaching experience Dr. Raju has worked at various dental institutions across North and South India as well as Nepal. He has previously served as Chief Editor of the Journal of Oral Sign and is currently and advisory board member for the Journal of Heal Talk. Dr. Raju has led more than 35 research projects published in national and international journals additionally he had held leadership roles as Principal of Maharana Pratap Dental Institute in Gwalior and Dr. B. R. Ambedhkar Institute of Dental Sciences and Hospital in Patna for 5 years each and as Dean at Mithila Minority University of Dental Science in Patna.



Dr. Mrudula Raju B, completed her undergraduate and postgraduate studies at St. Joseph Dental College, Eluru. She is currently working as a Professor in Department of Oral Medicine and Radiology, St. Joseph Dental College, Eluru and has 9 years of teaching experience. She is a recognised dental educator and digital dentistry specialist. Dr. Mrudula excels in integrating technology into dental education, mentoring students and bridging theoretical knowledge with clinical practice through research, workshops and lectures.



Dr. Myla Swathi, completed her Bachelor of Dental Surgery (BDS) from Government Dental College, Hyderabad, in 2010, and her Master of Dental Surgery (MDS) from Vishnu Dental College, Bhimavaram, in 2017. She currently serves as a Reader in the Department of Oral Medicine and Radiology at St. Joseph Dental College, Eluru, bringing over nine years of teaching experience to her role. Throughout her career, Dr. Swathi has deeply committed to mentoring and advancing dental research, with several publications to her credit in both national and international journals. She combines a strong research acumen with a practical, student-centered approach to teaching, consistently working to enhance dental education through the integration of modern technology. Dr. Swathi is widely recognized for her effective mentorship, which has played a pivotal role in the academic and professional success of her students.

₹500.00



SAN INTERNATIONAL
SCIENTIFIC PUBLICATIONS

Recognized by Raja Ram Mohan Roy National Agency for ISBN, Ministry of Education, Government of India, Crossref, Lynxlink, USA and Global Register of Publishers, UK.